

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

2006 JUL 24 AM 3 49

1. **Type of Well**  
Gas

2. **Name of Operator**

**ConocoPhillips**

3. **Address & Phone No. of Operator**

PO. Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**

Unit G (SWNE), 2200' FNL &amp; 1600' FEL, Sec. 7, T29N, R5W, NMPM

RECEIVED

070 FARMINGTON NM

5. **Lease Number**  
NMSF-078277

6. **If Indian, All. or  
Tribe Name**

7. **Unit Agreement Name**

San Juan 29-5 Unit

8. **Well Name & Number**

San Juan 29-5 Unit 7B

9. **API Well No.**

30-039-29332

10. **Field and Pool**

Blanco Mesa Verde

11. **County and State**

Rio Arriba Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA****Type of Submission****Type of Action**☐ Notice of Intent☐ Abandonment☐ Change of Plans☒ Other - Casing Report☒ Subsequent Report☐ Recompletion☐ New Construction☐ Final Abandonment☐ Plugging☐ Non-Routine Fracturing☐ Casing Repair☐ Water Shut off☐ Altering Casing☐ Conversion to Injection**13. Describe Proposed or Completed Operations**

7/3/06 RIH w/8 3/4" bit @ TOC @ 172'. D/O cement and drill ahead to 3809'. Circ hole. RIH w/48 jts 7", 20#, J-55 ST&C casing and set @ 3762. Circ. hole. Pump preflush 20 bbls gel water/dye. Pump Lead 420 sx (1096 cf - 195 bbls slurry) Class G, w/3% DO79, 0.2% D20, .2%D20, .2%D46, 1.0 #/bbl Cemnet. Tail 235 sx (293 cf - 52 bbls slurry) 50/50 POZ, Class G, w/2% D20, .2%D46, 2% S-001, 5# sx D24, .015%D65, 1.0 # bbl Cemnet. Dropped plug and displaced w/150 bbls FW. Bumped plug w/1850#. Circ. 70 bbls cement to surface. WOC. PT casing to 1800#/30 mins. OK

7/9/06 RIH w/6 1/4" bit TOC @ 3746'. D/O cement and drill ahead to 5985'. Circ. hole. RIH w/140 jts 4.5", 20<sup>10.5</sup>#, J-55 ST&C casing and set @ 5956'. Circ. hole. Pump 10/10/10 preflush ahead of 260 sx (375 cf - 66.7 bbls slurry) 50/50 POZ, Class G, .25#/sx DO29, 3.0% DO20, 1.0#/sx DO24, .25%D167, .015%DO65, 0.10%D800, 0.10% DO46, 3.5#/sx. Dropped Plug and displaced till caught cement. Bump plug w/1670#. ND BOP. PU stack & set slips, cut off casing. Install trash cap. RD release rig 7/15/06

PT will be conducted by the completion rig & results will be shown on the next report. TOC will also be reported.

**14. I hereby certify that the foregoing is true and correct.**

Signed



Rhonda Rogers

Title Regulatory Assistant

Date 7/20/06

(This space for Federal or State Office use)

APPROVED BY

Title

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

ACCEPTED FOR RECORD

AUG 01 2006

FARMINGTON FIELD OFFICE

NMCCD