

Submit 3 Copies To Appropriate District Office  
District I  
1625 N. French Dr., Hobbs, NM 88240  
District II  
1301 W. Grand Ave., Artesia, NM 88210  
District III  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised May 08, 2003

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO.  
30-45-31592

5. Indicate Type of Lease  
STATE ☐ FEE ☒  
State Oil & Gas Lease No.

Lease Name or Unit Agreement Name  
MONTROYA 27

8. Well Number  
2

9. OGRID Number  
9812

10. Pool name or Wildcat  
BASIN FRUITLAND COAL

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG OR ABANDON A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-104) FOR SUCH PROPOSALS.)

1. Type of Well:  
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator  
HEC PETROLEUM, INC.

3. Address of Operator  
463 TURNER DRIVE #101, DURANGO, CO 81303

4. Well Location  
Unit Letter   M   :   705   feet from the   SOUTH   line and   1210   feet from the   WEST   line  
Section   27   Township   32N   Range   13W   NMPM County   SAN JUAN  

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
5904"

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SPUD 12 1/4" HOLE 5/9/03 7D - 357' RAN 8 JTS 8 5/8 24# J-55 CSG SET @ 356' CMT BY AMERICAN / W 300 SX "B" TESTED BOPE 600 PSI BOTH SIDES OK. DRILLED 7 7/8" HOLE TO TD 2215 FT. RAN SCHLUMBERGER TRIPLE LITHO DENSITY GR LOGS, RAN 5 1/2" 15.5, J-FF CSG SET @ 2210 FT. CMT BY BJ SERVICES WITH 470 SX PREM LITE CIR 32 BBLS TO PIT. PRESSURE TEST CSG TO 1000 PSI OK.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jim Bonaventura TITLE Area Production Foreman DATE 7/10/03

Type or print name Jim Bonaventura Telephone No. 970/259-1374

(This space for State use)

APPROVED BY Charles L. [Signature] TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 3 DATE JUL 17 2003

Conditions of approval, if any: