Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED OMB NO. 1004-0135 Expires: November 30, 2000

NMSF0079047

| SUNDRY | NOTICES | AND | REPORTS | ON | WELLS |
|--------|---------|-----|----------------|----|-------|
|--------|---------|-----|----------------|----|-------|

16. If Indian, Allottee or Tribe Name

| abandoned well. Use For | ກ 3160-3 (APD) for sເ | ich proposa | JIII 2 | an, Anottee of Trice Name | | |
|---|--|--|---|--|--|--|
| SUBMIT IN TRIPLICATE - | Other instructions o | n reverse side O/L | COMO D 7. In Unit | t or CA/Agreement, Name and/or No | | |
| 1. Type of Well Oil Well X Gas Well Other | | | TOT STV. ST | Name and No. | | |
| 2. Name of Operator ConocoPhillips Company | | | S 7 E 7 SJ 32-8 | 3 Unit #243A | | |
| 3a. Address 5525 Highway 64, NBU 3004, Farmingt | | 20. Phone No. (include area code) 30 - 045 - 31666 - 00 - X1 10. Field and Pool, or Exploratory Area | | | | |
| Location of Well (Footage, Sec., T., R., M., or Survey I Unit F, (SENW) 2115' FNL & 1365' FW Section 11, T31N, R8W | | | | ruitland Coal ty or Parish, State | | |
| 12. CHECK APPROPRIATE | BOX(ES) TO INDIC | ATE NATURE OF | | | | |
| TYPE OF SUBMISSION | TYPE OF ACTION | | | | | |
| Notice of Intent X Subsequent Report | Acidize Alter Casing | Deepen Fracture Treat | Production (Start/Resun | Water Shut-Off Well Integrity | | |
| Final Abandonment Notice | Casing Repair Change Plans Convert to Injection | New Construction Plug and Abandon Plug Back | Recomplete Temporarily Abandon Water Disposal | 7" casing report | | |
| Describe Proposed or Completed Operation (clearly If the proposal is to deepen directionally or recomp Attach the Bond under which the work will be per following completion of the involved operations. I testing has been completed. Final Abandonment N determined that the final site is ready for final inspect 7/6/03 RIH w/8-3/4" bit & tagged RIH w/7", 20#, J-55 casing and se w/dye in last 10 bbls. Pumped Le 0.25#/sx Cellophane, & 0.2% Antif w/2% gel, 5#/sx Gilsonite, 2% BWO displaced plug w/130 bbls FW. Busurface. RD Schlumberger. ND BO hrs 7/9/02. Will report casing P | lete horizontally, give subsiformed or provide the Bon f the operation results in a Notices shall be filed only action.) cement @ 179'. [t @ 3268'. RU Schad - 415 sx (1083.oam. Tail - Pumpe C CaCl2, 0.25#/sx mped plug w/1490 pP, PU stack. Set | urface locations and meand No. on file with BLM multiple completion or rufter all requirements, incompletion of the completion of the comp | sured and true vertical depths /BIA. Required subsequent recompletion in a new interval cluding reclamation, have been deformation to 327. ment. Pumped a presol slurry) Class G v f - 22.5 bbl slurry2% Antifoam. Relea /8/03. Circ. 22 bbl: | of all pertinent markers and zones. eports shall be filed within 30 days, a Form 3160-4 shall be filed once in completed, and the operator has 1'. Circ. hole. flush of 30 bbls FW w/3% extender, 0 50/50 Class G POZ ased wiper plug and s good cement to | | |
| 14. I hereby certify that the foregoing is true and correct Name (Printed/Typed) | | Title | | | | |
| | Patsy Clugston | 1 | <u>Administrative Assi</u> | stant | | |
| Talsy Cuest | SPACE FOR FEDER | Date 7/8/03 | | ACCEPTED FOR RECORD | | |
| Approved by | | Title | | Date JUL 1 6 2003 | | |

Office