

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL, DEEPEN, OR PLUG BACK

1a. Type of Work DRILL	5. Lease Number NMSF-078146 Unit Reporting Number 070 FARMINGTON NM	
1b. Type of Well GAS	6. If Indian, All. or Tribe	
2. Operator ConocoPhillips	7. Unit Agreement Name	
3. Address & Phone No. of Operator PO Box 4289, Farmington, NM 87499 (505) 326-9700	8. Farm or Lease Name 9. Well Number Newberry A #2M	
4. Location of Well Unit D (NWNW), 810' FNL & 760' FWL, Latitude 36° 91858'N Longitude 108° 10738'W	10. Field, Pool, Wildcat Blanco MV / Basin DK 11. Sec., Twn. Rge. Mer. (NMPM) Sec. 9, T31N, R12W API # 30-045- 33879	
14. Distance in Miles from Nearest Town	12. County San Juan	13. State NM
15. Distance from Proposed Location to Nearest Property or Lease Line 760	17. Acres Assigned to Well MV & DK 320.0 - W/2	
16. Acres in Lease	18. Distance from Proposed Location to Nearest Well, Drlg, Compl, or Applied for on this Lease	
19. Proposed Depth 7222'	20. Rotary or Cable Tools Rotary	
21. Elevations (DF, FT, GR, Etc.) 6071' GL	22. Approx. Date Work will Start	
23. Proposed Casing and Cementing Program See Operations Plan attached		
24. Authorized by: <u>Peter C. Clug</u> Sr. Regulatory Analyst	Date <u>8/1/06</u>	

PERMIT NO.

APPROVAL DATE

APPROVED BY [Signature]

TITLE

Acting AFM

DATE

8/1/06

Archaeological Report submitted

Environmental Assessment was submitted.

NOTE: This format is issued in lieu of U.S. BLM Form 3160-3

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or presentations as to any matter within its jurisdiction.

DRILLING OPERATIONS AUTHORIZED ARE
SUBJECT TO COMPLIANCE WITH ATTACHED
"GENERAL REQUIREMENTS".

This action is subject to technical and
procedural review pursuant to 43 CFR 8100.8
and appeal pursuant to 43 CFR 8100.4

District I
PO Box 1980, Hobbs, NM 88241-1980

District II
PO Drawer DD, Artesia, NM 88211-0719

District III
1000 Rio Brazos Rd., Aztec, NM 87410

District IV
PO Box 2088, Santa Fe, NM 87504-2088

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form O-102
Revised February 21, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 4 Copies
Fee Lease - 3 Copies

☐ AMENDED REPORT

WELL LOCATION AND ACREAGE DEDICATION PLAT

*API Number 30-045-33879		*Pool Code 72319 / 71599	*Pool Name BLANCO MESAVERDE / BASIN DAKOTA
*Property Code 31840	*Property Name NEWBERRY A		*Well Number 2M
*OGRID No. 217817	*Operator Name CONOCOPHILLIPS COMPANY		*Elevation 6071'

¹⁰ Surface Location

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
0	9	31N	12W		810	NORTH	760	WEST	SAN JUAN

¹¹ Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Idn	Feet from the	North/South line	Feet from the	East/West line	County
¹² Dedicated Acres 320.0 Acres - W/2 (MV) 320.0 Acres - W/2 (DK)					¹³ Joint or Infill	¹⁴ Consolidation Code	¹⁵ Order No.		

NO ALLOWABLE WILL BE ASSIGNED TO THIS COMPLETION UNTIL ALL INTERESTS HAVE BEEN CONSOLIDATED
OR A NON-STANDARD UNIT HAS BEEN APPROVED BY THE DIVISION

<p>LAT: 36.91858°N LONG: 108.10738°W DATUM: NAD83</p> <p>5288.58'</p> <p>5279.34'</p> <p>5211.36'</p> <p>5307.06'</p> <p>760'</p> <p>810'</p> <p>LEASE USA SF-078146</p>	<p>¹⁷ OPERATOR CERTIFICATION</p> <p>I hereby certify that the information contained herein is true and complete to the best of my knowledge and belief</p> <p><i>Virgil E. Chavez</i></p> <p>Signature Virgil E. Chavez</p> <p>Printed Name Projects & Operations Lead</p> <p>Title</p> <p>Date <u>June 28, 2006</u></p>
	<p>¹⁸ SURVEYOR CERTIFICATION</p> <p>I hereby certify that the well location shown on this plat was plotted from field notes of actual surveys made by me or under my supervision, and that the same is true and correct to the best of my belief</p> <p>Survey Date: JANUARY 30, 2006</p> <p>Signature and Seal of Professional Surveyor</p> <p> JASON C. EDWARDS Certificate Number 15269</p>

Submit 3 Copies To Appropriate District Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Ave., Artesia, NM 88210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103

May 27, 2004

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO.	30-045- 33879
5. Indicate Type of Lease	STATE <input type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	Federal Lease - SF-078146
7. Lease Name or Unit Agreement Name	Newberry A
8. Well Number	#2M
9. OGRID Number	217817
10. Pool name or Wildcat	Blanco Mesaverde / Basin DK

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
ConocoPhillips Company

3. Address of Operator
3401 E. 30TH STREET, FARMINGTON, NM 87402

4. Well Location
Unit Letter D : 810' feet from the North line and 760' feet from the West line
Section 9 Township 31N Rng 12W NMPM County San Juan

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
6071' GL

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type New Drill Depth to Groundwater > 100' Distance from nearest fresh water well > 1000' Distance from nearest surface water > 1000'

Pit Liner Thickness: 12 mil Below-Grade Tank: Volume bbls; Construction Material

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>	PLUG AND ABANDON	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>	CHANGE PLANS	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	MULTIPLE COMPL	<input type="checkbox"/>
OTHER:	<input checked="" type="checkbox"/> New Drill		

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input type="checkbox"/>	P AND A	<input type="checkbox"/>
CASING/CEMENT JOB	<input type="checkbox"/>		
OTHER:	<input type="checkbox"/>		

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

We are constructing Drilling and workover pits as per our General plan on file with the OCD dated June 2005 and we are closing all pits as per the November 1, 2004 Guidelines.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☒ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Patsy Clugston TITLE Sr. Regulatory Specialist DATE 6/29/2006

Type or print name Patsy Clugston E-mail address: plclugston@br-inc.com Telephone No. 505-326-9518
For State Use Only





APPROVED BY [Signature] TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 3 DATE AUG 16 2006
Conditions of Approval (if any):

**CONOCOPHILLIPS COMPANY NEWBERRY A #2M
810' FNL & 760' FWL, SECTION 9, T31N, R12W, NMPM
SAN JUAN COUNTY, NEW MEXICO ELEVATION: 6071'**

**LATITUDE: 36.91858° N
LONGITUDE: 108.10738° W
DATUM: NAD1983**

PLAT NOTE:

SURFACE OWNER
Bureau of Land
Management



PROJECT PROPOSAL - New Drill / Sidetrack

San Juan Business Unit

NEWBERRY A 2M

Lease:		AFE #: WAN.CNV.6145		AFE \$:	
Field Name: NEW MEXICO-NORTH	Rig: 486-0597	State: NM	County: SAN JUAN	API #:	
Geoscientist: Glaser, Terry J	Phone: (832)486-2332	Prod. Engineer: Piotrowicz, Greg M.	Phone: +1 832-486-3486		
Res. Engineer: Tomberlin, Timothy A	Phone: (832) 486-2328	Proj. Field Lead: Fransen, Eric E.	Phone:		

Primary Objective (Zones):

Zone	Zone Name
R20002	MESAVERDE(R20002)
R20076	DAKOTA(R20076)

Location: Surface		Datum Code: NAD 27		Straight Hole	
Latitude: 36.918580	Longitude: -108.107380	X:	Y:	Section: 9	Range: 12W
Footage X: 760 FWL	Footage Y: 810 FNL	Elevation: 6071	(FT)	Township: 31N	
Tolerance:					

Location Type: Year Round	Start Date (Est.):	Completion Date:	Date In Operation:
Formation Data: Assume KB = 6087 Units = FT			

Formation Call & Casing Points	Depth (TVD in Ft)	SS (Ft)	Depletion (Yes/No)	BHP (PSIG)	BHT	Remarks
Surface Casing	216	5871	<input type="checkbox"/>			12-1/4 hole. 9 5/8" 32.3 ppf, H-40, STC casing. Circulate cement to surface.
OJAM	1387	4700	<input type="checkbox"/>			Possible water flows.
KRLD	1607	4480	<input type="checkbox"/>			
FRLD	2067	4020	<input type="checkbox"/>			Possible gas.
PCCF	2417	3670	<input type="checkbox"/>			
LEWS	2617	3470	<input type="checkbox"/>			
Intermediate Casing	2717	3370	<input type="checkbox"/>			8 3/4" Hole. 7", 20 ppf, J-55, STC Casing. Circulate cement to surface.
CHRA	3627	2460	<input type="checkbox"/>			
CLFH	4187	1900	<input type="checkbox"/>			Gas; possibly wet
MENF	4307	1780	<input type="checkbox"/>			Gas.
PTLK	4827	1260	<input type="checkbox"/>			Gas.
MNCS	5077	1010	<input type="checkbox"/>			
GRHN	6872	-785	<input type="checkbox"/>			Gas possible, highly fractured
TWLS	7012	-925	<input type="checkbox"/>			Gas
PAGU	7072	-985	<input type="checkbox"/>			Gas. Highly Fractured.
Total Depth	7222	-1135	<input type="checkbox"/>			6 1/4" hole possibly underreamed to 9.5". Optional Liner: 5 1/2", 15.5#, J-55 LTC, left uncemented.

Reference Wells:

Reference Type	Well Name	Comments
----------------	-----------	----------

See APD cement
calculation page for
production string, size,
weight & grade.

PROJECT PROPOSAL - New Drill / Sidetrack

NEWBERRY A 2M

Logging Program:Intermediate Logs: ☐ Log only if show ☐ GR/ILD ☐ Triple ComboTD Logs: ☐ Triple Combo ☐ Dipmeter ☐ RFT ☐ Sonic ☐ VSP ☒ TDT**Additional Information:**

Log Type	Stage	From (Ft)	To (Ft)	Tool Type/Name	Remarks
----------	-------	-----------	---------	----------------	---------

Comments:

HOLE: 12.25 "
CSG OD: 9.625 "
CSG ID: 9.001 "
WGT: 32.3 ppf
GRADE: H-40
EXCESS: 125 %
DEPTH: 235'

SURFACE:
Option 1
148 sx
30.8 bbls
172.9 cuft
1.17 ft³/sx
15.8 ppg
4.973 gal/sx
Class G Cement
+ 3% S001 Calcium Chloride
+ 0.25 lb/sx D029 Cellophane Flakes

Option 2
143 sx
30.8 bbls
172.9 cuft
1.21 ft³/sx
15.6 ppg
5.29 gal/sx
Standard Cement
+ 3% Calcium Chloride
+ 0.25 lb/sx Flocele

Comp. Strength
6 hrs 250 psi
8 hrs 500 psi

Option 3
65 sx
18.6 bbls
104.3 cuft
1.61 ft³/sx
14.5 ppg
7.41 gal/sx
Type I-II Ready Mix
+ 20% Fly Ash

Comp. Strength
8 hrs 475 psi
24 hrs 1375 psi

INTERMEDIATE LEAD:

Option 1
283 sx
137.1 bbls
769.9 cuft
2.72 ft³/sx
11.7 ppg
15.74 gal/sx
Class G Cement
+ 3% D079 Extender
+ 0.20% D046 Antifoam
+ 10 lb/sx Phenoseal

HOLE: 8.75 "
CSG OD: 7 "
CSG ID: 6.456 "
WGT: 20 ppf
GRADE: J-55
EXCESS: 150 %
TAIL: 543.4'
DEPTH: 2717'

Option 2
296 sx
137.1 bbls
769.9 cuft
2.60 ft³/sx
11.5 ppg
14.62 gal/sx
Type III Ashgrove Cement
+ 30 lb/sx San Juan Poz
+ 3% Bentonite
+ 5.0 lb/sx Phenoseal

Comp. Strength
1:47 hrs 50 psi
12 hrs 350 psi
24 hrs 450 psi

Option 3
293 sx
137.1 bbls
769.9 cuft
2.63 ft³/sx
11.7 ppg
15.92 gal/sx
Class G Cement
+ 3% D079 Extender
+ 0.20% D046 Antifoam
+ 1.0 lb/bbl CemNet

Comp. Strength
3 hrs 100 psi
24 hrs 443 psi

INTERMEDIATE TAIL:

Option 1
163 sx
38.1 bbls
213.9 cuft
1.31 ft³/sx
13.5 ppg
5.317 gal/sx
50/50 Poz: Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 3% S001 Calcium Chloride
+ 2% D020 Bentonite
+ 1.5 lb/sx D024 Gilsontite Extender
+ 0.1% D046 Antifoamer
+ 6 lb/sx Phenoseal

HOLE: 6.25 "
CSG OD: 4.5 "
CSG ID: 4 "
WGT: 11.6 ppf
GRADE: N-80
EXCESS: 50 %
DEPTH: 7222'

Option 2
161 sx
38.1 bbls
213.9 cuft
1.33 ft³/sx
13.5 ppg
5.52 gal/sx
50/50 Poz: Standard Cement
+ 2% Bentonite
+ 6.0 lb/sx Phenoseal

Comp. Strength
2:05 50 psi
4:06 500 psi
12 hrs 1250 psi
24hrs 1819 psi

Option 3
167 sx
38.1 bbls
213.9 cuft
1.28 ft³/sx
13.5 ppg
5.255 gal/sx
50/50 Poz: Class G Cement
+ 2% D020 Bentonite
+ 5.0 lb/sx D024 Gilsontite Extender
+ 2% S001 Calcium Chloride
+ 0.1% D046 Antifoamer
+ 0.15% D065 Dispersant
+ 1.0 lb/bbl CemNet

Comp. Strength
24 hrs 1850 psi
48 hrs 3411 psi

PRODUCTION:

Option 1
498 sx
127.7 bbls
717.0 cuft
1.44 ft³/sx
13.0 ppg
6.47 gal/sx
50/50 Poz: Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 3% D020 Bentonite
+ 1.0 lb/sx D024 Gilsontite Extender
+ 0.25% D167 Fluid Loss
+ 0.25% D065 Dispersant
+ 0.1% D800 Retarder
+ 0.1% D046 Antifoamer
+ 3.5 lb/sx Phenoseal

Comp. Strength
7 hrs 500 psi
24 hrs 2100 psi

Option 2
494 sx
127.7 bbls
717.0 cuft
1.45 ft³/sx
13.1 ppg
6.55 gal/sx
50/50 Poz: Standard Cement
+ 3% Bentonite
+ 0.2% CFR-3 Friction Reducer
+ 0.1% HR-5 Retarder
+ 0.8% Halad-9 Fluid Loss Additive
+ 3.5 lb/sx Phenoseal

Comp. Strength
9:32 50 psi
12 hrs 500 psi
13:29 1026 psi
24 hrs 2300 psi

Option 2
494 sx
127.7 bbls
717.0 cuft
1.45 ft³/sx
13.1 ppg
6.55 gal/sx
50/50 Poz: Standard Cement
+ 3% Bentonite
+ 0.2% CFR-3 Friction Reducer
+ 0.1% HR-5 Retarder
+ 0.8% Halad-9 Fluid Loss Additive
+ 3.5 lb/sx Phenoseal

Comp. Strength
9:32 50 psi
12 hrs 500 psi
13:29 1026 psi
24 hrs 2300 psi

Newberry A #2M

HOLE: 12.25 "
CSG OD: 9.625 "
CSG ID: 9.001 "
WGT: 32.3 ppf
GRADE: H-40
EXCESS: 125 %
DEPTH: 235'

SURFACE:

INTERMEDIATE LEAD:

Option 4

267 sx
137.1 bbls
769.9 cuft
2.88 ft³/sx
11.5 ppq
16.85 gal/sx
Standard Cement
+ 3% Econolite (Extender)
+ 10 lb/sx Phenoseal

Comp. Strength
1:47 50 psi
12 hrs 350 psi
24 hrs 450 psi

HOLE: 8.75 "
CSG OD: 7 "
CSG ID: 6.456 "
WGT: 20 ppf
GRADE: J-55
EXCESS: 150 %
TAIL: 543.4'
DEPTH: 2717'

Option 5

367 sx
137.1 bbls
769.9 cuft
2.10 ft³/sx
11.7 ppq
11.724 gal/sx
75% Type XI / 25% Class G Cement
+ 0.25 lb/sx D029 Cellophane Flakes
+ 3% D079 Extender
+ 0.20% D046 Antifoam

Comp. Strength
10:56 500 psi
42 hrs 1012 psi

INTERMEDIATE TAIL:

PRODUCTION:

HOLE: 6.25 "
CSG OD: 4.5 "
CSG ID: 4 "
WGT: 11.6 ppf
GRADE: N-80
EXCESS: 50 %
DEPTH: 7222'

TOPSET FRUITLAND COAL Wells: (topset casing above coal to prepare for cavitation/DO/UR)

Drilling Mud Program:

Surface: spud mud

Intermediate: fresh water mud with bentonite and polymer as needed

Below Intermediate: air/mist/nitrogen drilling media with foamer, polymer, & corrosion inhibitor as needed

Centralizer Program:

Surface: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 3rd, & 4th joints

Intermediate: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 4th, 6th, 8th, & 10th joints

Turbolizers placed one per joint from the top of the Ojo Alamo to the top of the Kirtland Shale

Below Intermediate: no centralizers used in air holes. In mud holes centralizers are spaced out appropriately

CASE & FRAC FRUITLAND COAL Wells: (casing set below coal to prepare for frac completion)

Drilling Mud Program:

Surface: spud mud

Production: fresh water mud with bentonite and polymer as needed

Centralizer Program:

Surface: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 3rd, & 4th joints

Production: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 4th, 6th, 8th, & 10th joints

Turbolizers placed one per joint from the top of the Ojo Alamo to the top of the Kirtland Shale

MESA VERDE Wells:

Drilling Mud Program:

Surface: spud mud

Intermediate: fresh water mud with bentonite and polymer as needed

Below Intermediate: air/mist drilling media with foamer, polymer, & corrosion inhibitor as needed

Centralizer Program:

Surface: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 3rd, & 4th joints

Intermediate: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 4th, 6th, 8th, & 10th joints

Turbolizers placed one per joint from the top of the Ojo Alamo to the top of the Kirtland Shale

Below Intermediate: no centralizers used in air holes. In mud holes centralizers are spaced out appropriately

DAKOTA Wells:

Drilling Mud Program:

Surface: spud mud

Intermediate: fresh water mud with bentonite and polymer as needed

Below Intermediate: air/mist/nitrogen drilling media with foamer, polymer, & corrosion inhibitor as needed

Centralizer Program:

Surface: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 3rd, & 4th joints


Intermediate: centralizers placed 10' above the shoe latched over a stop collar and at the top of the 2nd, 4th, 6th, 8th, & 10th joints

Turbolizers placed one per joint from the top of the Ojo Alamo to the top of the Kirtland Shale


Below Intermediate: no centralizers used in air holes. In mud holes centralizers are spaced out appropriately

BLOWOUT PREVENTER ARRANGEMENT & PROGRAM

For Drilling to Intermediate Casing Point & Setting 7" Intermediate Casing



1. Rotating Head
- 2A. Fill-up Line & valve
- 2B. Flowline
3. Spacer Spool
4. Double Ram BOP (11", 3000 psi)
5. Pipe Rams
6. Blind Rams
7. Kill Line
8. Kill Line Check Valve
9. Kill Line Valve
10. Inner Choke Line Valve (3")
11. Outer Choke Line Valve (3")
12. Choke Line (3")
13. Variable Choke
14. Choke Line Valve (2")
15. Panic Line Valve (3")
16. Choke Manifold Pressure Gauge
17. Choke Line (2")
18. Mud Cross Spacer Spool
19. Casing Head "A" Section
20. Casing Head "A" Section 2" Valve
21. 9 5/8" Casing Collar




A 12-1/4" hole will be drilled to approximately 220' and the 9-5/8" surface casing will be run and cemented. The Casing Head "A" Section will be screwed onto the 9-5/8" surface casing stub. The BOP will be installed on the Casing Head "A" Section. A test plug will be set in the wellhead and the pipe rams and choke manifold will be tested to 200 psi to 300 psi (low pressure test) for 10 minutes and to 1000 psi (high pressure test) for 10 minutes. Then the test plug will be removed, and the 9-5/8" casing will be pressure tested against closed blind rams to 200 psi to 300 psi for 10 minutes and to 1000 psi for 30 minutes (this value is one 44% of the minimum internal yield pressure of the 9-5/8" casing). (Note: per regulatory requirements we will wait on cement at least 3 hrs after placement before testing the 9-5/8" surface casing). Then an 8-3/4" hole will be drilled to intermediate casing point and 7" intermediate casing will be run and cemented.


In addition to the equipment in the above diagram the following equipment will comprise the BOP system:

BLOWOUT PREVENTER ARRANGEMENT & PROGRAM

For Drilling to TD and Setting 4.5 inch Casing



1. Rotating Head
- 2A. Fill-up Line & valve
- 2B. Bloopie Line (for Air Drilling)
3. Spacer Spool
4. Double Ram BOP (11", 3000 psi)
5. Pipe Rams
6. Blind Rams
7. Kill Line
8. Kill Line Check Valve
9. Kill Line Valve
10. Inner Choke Line Valve (3")
11. Outer Choke Line Valve (3")
12. Choke Line (3")
13. Variable Choke
14. Choke Line Valve (2")
15. Panic Line Valve (3")
16. Choke Manifold Pressure Gauge
17. Choke Line (2")
18. Mud Cross Spacer Spool
- 19A Csg Spool "B" Section (11", 3M)
- 19B "B" Section Csg Valve (2", 3M)
- 20A Csg Head "A" Section (11", 3M)
- 20B "A" Section Csg Valve (2", 3M)
21. 9 5/8" Casing Collar



After the 7" intermediate casing has been run and cemented, the Casing Spool ("B" Section) will be installed on the wellhead ("A" Section) and the BOP will be installed on the Casing Spool. A test plug will be set in the wellhead and the pipe rams, blind rams, and choke manifold will be tested to 200 psi to 300 psi (low pressure test) for 10 minutes and to 3000 psi (high pressure test) for 10 minutes. Then the test plug will be removed and the 7" casing will be pressure tested against closed blind rams to 200 psi to 300 psi for 10 minutes and to 1800 psi for 30 minutes - this test pressure is 48% of the minimum internal yield strength of 3740 psi for the 7", 20#, J-55, STC casing. Then we will air drill the 6-1/4" hole to TD and run and cement the 4-1/2" casing.

In addition to the equipment in the above diagram the following equipment will comprise the BOP system:

1. Upper Kelly cock Valve with handle
2. Stab-in TIW valve for all drillstrings in use