Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

FORM APPROVED Budget Bureau No. 1004-0135 Expires: November 30, 2000

Lease Serial No. NMNM - 112957

SUNDRY NOTICES AND REPORTS ON WELLS

I I I I I I I I I I I I I I I I I I I				If Indian, Allottee or Tribe	3/1
SUBMITIN	TRIPLICATE - Other instructions on	reverse side	, c 70	If Unit or CA/Agreement, FARMINGTON	Name and/or No.
Oil Well Gas Well Other				Well Name and No. TSAH TAH 35 #2 API Well No.	
ROSETTA RESOURCES				30-045-33756	Ko,
3a. Address c/o Walsh Engingeeirng & Production Corp. 7415 East Main St. Farmington, NM 87402 3b. Phone No. (include area code) (505) 327-4892				10. Field and Pool, or Exploratory Area. Q G 7 BASIN FRUITLAND COAL	
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 1135' FNL & 1435' FwL SEC 35 T25N R10W				11. County or Parish, State San Juan, New Mexico	
12. CHECK AF	PROPRIATE BOX(ES) TO IND	DICATE NATURE	OF NOTICE, REP	ORT, OR OTHER DA	ATA
TYPE OF SUBMISSION	TYPE OF ACTION				
 □ Notice of Intent ☑ Subsequent Report □ Final Abandonment Notice 	☐ Alter Casing ☐ F ☐ Casing Repair ☐ N ☐ Change Plans ☐ P	Deepen [Fracture Treat [New Construction [Plug and Abandon [Plug Back [Production (Start/I Reclamation Recomplete Temporarily Abanda Water Disposal	☐ Well Into	egrity CASING/CEMENT
13. Describe Proposed or Completed Ope			·-		
zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, A Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.) 08/02/06 spud 8-3/4" surface hole. Drilled to 128'KB. Ran 3 jts (118.35') of 7", 20#, J-55, ST&C new LS casing and set casing at 124'KB. Cemented with 45sx (53 cu. ft.) of Type 5 with 3% CaCl ₂ Circulated 4.0 bbls of good cement to surface. 08/04/06 Nippled up the BOP and pressure tested the casing and BOP to 1000 psi. 08/05/06 TD 6-1/4" hole at 1908' KB. Ran 49 jts (1880.46') of 4-1/2", 10.5#, J-55, ST&C production casing and landed at 1885.46' KB. Insert float is at 1864'KB. Cemented with 150 sx (309cu.ft.) of Type 5, 2% sodium metasillicate, 1/4#/sk celloflake, followed by 75 sx (89 cu. ft.) of Type 5, with 1/4# celloflake. Bumped plug to 1600 psi. Circulated 20 bbls of cement to the surface.					
Name (Printed/Typed)	The dia officer	Tist.	Frairce / Age		
Paul C. Thompson, P.E.		Title	Engineer / Age	iit	
Signature Paul C.	Thomas -	Date	August 14, 200	06	
THIS SPACE FOR FEDERAL OR STATE OFFICE USE					
Approved by		Title		Date	-
Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operation thereon.				ACCEP	EDPORTECCED
Title 18 U.C.S. Section 1001 and Title 43 U.S. States any false, fictitious or fraudulent statem	C. Section 1212, makes it a crime for any	person knowingly and wil hin its jurisdiction.	Ifully to make any depar	tment or agency of the Unite	5 1 8 2006

