Form 3160-5 (August 1999)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED Budget Bureau No. 1004-0135 Expires: November 30, 2000

5 Lease Serial No. 20 7 NMOVM 1112957

SUNDRY N	OTICES AND REPORTS ON WELLS				
Do not use this form for proposals to drill or to re-enter an					
abandoned well.	Use Form 3160-3 (APD) for such proposals				
	ϵ				

Do not use thi abandoned well	6. If Indian, Allottee or Tribe Name 2007 273377. If Unit or CA/Agreement, Name and/or No.								
SUBMITIN	TRIPLICATE - Other instructio	ns on reverse side	U / U (1°)	RMMG106		AUG 2006			
1. Type of Well ☐ Oil Well ☐ Gas V	Well Dother			8. Well Name and TSAH TAH					
2. Name of Operator				9. API Well No.	Yar.	Micro d			
ROSETTA RESOURCES 3a. Address c/o Walsh Engingeeirng 7415 East Main St. Farmingto	·	ne No. (include area code) 5) 327-4892		30-045-3376 10. Field and Pool, of BASIN FRUI	or Exploratory				
4. Location of Well (Footage, Sec., T.,			11. County or Parisl	-					
1350' FNL & 1200' FEL SEC 35 T251			San Juan, New Mexico						
12. CHECK AP	PROPRIATE BOX(ES) TO	INDICATE NATUR	E OF NOTICE, R	EPORT, OR OT	HER DATA	4			
TYPE OF SUBMISSION		TYPE OF A	CTION			` .			
☐ Notice of Intent	☐ Acidize ☐ Alter Casing	☐ Deepen ☐ Fracture Treat	Production (St	rart/Resume)		-			
Subsequent Report	Casing Repair	New Construction	Recomplete		-	CASING/CEMENT			
Final Abandonment Notice	☐ Change Plans ☐ Convert to Injection	☐ Plug and Abandon ☐ Plug Back	☐ Temporarily A ☐ Water Disposa		REPORT				
and the operator has determined that the site is ready for final inspection.) 07/29/06 spud 8-3/4" surface hole. Drilled to 125'KB. Ran 3 jts (116.04') of 7", 20#, J-55, ST&C new LS casing and set casing at 122'KB. Cemented with 60sx (72 cu. ft.) of Type 5 with 3% CaCl ₂ Circulated 5.0 bbls of good cement to surface. 08/01/06 Nippled up the BOP and pressure tested the casing and BOP to 500 psi. 08/02/06 TD 6-1/4" hole at 1908' KB. Ran 49 jts (1881.62') of 41/2", 10.5#, J-55, ST&C production casing and landed at 1886.39' KB. Insert float is at 1886.39'KB. Cemented with 150 sx (309cu.ft.) of Type 5, 2% sodium metasillicate, 1/4#/sk celloflake, followed by 75 sx (89 cu. ft.) of Type 5, with 1/4# celloflake. Bumped plug to 1500 psi. Circulated 28 bbls of cement to the surface.									
14. I hereby certify that the foregoing is	true and correct	<u> </u>							
Name (Printed/Typed) Paul C. Thompson, P.E.	_	Title	Engineer / A	Agent					
Signature Paul C.	Thomas -	Date	August 14,	2006	Sept Ser				
	THIS SPACE FO	RITEDERAL ORS	ATE OFFICE	USE					
Approved by		Title			Date				
Conditions of approval, if any, are attached. Approval of this notice does not warrant or				AG	CEP TEUT	Unitedian			

which would entitle the applicant to conduct operation thereon. Title 18 U.C.S. Section 1001 and Title 43 U.S.C. Section 1212, makes it a crime for any person knowingly and willfully to make any department or agency of the 2006 States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

certify that the applicant holds legal or equitable title to those rights in the subject lease

Title Office