UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

Type of Well GAS AUG 2008 070	28 - HI 5. RECEIV.	Lease Number SF-080673 If Indian, All. or Tribe Name
Name of Operator	7.	Unit Agreement Name
BURLINGTON RESCURCES OIL & GAS COMPANY LP	8.	San Juan 27-4 Unit Well Name & Number
PO Box 4289, Farmington, NM 87499 (505) 326-9700	9.	San Juan 27-4 Unit #39N API Well No.
Location of Well, Footage, Sec., T, R, M	10.	30-039-29559 Field and Pool
Unit C (NENW), 740' FNL & 2350' FWL, Section 5, T27N R4W, NMPM		
		sin Dakota/Blanco MesaVerd
	11.	County and State Río Arriba Co., NM
Final Abandonment Altering Casing Conversion to Injection 3. Describe Proposed or Completed Operations		
• •		
ee attached for description of work performed to drill & cement the 7" & 4 $\frac{1}{2}$ " casing	s.	
ee attached for description of work performed to drill & cement the 7" & 4 ½" casing 4. I hereby certify that the foregoing is true and correct.	s.	
ee attached for description of work performed to drill & cement the 7" & 4 ½" casing		Date <u>08/24/06</u>
ee attached for description of work performed to drill & cement the 7" & 4 ½" casing 4. I hereby certify that the foregoing is true and correct.	y Assistant	
4. I hereby certify that the foregoing is true and correct. igned	y Assistant	Date 08/24/06 .

MNOCD 9

FARMENSTON STEED OFFICE

San Juan 27-4 Unit # 39N Lease # - SF 080673 API # - 30-039-29559

8/6/06 RIH w/8 ¾" bit, tagged cement @ 100'. D/O cement @ ahead to 4130' (intermed). Circ. & cond. hole. RIH w/89 jts 7"20# J-55 ST & C casing & 9 jts- 7", 23# J-55 ST & C casing. Set @ 4129' w/ DV tool set @ 3394'. RU to cement. Pumped pre-flush of 10 bbls FW/10 bblsmudflush/10 bbls FW. 1st Stage-Lead pumped 19 sx(57cf – 10 bbls)Scavenger Type III cement w/.05 #/sx D-29 Cellophane, .30% CD-32, 6.25 #/sx LCM-1, & Fl-52. Tail- pumped 119 sx(164-29 bbls) Premium LiteType II cement w/.25 #/sx Cello-Flake, .30% CD-32, 6.25 #/sx LCM-1, & 1% FL-52. Bumped plug w/1950# @ 1446 hrs on 8/11/06. Opened DV tool, & circ. between stages.

8/11/06- Rec'd verbal approval from Jim Lovato to continue w/ 2nd Stage- Had full returns w/ hint of cement to surface on 1st Stage.

2nd Stage- pumped pre-flush 10 bbls FW/10 bbls mudflush/10 bbls FW. Lead- pumped 19sx(57cf – 10 bbls) Scavenger Type III cement w/.05 #/sx D-29 Cellophane, .30% CD-32, 6.25 #/sx LCM-1, & 1% FL-52. Tailed w/451 sx(961cf –171 bbls) Premium Lite Type III cement w/ .25 #/sx Cello-Flake, .30% CD-32, .50 #/sx LCM-1, & .40% FL-52. Bumped plug w/ 2450# @1955 hrs. 8/11/06. ND. Install B section wellhead.

8/12/06 Rec'd verbal approval from Jim Lovato to continue w 4 ½" casing- cement didn't circulate to surface on 2nd Stage. But ran Bomber Log- TOC @ 450' - Surf casing@ 150', & Ojo Alamo @ 3415'.

8/12/06 RIH w/4-½" bit. D/O DV tool @ 3394'. PT pipe rams & casing 1500#/30 min.- OK. Drilled from 4130 – 8358' (TD) TD reached 8/15/06.Circ. hole. RU casing crew. RIH w/15jts 4 ½" 11.6# LT & C casing on bottom, 149 jts 4 ½" 10.50# ST & C casing & 31 jts 4 ½"11.60# LT & C casing on top. Set @ 8357'. RU to cement. Pumped pre-flush 10 bbls gel spacer/5 bbls H2O. Lead-pumped 9 sx(28 cf – 5 bbls) 11# Scavenger cement w/.25 #/sk Cello-flake, .30% CD-32, 6.25 #/sk LCM-1, & 1% FL-52. Tailed w/300sx (594cf – 106 bbls) Premium Lite cement w/.25 #/sk Cello-flake, .30% CD-32, 6.25 #/sk LCM-1, & 1% FL-52. Bumped plug @08:00 hrs 8/16/06. Land casing, & nipple down. RR 14:00 hrs 08/16/06.

PT will be done by completion rig. PT results & TOC will be shown on next report.