Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

/	FORM	APPR	OVE	D	
Budget Bureau No. 1004-0135					
E	xpires:	March	31,	1993	

٠.	Democ Decibration	 	
M.	013642		

	RECE	NM-013642			
SUNDRY NOTICES AND	6. If Indian, Allottee or Tribe Name				
Do not use this form for proposals to drill or					
Use "APPLICATION FOR PE	RMIT—" for such proposals 203 JUL 23	MNA 08			
SUBMIT IN T	RIPLICATE RESIDENT SITTING	7. If Unit or CA, Agreement Designation			
1. Type of Well Oil Gas Gas					
Well X Well Other	JUL 2003	8. Well Name and No.			
2. Name of Operator	ROLL COLLEGE	Gardner 7			
Koch Exploration Company, LLC.	9. API Well No.				
3. Address and Telephone No.		30-045-30749			
P.O. Box 489 Aztec, New Mexico 8	37410 (505)334-91H	10. Field and Pool, or Exploratory Area			
,	3 St. VI CER	Blanco Mesa Verde			
4. Location of Well (Footage, Sec., T., R., M., or Survey De	escription)	11. County or Parish, State			
1815' FNL & 1395' FWL		San Luan Caunty			
S26, T32N, R9W (F)		San Juan County			
320, 132N, R9W (I')	New Mexico				
12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA					
TYPE OF SUBMISSION	ACTION				
Notice of Intent		X as and			
Notice of intent	Abandonment	Change of Plans			
	Recompletion	New Construction			
X Subsequent Report	Plugging Back	Non-Routine Fracturing			
	Casing Repair	Water Shut-Off			
Final Abandonment Notice	Altering Casing	Conversion to Injection			
	Other Cement Surface Casing	Dispose Water			
		Note: Report results of multiple completion on Well Completion r Recompletion Report and Log form.)			
13. Describe Proposed or Compelted Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)					
	,				

Drilled 12 1/4" hole and ran 9 5/8", J-55, 36#, ST&C casing and landed at 232' KB. KB = 13'0"

Ran centralizers on the bottom 3 joints including shoe joint. Cemented with 135 sks 15.8# Class G Cement with 2% CaCl2, .25 lb/sk D29 Cellophane, yield 1.16. Circulated 18 BBL's cement to surface. WOC 12 hours.

7/15/03 - Pressure tested casing to 750 psi for 30 min. Held OK.

	·		
I hereby certify that the foregoing is true and open	rect.		
Signed MAM	Title District Superintendent	Date	ACCEPTED FOR RECORD 7/20/03
(This space for rederal or State office use)			
Approved by	Title		JUL 2 5 2003
Date			ZAMANA
Conditions of approval, if any:			FAHMINGTUM FIELD UFFICE