

UNITED STATES  
\* DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

5. Lease Designation and Serial No.

NM013642

6. If Indian, Allottee or Tribe Name

NA

7. If Unit or CA, Agreement Designation

NA

8. Well Name and No.

Federal Blancett Com C1A

9. API Well No.

3004531389

10. Field and Pool, or Exploratory Area

Basin Fruitland Coal

11. County or Parish, State

San Juan County  
New Mexico

SUBMIT IN TRIPLICATE

070 Farmington

1. Type of Well

☐ Oil Well

☒ Gas Well

☐ Other

2. Name of Operator

Koch Exploration Company, LLC

3. Address and Telephone No.

P.O. Box 489 Aztec, NM 87410

(505) 334-9111

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

S27, T32N, R9W (I)  
1745 FSL & 1170 FEL

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment

☐ Recompletion

☐ Plugging Back

☐ Casing Repair

☐ Altering Casing

☒ Other Surface Casing Cement

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut-Off

☐ Conversion to Injection

☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Drilled 12 1/4" hole and ran 9 5/8", J-55, 36#, ST&C casing and landed at 232' KB. KB = 13'0"

Ran centralizers on the bottom 3 joints including shoe joint. Cemented with 120 sks 15.8# Class G Cement with 2% CaCl2, .25 lb/sk D29 Cellofane, yield 1.16. Had good cement returns to surface. WOC 12 hours.

7/15/03 - Pressure tested casing to 700 psi for 30 min. Held OK.

I hereby certify that the foregoing is true and correct

Signed  
(This space for Federal or State office use)

Title District Superintendent

Date 7/20/03  
ACCEPTED FOR RECORD

Approved by  
Date

Title

Conditions of approval, if any:

JUL 25 2003

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations

NMOC