

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

2006 JUL 20 FARMING 107827

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

RECEIVED

7. UNIT AGREEMENT NAME

San Juan 29-5 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 29-5 Unit #20C

9. API WELL NO.

30-039-29334

10. FIELD AND POOL, OR WILDCAT

Blanco Mesaverde

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 7, T29N, R5W, NMPM

1a. TYPE OF WELL:

OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐

2. NAME OF OPERATOR

CONOCOPHILLIPS COMPANY

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface Unit C, (NENW), 295' FNL & 2120' FWL,

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR PARISH

Rio Arriba

13. STATE

New Mexico

15. DATE SPUDDED

5/26/06

16. DATE T.D. REACHED

6/1/06

17. DATE COMPL. (Ready to prod.)

7/13/06

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)*

KB- 6557'

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

6025'

21. PLUG, BACK T.D., MD & TVD

6017'

22. IF MULTIPLE COMPL., HOW MANY*

1

23. INTERVALS DRILLED BY

ROTARY TOOLS

CABLE TOOLS

Yes

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesaverde - 4252' - 5824'

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

CBL, GR/CBL

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9-5/8"	32.3# H-40	229'	12-1/4"	Surface: 150 sx (175 cf)	15 bbis
7"	20#, J-55	3790'	8-3/4"	Surface: 655 sx (1423 cf)	71 bbis
4-1/2"	10.5#, J-55	6018'	6-1/4"	TOC @ 2850'; 255 sx (367 cf)	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	5696'	
					4.7#		

31. PERFORATION RECORD (Interval, size and number)

MV perforations
Lewis - 4252' - 4784'
CH & Upper Menefee - 5080' - 5594'
Lower Menefee & Pt Lookout - 5639' - 5824'

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

DEPTH INTERVAL (MD)	AMOUNT AND KIND OF MATERIAL USED
4252' - 4784'	420 gals 15% HCL acid; 658 bbis 75 Q Linear gel w/198,088# 20/40 Brady sand & 1,419,300 scxf N2.
5080' - 5594'	420 gal 15% HCL; 1183 bbis 60 Q Slickwater foam w/95,150# 20/40 Brady sand & 1,244,300 scf N2
5639' - 5824'	420 gal 15% HCL; 1,217 bbis 60 Q Slickwater foam w/99,933# 20/40 Brady sand & 1,282,700 scf N2

33. PRODUCTION

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)					WELL STATUS (Producing or shut-in)	
SI		flowing					SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS/OIL RATIO	
7/12/06	4	1/2"	→		253 mcf			
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)		
SITI SI - n/a	FCP - 230#	→		1518 mcf	1 bwpd			

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY:

35. LIST OF ATTACHMENTS

This will be a single zones Mesaverde well.

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED [Signature] TITLE Sr. Regulatory Specialist

DATE 7/12/06

(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

Ojo Alamo	2625'	2840'	White, cr-gr ss.	Ojo Alamo	2625'
Kirtland	2840'	3246'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2840'
Fruitland	3246'	3482'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3246'
Pictured Cliffs	3482'	4231'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3482'
Lewis	4231'	4499'	Shale w/siltstone stringers	Lewis	4231'
Huerfanito Bentonite	xxxxx'		White, waxy chalky bentonite	Huerfanito Bent.	xxxxx'
Chacra	4499'	5302'	Gry fn grn silty, glauconitic sd stone w/drk gry shale	Chacra	4499'
Mesa Verde	5302'	5384'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	5032'
Menefee	5384'	5675'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5384'
Point Lookout	5675'		Med-light gry, very fine gr ss w/frequent	Point Lookout	5675'