

**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

## Sundry Notices and Reports on Wells

1. **Type of Well**  
GAS

2. **Name of Operator**

**BURLINGTON**  
RESOURCES OIL & GAS COMPANY LP

3. **Address & Phone No. of Operator**

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**  
Sec., T--N, R--W, NMPM

Unit H (SENE), 1765' FNL & 810' FEL, Sec. 6, T26N, R9W, NMPM

5. **Lease Number**  
NMNM-03017  
6. **If Indian, All. or  
Tribe Name**

7. **Unit Agreement Name**

Huerfano Unit #200E

8. **Well Name & Number**

Huerfano Unit #200E  
9. **API Well No.**

30-045-26667

10. **Field and Pool**

Basin Dakota

11. **County and State**  
San Juan Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

**Type of Submission**

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

**Type of Action**

☐ Abandonment

☐ Recompletion

☐ Plugging

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

☒ Other - Restimulation

**13. Describe Proposed or Completed Operations**

4/20/06 MIRU Drake #24. ND WH, NU BOP, TOO H w/tubing. TIH w/5-1/2" <sup>BP</sup> RPB & set @ 6673'. Load csg and PT casing to 1500 psi/15 min. OK. ND BOP, ND WH. NU 5000# frac head. NU frac valve. PT csg to 3500psi for 15mins, ok. ND frac valve. NU BOP. Pull and LD pkr set @ 30'. TOH to 3000'. Unload hole w/air @ 3000'. TIH to RBP @ 6673'. Lay down 2 3/8" tbg. ND BOP. NU frac valve. RD & released rig 4/24/06.

4/27/06 RU Schlumberger to frac DK interval. Broke down formation with 260 TNS CO2 and 22000# 30/50 sand. RD Schlumberger & RU to flowback. Flowed back for 3 days. RD & released flowback crew.

7/14/06 MIRU Drake #24. Bled down well, no water to kill well. ND frac head. NU BOP, TIH w/2-3/8" tubing and tagged fill @ 6525'. Est. circulation w/air. C/O to @ 6700'. C/O sand fill from 6700' to PBTD @ 6950'. Flowed naturally and then circ. w/air 7/19/06 Bleed down well slowly. Hang tbg off w/pkr # 30'. ND BOP. ND 5000# frac head. NU 2000# tbg head. PT seals TP 2000psi, ok. NU BOP. Pull pkr. TIH w/10 stads. Tag 25' sand fill. Flowed back 2days. PU and land 214 jts 2-3/8", 4.7# J-55 tbg 8rd @ 6790'. ND BOP, NU WH. Pumped off expendable check. RD & released rig on 7/21/06.

**14. I hereby certify that the foregoing is true and correct.**

Signed Amanda Sanchez Title Sr. Regulatory Analyst Date 8/22/06

**ACCEPTED FOR RECORD**

(This space for Federal or State Office use)

APPROVED BY [Signature] Title \_\_\_\_\_ Date SEP 18 2006

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

**FARMINGTON FIELD OFFICE**  
BY [Signature]

NMOCDB