

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

2006 OCT 12 PM 4 CO
RECEIVED
OTO FARMINGTON

1. Type of Well
GAS

2. Name of Operator
CONOCOPHILLIPS

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit G, 1610' FNL & 1690' FEL, Section 8, T25N, R5W, NMPM

5. Lease Number
JIC 147

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. Well Name & Number

AXI Apache J #27
9. API Well No.

30-039-21349

10. Field and Pool

Blanco Pictured Cliffs, South

11. County and State
Rio Arriba Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

☐ Notice of Intent

☒ Subsequent Report

☐ Final Abandonment

Type of Action

☒ Abandonment

☐ Recompletion

☐ Plugging

☐ Casing Repair

☐ Altering Casing

☐ Change of Plans

☐ New Construction

☐ Non-Routine Fracturing

☐ Water Shut off

☐ Conversion to Injection

☐ Other

13. Describe Proposed or Completed Operations

9/11/06 MIRU A-Plus #4. Kill well. ND WH, NU BOP. POOH w/91 jts 1-1/4" tbg. RIH w/2.875" gauge ring to 2980'. POOH. RIH w/CIBP & set @ 2926'. POOH. RIH w/tbg & tagged CIBP @ 2926'. Circ. Hole. Unable to PT, established injection rate @ 1.5 bpm @ 500#. Pumped Plug #1 - 18 sx ASTM Type III cement. TOC should be @ 2195'. WOC. Tried to PT - no good. RIH w/WL & tagged cement @ 2385'. POOH. Pumped Plug 1A - w/17 sx ASTM Type III. 9/15/06 RIH & tagged TOC @ 2030'. Perf'd 2 squeeze holes @ 990' & set cement retainer @ 940'. PU singer & TIH to 940'. Sting in to cement retainer. Estab. Injection rate. Pumped Plug #2 w/50 sx ASTM Type III cement. 45 outside casing; 2 sx below retainer; 3 sx on top of retainer. Perf'd 2 squeeze holes @ 557'. Pumped Plug #3 (&4). w/175 sx ATSM Type III. Cement from 557' to surface. Circulated good cement to surface. Combined plug 3 & 4 - approved by B Hammond with JAT (on location). 9/18/06 Tagged cement in casing full. RD lines. Dig out WH. Cut off WH, Cement in annulus down 5". Installed DH marker w/20 sx Type III cement. Cut off anchors. Install DH Marker.

14. I hereby certify that the foregoing is true and correct.

Signed

Patsy Clugston

Patsy Clugston

Title Sr. Regulatory Specialist

Date 6/23/06

(This space for Federal or State Office use)

APPROVED BY

Title

Date

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

ACCEPTED FOR RECORD

OCT 13 2006

FARMINGTON FIELD OFFICE

NMOCD