

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator
ConocoPhillips

3. Address & Phone No. of Operator


PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit N (SESW) 830' FSL & 1935' FWL, Sec. 26, T31N, R8W, NMPM

2006 OCT 12 PM 4 04

RECEIVED
OTO FARMINGTON NM



5. Lease Number
NMNM-012641
6. If Indian, All. or
Tribe Name
7. Unit Agreement Name
8. Well Name & Number
Blanco #10B
9. API Well No.
30-045-33024
10. Field and Pool
Blanco Mesa Verde
11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection

☒ Other - Casing Report

13. Describe Proposed or Completed Operations

9/27/06 MIRU Patterson. PT surface casing 1000/# 30 min. Test OK. RIH w/8 3/4" bit. D/O cement & ahead to 3032' intermediate. Circ. hole. RIH w/71 jts, 7" 20#, J-55 ST & C casing & set @ 3020'. RU to cement. Pumped pre-flush of 30 bbls gelled water spacer last 10 bbls w/GD. Lead- pumped 305 sx (878 cf - 156 bbls) Mountain G Cement w/ 3% Econolite, 10 lb/sx Pheno seal medium. Tail- pumped 180 sxs (239 cf - 43 bbls) 50/50 G-POZ Mountain G Cement w/2.05 Bentonite, 6 #/sx Pheno seal fine. Bumped plug. Circ 97 bbls to surf. WOC. PT casing to 1800 #/30 min. Test Good.

10/3/06 RIH w/6 1/4" bit. D/O cement and ahead to 5678' (TD) TD reached on 10/5/06. Circ hole. RIH w/133 jts 4 1/2" 10.5 # J-55 ST & C casing, set @ 5666'. Pumped pre-flush of 20 bbls Chemwash & 5 bbls H2O. Lead- pumped 305 sx (442 cf-79 bbls) 50/50 Type G POZ Cement w/2% Bentonite, 3.5 #/sx Pheno Seal, .20% Friction Reducer, .1% Retarder, .8% Fluid loss. Displaced w/90 bbls FW. Bumped plug. ND BOP. RD equip. & rig. RR at 1600 hrs on 10/6/06.

Pressure Test & TOC will be done by the completion rig. Results will be shown on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Assistant Date 10/10/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

