

**UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT**

Sundry Notices and Reports on Wells

2006 OCT 12 PM 4 05

1. Type of Well
GAS

2. Name of Operator
ConocoPhillips

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

Unit H (SENE) 2380' FNL & 715' FEL, Sec. 15, T31N, R8W, NMPM

5. Lease Number
NMSF-079004

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

8. San Juan 32-8 Unit
Well Name & Number

9. SJ 32-8 Unit #21B
API Well No.

30-045-33700

10. Field and Pool

Blanco Mesa Verde

11. County and State
San Juan Co., NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Other - Casing Report

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

13. Describe Proposed or Completed Operations

9/29//06 MIRU Aztec. NU. PT casing 600 psi 30 min. test OK. RIH w/8 3/4" bit, tagged cement @ 189'. D/O & ahead to 3155' Intermediate. RU casing. RIH w/73 jts 7" 20# J-55 ST & C casing & set @ 3145'. RU cement. Pumped pre-flush 10 bbls H2O/ 10 bbls mud clean/10 bbls H2O. Pumped Scavenger 19sx(57cf-10bbls) Cement. Lead-pumped 351 sx(748cf-133 bbls) Premium Lite cement w/3% CaCl2, .25 #/sx Celloflake, 5 #/sx LCM1, .4% FL52, .4% SMS. Tail- pumped 90 sx(124cf-22 bbls) Type III Cement w/1% CaCl2, .25 #/sx Celloflake, .2% FL52. Dropped plug & displaced w/125 bbls H2O. Plug down @ 00:18 hrs. 10/4/06. Circ. 50 bbls cement to surface.

10/4/06 NU B section & BOP. PT 7" casing to 1500 #/30 min. - good test. RIH w/6 1/4" bit, tagged cement @ 3095'. D/O cement & ahead to 6133' (TD). TD reached 10/7/06. RIH w/144 jts 4 1/2" 10.5# J-55 ST & C casing, set @ 6124'. RU to cement. Pumped Pre-flush of 10 bbls gel water/2 bbls H2O. Lead pumped Scavenger 9sx(27cf- 10 bbls) Cement w/ .3% CD-32, .25 #/sx Celloflake, 1 % FL-52, 6.25 #/sx LCM-1. Tail- pumped 192 sx(380cf- 68 bbls) Premium Lite Cement w/.25 #/sx Celloflake, .3% CD32, 6.25 #/sx LCM1, 1% FL52. Dropped plug & displaced w/98 bbls H2O. Plug down @ 20:53 hrs. ND BOP & RD. RR @ 03:00 hrs on 10/8/06.

The casing PT & TOC will be conducted by the completion rig and results shown on next report.

14. I hereby certify that the foregoing is true and correct.

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Assistant Date 10/12/06

(This space for Federal or State Office use)

APPROVED BY _____ Title _____

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOC

ACCEPTED FOR RECORD

Date OCT 13 2006

FARMINGTON FIELD OFFICE
BY TL Salvo/CCS