

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

DIST. 3

Form C-103
Revised May 08, 2003

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-045-33528
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator BP America Production Company		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 3092 Houston, Texas 77253		7. Lease Name or Unit Agreement Name State Gas Com BF
4. Well Location Unit Letter J : 2235 feet from the South line and 1695 feet from the East line Section 16 Township 29N Range 09W NMPM County San Juan		8. Well Number 1M
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 7065'		9. OGRID Number 000778
		10. Pool name or Wildcat Blanco Basin-Dakota Mesaverde

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: **Subsequent** ☒

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

10/03/06 DRILL CEMENT AND COMPOSITE PLUG OUT, RIG DOWN SWIVEL, TIH TO 4700', TOO H, SECURE LOCATION.

10/04/06 CASING 0 PSI, TIH WITH 4 1/2" SCRAPER TO 4700', TOO H, TIH WITH 4 1/2" RBP AND SET AT 4360' PRESSURE TEST TO 2350 PSI, HELD 5 MIN, GOOD TEST, RELEASE PRESSURE. TEST CASING TO 4850 PSI, HELD 10 MIN, GOOD TEST, BLEED PSI DOWN, RIG DOWN PUMP TRUCK, TIH, SECURE LOCATION, SHUT DOWN OVERNIGHT

10/06/06 PERFORATED THE MESAVERDE FROM 4,454' TO 4,681'.

10/11/06 FRAC. THE MESAVERDE DOWN 4 1/2 " CASING @ 60 BBLs. / MIN. USING 175,000 LBS. OF 16/30 BRADY SAND WITH SCHLUMBERGER CLEAR FRAC. IN 70 % QUALITY FOAM AND N2. PUMPED J-516 FLOW SAVER DURING THE PAD. THE LAST 45,000 LBS OF SAND WAS TREATED WITH PROPNET.

10/17/06 LAND TUBING AT 6775'

10/18/06 FLOW WELL TO FLAIR PIT ON 3/4" CHOKE FOR DELEVERABILITY TEST, 30 PSI AVERAGE.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kristina Hurts TITLE Regulatory Analyst DATE 10/19/2006

Type or print name Kristina Hurts

Telephone No. 281-366-3866

(This space for State use) APPROVED

BY H. Villanueva TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 3 DATE NOV 01 2006