

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources
OIL CONSERVATION DIVISION
1220 South St. Francis Dr. Div.
Santa Fe, NM 87505

Form C-103
Revised June 10, 2003

WELL API NO.
30-043-26514

5. Indicate Type of Lease
STATE ☐ FEE ☒

6. State Oil & Gas Lease No.
NM 024158

7. Lease Name or Unit Agreement Name
AMOCO

8. Well Number
1

9. OGRID Number 022521

10. Pool name or Wildcat
Flora Vista Fruitland (76600)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well:
Oil Well ☐ Gas Well ☒ Other

2. Name of Operator
Texakoma Oil & Gas

3. Address of Operator
5400 LBJ Freeway, Suite 500, Dallas, TX 75240

4. Well Location

Unit Letter A : 810 feet from the NORTH line and 880 feet from the EAST line

Section 21 Township 30N Range 12W NMPM San Juan County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
5656' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

On October 18, 2002, the Amoco #1 well was plugged and abandoned as follows:

Tagged sand at 1550' and reversed out to PBTD of 1880'.

Spot plug 1880' to 1400' & pick up to 1400' & spot plug 1400' to surface. Total 50 sx Class B neat.

Pick up to 260' & reverse out cement. TOH tbg & wait on cement 3 hrs.

RU Jet West & tag TOC @ 264'. Shoot 2 squeeze hole @ 260' KB.

ND BOP & tie to 2-7/8" csg. Pump 30 sx Class B to circulate bradenhead.

Cut off wellhead 7" csg & 2-7/8" csg & cement @ surface.

Henry Villanueva of NMOCD on location during job.

Erect dry hole marker clean up location.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Rodney A. Kiel TITLE Operation Engineer DATE 08/14/2003

Type or print name Rodney Kiel
(This space for State use)

E-mail address: rodkiel@airmail.net

Telephone No. 972-701-9106

APPROVED BY H. Villanueva

TITLE DEPUTY OIL & GAS INSPECTOR, DIST. #8

DATE AUG 18 2003

Conditions of approval, if any:

8-19-03