Form 3160-5 (November 1994)

UNITED STATES DEPARTMENT OF THE INTERIOR BUDGALLOG LAND MANAGEMENT

FURM AP	ישאי	12
OMB No.	1004	бı
Expires July	M,	19

5.	Lease	Serial	No.

DORLAG OF LAND MANAGEMENT		WATER.	pring.	******	11	- 1	1 1	١,	ŧ
	17	1 4	ſ,	1	11	. I	ا	1	į
INDRY NOTICES AND REPORTS ON WEL	ĿS	1	١,	ń.	1	Ą	-	مسا	

NMSF-07806

SI 6. If Indian, Allottee or Tribe Name Do not use this form for proposals to drill or reenter an abandoned well. Use Form 3160-3 (APD) for such proposals. 7. If Unit or CA/Agreement, Name and/or No. SUBMIT IN TRIPLICATE - Other instructions on reverse Type of Well 8. Well Name and No. X Oil Well Gas Well Other Name of Operator Carson Unit 19 #44 9. API Well No. Elm Ridge Resources, Inc. 3a. Address 3b. Phone No. (include area code) 30-045-28120 10. Field and Pool, or Exploratory Area PO Box 189 Farmington, NM 87499 505-632-3476 Location of Well (Footage, Sec., T., R., M., or Survey Description) Bisti Lower Gallup 11. County or Parish, State 330' FSL & 990' FEL Sec. 19-T25N-R11W San Juan, New Mexico 12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Production (Start/Resume) Water Shut-Off Acidize Deepen Well Integrity Reclamation Alter Casing Fracture Treat X Subsequent Report Casing Repair New Construction Recomplete Other Change Plans Temporarily Abandon Plug and Abandon Final Abandonment Notice Convert to Injection Water Disposal Plug Back Describe Proposed or Completed Operations (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days Following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once Testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.) Elm Ridge Resources, Inc plugged and abandoned the CarsonUnit 19 #44 on July 31, 2003 as follows: SEE ATTACHED SHEET FOR DETAILS

Certified	i return	receipt :	#

14. I hereby certify that the foregoing is true and correct		
Name (Printed/Typed)	Title	
Trudy Grub e Inik / /		Production Technician
Signature \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\ \\	Date	August 1, 2003
THIS SPACE FOR	R FEDERAL OR ST	ATE USE
Approved by	Title	Date
Conditions of approval, if any, are attached. Approval of this notice does not warm certify that the applicant holds legal or equitable title to those rights in the subject which would entitle the applicant to conduct operations thereon.		
Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and	d willfully to make to	any department or agency of the United States any false, fictitious or


(Instructions on reverse)

fraudulent statements or representations as to any matter within its jurisdiction

NWOCD

EN FOR RECORD

AUG 0 7 2003



Elm Ridge Resources Inc. Plug Abandon Report

Operator: Elm Ridge Resources, Inc.

Date: August 1, 2003 Field: Bisti Lower Gallup Contractor: Triple P Well Name: Carson Unit 19 #44

Report No.: 1

Location: Sec. 19, T25N, R11W Supervisor: Terry Lindeman

Work Summary:

Completed Operations: July 31, 2003

Plug #1 - Set CIBP @ 4694'. Spot 20 sx (23.6 cu. Ft) Class "B" cement from 4694' to 4600' inside casing -50% excess.

Plug #2 – Spot 20 sx (23.6 cu ft) Class "B" cement from 2022' to 1922' inside casing – 50% excess.

Plug #3 – Spot 20 sx (23.6 cu ft) Class "B" cement from 1297' to 1197' inside casing – 50% excess.

Plug #4 – Spot 20 sx (23.6 cu ft) Class "B" cement from 962' to 862' inside casing – 50% excesss.

Plug #5 – Spot 55 sx (64.9 cu ft) Class "B" cement from 456' to surface inside casing. Circulated cement to surface. Plugging complete.