

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88203
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources
Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
Revised June 10, 2003

WELL API NO.
30-045-33478

5. Indicate Type of Lease
STATE ☒ FEE ☐

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER ☐
b. Type of Completion:
NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER ☐

7. Lease Name or Unit Agreement Name
STATE COM I

2. Name of Operator
ConocoPhillips Company

8. Well No.

5B

3. Address of Operator
PO BOX 4289 Farmington, NM 87499

9. Pool name or Wildcat
BLANCO MESAVERDE / BASIN DAKOTA

4. Well Location
Unit Letter D : 740 Feet From The NORTH Line and 150 Feet From The WEST Line
Section 36 Township 31N Range 9W NMPM SAN JUAN County

10. Date Spudded 08/07/2006 11. Date T.D. Reached 08/30/2006 12. Date Compl. (Ready to Prod.) 10/26/2006 13. Elevations (DF& RKB, RT, GR, etc.) 5942 GL 14. Elev. Casinghead

15. Total Depth 7442' MD / 7332' TVD 16. Plug Back T.D. 7441' MD / 7331' TVD 17. If Multiple Compl. How Many Zones? Commingle 18. Intervals Drilled By x Rotary Tools Cable Tools

19. Producing Interval(s), of this completion - Top, Bottom, Name 7244'-7415' Dakota 20. Was Directional Survey Made No

21. Type Electric and Other Logs Run CBL/GR/CCL 22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9.625	32.3	252'	12.25	Surf: 474sx 549 cf	2 bbl
7.0	23.0	3206'	8.75	Surf: 580sx 1158 cf	105 bbl
4.5	11.6	7442'	6.25	TOC: 1400'	
				453 sx 744 cf	.75 bbl

24. LINER RECORD				25. TUBING RECORD			
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2.375	7324'	

26. Perforation record (interval, size, and number)
Dakota:
7244'-7415' 0.34" Dia. 88 Holes

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.	
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED
7244'-7415'	420 gal 15% HCL. Frac w/slick water; 27,050 #20/40 brady;
	2,762 clean fluid

28. PRODUCTION

Date First Production 10/26/2006		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing			Well Status (Prod. or Shut-in) SI		
Date of Test 10/25/2006	Hours Tested 1	Choke Size 1/2"	Prod'n For Test Period	Oil - Bbl 0	Gas - MCF 19.25 mcf	Water - Bbl. 0.75 bbl	Gas - Oil Ratio
Flow Tubing Press. FTP 70 psi	Casing Pressure SCIP 195 psi	Calculated 24-Hour Rate	Oil - Bbl. 0	Gas - MCF 462 mcfd	Water - Bbl. 18 bpd	Oil Gravity - API - (Corr.)	

29. Disposition of Gas (Sold, used for fuel, vented, etc.)
Sold

Test Witnessed By

30. List Attachments
This is a MV/DK commingle well. DHC 2099AZ

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature *Juanita Farrell* Printed Name Juanita Farrell Title Regulatory Specialist Date 11/03/2006
E-mail Address juanita.r.farrell@conocophillips.com

Ojo Alamo	1425' 1517'	White, cr-gr ss.	Ojo Alamo	1425'
Kirtland	1517' 2290'	Gry sh interbedded w/tight, gry, fine-gr ss.	Fruitland	2290'
Fruitland	2290' 2884'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Pic.Cliffs	2284'
Pictured Cliffs	2284' 3198'	Bn-Gry, fine grn, tight ss.	Cliff House	4404'
Mesa Verde	4404' 5130'	ss. Gry, fine-grn, dense sil ss.	Point Lookout	5130'
Point Lookout	5130' 5447'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Gallup	5839'
Gallup	5839' 7128'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh	Graneros	7179'
Graneros	7179' 7245'	Dk gry shale, fossil & carb w/pyrite incl.	Dakota	7245'
Dakota	7245' 7441'	Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks		