District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

### State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144

June 1, 2004

Pit or Below-Grade Tank Registration or Closure
Is pit or below-grade tank covered by a "general plan"? Yes X No ...

Type of action: Registration of a pit of	or below-grade tank 🔲 Clos	sure of a pit or below-gr	ade tank	<del></del>
Operator: BP America Production Company Telephor	ne: <u>(505)326-9200</u>	e-mail address:		
Address: 200 Energy Ct, Farmington, NM 87401				
Facility or well name: GCW # 221 API#:	3004511649	U/L or Otr/Otr	- Sec 3 ( T	29N R12W
				27 🔲 1983 🔀
Surface Owner: Federal State Private Indian				
Pit	Below-grade tank			
Type: Drilling Production Disposal	Volume:bbl Type	of fluid:		RCVD NOV1
Workover ☐ Emergency ☐	Construction material:			,,,,,,
Lined Unlined [	Double-walled, with leak detection? Yes If not, explain why not.			
Liner type: Synthetic Thickness mil Clay	UIL VOICE			
Pit Volumebbl				nar-t da
	Less than 50 feet	<del></del>	(20 points)	DIST\$
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less that	an 100 feet	(10 points)	
high water elevation of ground water.)	100 feet or more		( 0 points)	
	Yes		(20 points)	
Wellhead protection area: (Less than 200 feet from a private domestic			( 0 points)	
water source, or less than 1000 feet from all other water sources.)	No		( o points)	
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet		(20 points)	
tion canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less the	han 1000 feet	(10 points)	
tion canais, diteres, and perennial and epitemetal watercourses.)	1000 feet or more		( 0 points)	
	Ranking Score (Total Poi	ints)		
f this is a pit closure: (1) Attach a diagram of the facility showing the pit	s relationship to other equipm	nent and tanks. (2) Indi	cate disposal location: (c	heck the onsite box if
your are burying in place) onsite \( \subseteq \text{ offsite } \subseteq \text{ If offsite, name of facility} \)				
emediation start date and end date. (4) Groundwater encountered: No 📉				
		low ground surface	tt. and attach	sample results.
5) Attach soil sample results and a diagram of sample locations and excaval	nons.			
Additional Comments:				
See Attached Documentation				
			· · · · · · · · · · · · · · · · · · ·	
I hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideline	of my knowledge and belief.	I further certify that or an (attached) altern	the above-described pit ative OCD-approved pl	or below-grade tank an .
Date: 11/01/2005	1.			
Printed Name/Title Jeffrey C. Blagg, Agent Signat	ure	C. Oly,	,	
Your certification and NMOCD approval of this application/closure does notherwise endanger public health or the environment. Nor does it relieve t regulations.	not relieve the operator of liab			
Printed Name/Title  Printed Name/Title	Signature_BN	L EM	Date:	IOV 1 7 2006

30045/1641	36.6853 1 108.1560		
CLIENT: BP BLAGG ENGINEERING, INC.	LOCATION NO: 81050		
P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199	C.O.C. ND: <u>10</u> 892		
FIELD REPORT: PIT CLOSURE VERIFICATION	PAGE No:		
QUAD/UNIT: GEC: 31 TWP: Z92 RNG: 12W PM: NM CNTY: ST ST: NM	DATE STARTED: 8/26/02		
QTR/FOOTAGE: 2445 N/1690 E SWINE CONTRACTOR: FLINT (BEN)	ENVIRONMENTAL NV		
EXCAVATION APPROX. NA FT. x NA FT. x NA FT. DEEP. CUBIC	YARDAGE:NA		
DISPOSAL FACILITY: REMEDIATION METHO	D: LANDFARMED		
	RMATION: OK		
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 168 FT. 5	<del></del>		
DEPTH TO GROUNDWATER: 2100' NEAREST WATER SOURCE: 21000' NEAREST SURFACE	VATER:   >   > 00		
NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPM			
SOIL AND EXCAVATION ELEU 5615 DVM CALIB. REA			
	0 = 100 ppm RF = 0.52		
SOIL TYPE: (SAND / SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER _	BEORDCK (SANOSTELLE)		
SOIL COLOR: DE SEL CRANGE TO DK. GRAY BEDROCK - DE L'E COHESION (ALL OTHERS) (NON COHESIVE) / SLIGHTLY COHESIVE / COHESIVE / HIGHLY			
CONSISTENCY (NON COHESIVE SOILS) (LOOSE) FIRM / DENSE / VERY DENSE			
PCASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLAST DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD			
MOISTURE: DRY / SLIGHTLY MOIST / MOIST / WET / SATURATED / SUPER SATURATED			
DISCOLORATION/STAINING OBSERVED: VED/ NO EXPLANATION - ENTIRE TEST HOLE	& BEDROCK SHEFACE		
HC ODOR DETECTED: (ES) / NO EXPLANATION - TEST HOLE & our sample .  SAMPLE TYPE: GRAD / COMPOSITE - # OF PTS			
ADDITIONAL COMMENTS: COLLECTED FAMPLE FROM BEDROCK SURFACE. BEDROCK-HARD, FRIABLE.			
BEDROCK BOTTOM  WITHLITED OPERATOR TO MIX IMPACTED SOIL WITH MIN IMPACTED SOIL OF LERUE WITHIN PIT AREA.			
FIELD 418.1 CALCULATIONS			
SCALE SAMP. TIME SAMPLE I.D. LAB No: WEIGHT (g) mL. FREON DILU	TION READING CALC. ppm		
O FT			
PIT PERIMETER 42 PIT	PROFILE		
OVM	<u> LUOLILL</u>		
RESULTS			
SAMPLE PID (ppm)			
1 2 4 591			
BERM 2 @ 3 @ 1			
T.H. \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \			
8.P.D. 37 1	A PPLICABLE		
la Production of the Control of the			
LAR SAUGUES			
P.O.  LAB SAMPLES  SAMPLE ANALYSIS TIME  10  10  10  10  10  10  10  10  10  1			
B.G. " BTEX (80218) "	I		
P.D. = PIT DEPRESSION; B.G. = BELOW GRADE			
T.H. = TEST HOLE; ~ = APPROX.; B = BELOW			
TRAVEL NOTES: CALLOUT: 8/26/02 -mars. ONSITE: 8/26/02 -			



## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 4'	Date Reported:	08-29-02
Laboratory Number:	23648	Date Sampled:	08-26-02
Chain of Custody No:	10092	Date Received:	08-26-02
Sample Matrix:	Soil	Date Extracted:	08-26-02
Preservative:	Cool	Date Analyzed:	08-28-02
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	4.0	0.2
Diesel Range (C10 - C28)	1.8	0.1
Total Petroleum Hydrocarbons	5.8	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

GCU #221 Blow Pit Grab Sample.

Mister of Walters Analyst

Review

# ENVIROTECH LABS

#### PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

# EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 4'	Date Reported:	08-29-02
Laboratory Number:	23648	Date Sampled:	08-26-02
Chain of Custody:	10092	Date Received:	08-26-02
Sample Matrix:	Soil	Date Analyzed:	08-28-02
Preservative:	Cool	Date Extracted:	08-26-02
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	135	1.8
Toluene	943	1.7
Ethylbenzene	496	1.5
p,m-Xylene	1,660	2.2
o-Xylene	824	1.0
Total BTEX	4,057	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery	
	Fluorobenzene	99 %	
	1,4-difluorobenzene	99 %	
	Bromochlorobenzene	99 %	

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

GCU #221 Blow Pit Grab Sample.

Mister of Walter

Réview