District 1 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 1220 S. St. Francis Dr., Santa Fe, NM 87505

Approval

Printed Name/Title DEPUTY OIL & GAS INSPECTOR, DIST.

#### State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

June 1, 2004 For drilling and production facilities, submit to appropriate NMOCD District Office.

Form C-144

OIL CONS. DIV.

DEC 0 5 2006

For downstream facilities, submit to Santa Fe <u>Prinder</u>5'06


#### Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌 DIST. 3 Type of action: Registration of a pit or below-grade tank [] Closure of a pit or below-grade tank [3] Operator: BP America Production Company Telephone: (505)326-9200 e-mail address: Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: \_ ALLEN A #1E API#: 30045 26214 U/L or Qtr/Qtr 6 Sec / T 29 NR 12 W County: San Juan NAD: 1927 🗌 1983 🔀 Latitude Surface Owner: Federal 🔲 State 🔲 Private 🔀 Indian 🔲 Pit Below-grade tank Type: Drilling Production X Disposal Volume: \_\_\_\_\_bbl Type of fluid: Construction material: Lined Unlined Double-walled, with leak detection? Yas I If not explain why not. Liner type: Synthetic Thickness mil Clay Pit Volume bbl Less than 50 feet (20 points) Depth to ground water (vertical distance from bottom of pit to seasonal 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water.) 100 feet or more ( 0 points) Yes (20 points) Wellhead protection area: (Less than 200 feet from a private domestic No ( 0 points) water source, or less than 1000 feet from all other water sources.) Less than 200 feet (20 points) Distance to surface water: (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) irrigation canals, ditches, and perennial and ephemeral watercourses.) 1000 feet or more ( 0 points) Ranking Score (Total Points) If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite \( \sqrt{\omega} \) offsite \( \sqrt{\omega} \) If offsite, name of facility . (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No 🔁 Yes 🔲 If yes, show depth below ground surface\_\_\_\_\_\_ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: See Attached Documentation I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines 🕱, a general permit 🗀, or an (attached) alternative OCD-approved plan 🗀. Date: 11/01/2005 Printed Name/Title \_\_\_\_\_Jeffrey C. Blagg, Agent Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations.

Signature Both July

50045 66614 **BLAGG ENGINEERING, INC.** LOCATION NO: \_ らしつまっ P.O. BOX 87, BLOOMFIELD, NM 87413 11296 COCR NO: (505) 632-1199 FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: 1 TYPE: PROD WELL#: 1/2 DATE STARTED: LOCATION: NAME: ALLEN DATE FINISHED: TWP: 29N RNG: 12W PM: NM CNTY: S.J ST: NM QUAD/UNIT: L SEC: ENVIRONMENTAL JUB 790'W NWISW CONTRACTOR: FUNT (BEN) QTR/FOOTAGE: /450'5 SPECIALIST: FT. x 2 FT. DEEP. CUBIC YARDAGE: FT. x /2 CLUSE \_ REMEDIATION METHOD: **DISPOSAL FACILITY:** RANGE NM U73658 FORMATION: LAND USE: PIT LOCATED APPROXIMATELY 130 FIELD NOTES & REMARKS: DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: NMOCD TPH CLOSURE STD: 5000 PPM NMOCD RANKING SCORE: OVM CALIB. READ. = 53.3 ppm SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. GAS = \_\_\_\_\_\_ ppm RF = 0.52TIME: 0945 am/pm DATE: BEDRUCE 55 @ SOIL TYPE: SAND (SILTY SAND) SILT / SILTY CLAY / CLAY / GRAVEL / OTHER 4/Tou TAN SOIL COLOR: COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD CLOSED MOISTURE: DRY / SLIGHTLY MOIST MOIST WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: YES INO EXPLANATION - GAZAL HC ODOR DETECTED: (YES) NO EXPLANATION - MUDICIALITE SAMPLE TYPE: GRAB COMPOSITE - # OF PTS. BEDROCK ADDITIONAL COMMENTS: BEDROCK BOTTOM FIELD 418.1 CALCULATIONS SCALE SAMP, TIME DILUTION READING CALC. (ppm) SAMP, ID LAB NO. WEIGHT (g) mL FREON FT 0 PIT PROFILE PIT PERIMETER OVM READING 12 -SAMPLE FIELD HEADSPACE ID 1@ 2@ 3@ 4@ A A (1)5@ 12 weu

TH LAB SAMPLES ANALYSIS TIME TOH BTEX 0825 P.D. = PIT DEPRESSION; B.G. = BELOW GRADE; B = BELOW T.H. = TEST HOLE; ~ = APPROX.; T.B. = TANK BOTTOM TRAVEL NOTES: 9/5/03



CALLOUT: \_

ONSITE:

0750



## EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Prod. 1 @ 4'	Date Reported:	09-08-03
Laboratory Number:	26518	Date Sampled:	09-05-03
Chain of Custody No:	11295	Date Received:	09-05-03
Sample Matrix:	Soil	Date Extracted:	09-05-03
Preservative:	Cool	Date Analyzed:	09-08-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	16.1	0.2
Diesel Range (C10 - C28)	22.0	0.1
Total Petroleum Hydrocarbons	38.1	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Allen A #1E.

Analyst C. Q

Mustine of Warters Review



# EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	Prod. 1 @ 4'	Date Reported:	09-08-03
Laboratory Number:	26518	Date Sampled:	09-05-03
Chain of Custody:	11295	Date Received:	09-05-03
Sample Matrix:	Soil	Date Analyzed:	09-08-03
Preservative:	Cool	Date Extracted:	09-05-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	ND	1.8	
Toluene	36.9	1.7	
Ethylbenzene	21.7	1.5	
p,m-Xylene	454	2.2	
o-Xylene	131	1.0	
Total BTEX	644		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	99 %
	1,4-difluorobenzene	99 %
	Bromochlorobenzene	99 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Allen A #1E.

Analyst C. Ciferen

Review Worters

P.O. BOX 87, BLO	NEERING, INC.  OMFIELD, NM 87413  032-1199  C.D.C. NO: 13399			
FIELD REPORT: LANDFARM/COMF	OST PILE CLOSURE VERIFICATION			
QUAD/UNIT: 4 SEC: 1 TWP: 290 RNG: 12W  QTR/FOOTAGE: WISW CONTRACTOR:	PM:NM CNTY: ST ST:NM DATE FINISHED:			
SOIL REMEDIATION:  REMEDIATION SYSTEM: CANDFARM  LAND USE: LANGE - FEE LSE	APPROX. CUBIC YARDAGE:			
FIELD NOTES & REMARKS: NMOCD RANKING SCORE DEPTH TO GROUNDWATER: >100' NEAREST WATER SOURCE:	>1000' NEAREST SURFACE WATER: >1000'			
SOIL TYPE: GAND / SILTY SAND / SILTY CLAY / CLAY / GRAVEL / OTHER  SOIL COLOR: DR. YELL. DRANGE / MED. CRAY MIX  COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE  CONSISTENCY (NON COHESIVE SOILS): COOSE / FIRM / DENSE / VERY DENSE  PLASTICITY (CHAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC  BENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD  MOISTURE: DRY / SLIGHTLY MOIST / MOISD / WET / SATURATED / SUPER SATURATED  DISCOLORATION/STAINING OBSERVED: TE / NO EXPLANATION - VARYING GRAY IN ALL SAMPLE PTS.  HC ODOR DETECTED: PES / NO EXPLANATION - TUGHT W ALL SAMPLE PTS.  SAMPLING DEPTHS (LANDFARMS): 4 - 8 (INCHES)  SAMPLE TYPE: GRAB / COMPOSITE - # OF PIS. 5				
FIELD 418	1 CALCULATIONS			
SKETCH/SAMPLE LOCATIONS ()	OVM CALIB. READ. 53.4 ppm  DVM CALIB. GAS = 100 ppm; RF = 0.52  TIME: 12:10 am (pp) DATE: 3/24/05			
BI) PERMIETEK	OVM RESULTS LAB SAMPLES			
NISE TERM WELL WEAD	SAMPLE FIELD HEADSPACE   SAMPLE   ANALYSIS TIME   RESULTS    LF-1   38.9   LF-1   TPH   1200   37.1			
METER DESIGNATION HEAD	P.C. 9/s/03  SCALE  0 FT			
TRAVEL NOTES: CALLOUT: N/A	ONSITE: 3/24/05			



## **EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons**

Client:	Blagg / BP	Proiect #:	94034-010
Sample ID:	LF - 1	Date Reported:	03-28-05
Laboratory Number:	32 <del>44</del> 5	Date Sampled:	03-24-05
Chain of Custody No:	13399	Date Received:	03-25-05
Sample Matrix:	Soil	Date Extracted:	03-25-05
Preservative:	Cool	Date Analyzed:	03-28-05
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	37.1	0.1
Total Petroleum Hydrocarbons	37.1	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Allen A #1E Landfarm 5 Pt. Composite Sample.