

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form CD 103.3
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-045-07782
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: MADDOX GAS COM B
8. Well Number #1
9. OGRID Number 5380
10. Pool name or Wildcat AZTEC PICTURED CLIFFS

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other	7. Lease Name or Unit Agreement Name: MADDOX GAS COM B
2. Name of Operator XTO Energy Inc.	8. Well Number #1
3. Address of Operator 2700 Farmington Ave., Bldg. K. Ste 1 Farmington, NM 87401	9. OGRID Number 5380
4. Well Location Unit Letter O : 880 feet from the SOUTH line and 1835 feet from the EAST line Section 27 Township 29N Range 10W NMPM County SAN JUAN	10. Pool name or Wildcat AZTEC PICTURED CLIFFS
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	
Pit or Below-grade Tank Application ☐ or Closure ☐ Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____ Pit Liner Thickness: _____ mil Below-Grade Tank: Volume _____ bbls; Construction Material _____	

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPLETION ☐
OTHER: ☐	

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐	
OTHER: REFRAC ☒	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/23/06 - 8/30/06 MIRU. ND WH. NU BOP. TOH & LD w/tbg & perf'd OPMA. PU & TIH w/strg ml, XO & tbg. TOH w/tbg. TOH & LD w/XO & strg ml. PU & TIH w/NC, pmp blr & tbg. CO fill fr/1871' - 1891' (PBTD). TOH w/tbg, pmp blr & NC. CO 4 gals for sd fr/pmp blr. TIH w/5-1/2" RBP & tbg. Set RBP @ 503'. TOH w/tbg. TIH w/retr tl & tbg. Caught & rlsd RBP @ 503'. TOH & LD w/tbg & RBP. PU & TIH w/5-1/2" pkr, SN, tbg & XO. Set pkr @ 1718'. ND BOP. NU frac stack. PT pkr & TCA to 500 psig for 5 min. Tstd OK. MIRU ac equip. A. w/1000 gals 15% NEPE HCl acid. Frac'd PC perms fr/1829' - 1875' w/67,045 gals 70Q foam, 25# linear gel, 2% KCl wtr carrying 115,300# sd. RDMO frac equip. MIRU. Ppd dwn frac string w/30 bbls 2% KCl wtr & KW. ND frac stack. NU BOP. Rlsd pkr @ 1718'. TOH & LD w/tbg. TOH & LD w/tbg & pkr. PU & TIH w/bit, XO, <<Con't att>>

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOC guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐

SIGNATURE Lorri D. Bingham TITLE REGULATORY COMPLIANCE TECH DATE 12/06/06
Type or print name LORRI D. BINGHAM E-mail address: lorri_bingham@xtoenergy.com Telephone No. 505-324-1090

For State Use Only

APPROVED BY H. Villanueva DEPUTY OIL & GAS INSPECTOR, DIST # 8 DATE DEC 08 2006
Conditions of Approval, if any:

Con't

8/30/06 – 9/1/06 SN, & tbg. RU pwr swivel. Att'd to estb circ w/50 bbls 2% KCl wtr. Unable to estb circ. Rd pwr swivel. TOH w/tbg. MIRU AFU. RU pwr swivel. Estb circ w/AFU. CO fill fr/1874' – 1891' (PBSD). Circ ½ hr. DO cmt fr/1891' – 1896' (FC). DO FC @ 1896'. DO cmt fr/1896' – 1920' (new PBSD). Circ 5 hrs. Used 35 bbls 2% KCl wtr w/AFU. Rec'd 100 BLW w/AFU. Rd pwr swivel. TOH w/tbg, XO & bit. TIH w/OEMA w/1/4" weep hole & pin, SN, 2-3/8", 4.7#, J-55, EUE 8rd tbg. ND BOP. NU WH. Ld tbg w/donut & 2-3/8" seal assy as follows; SN @ 1866'. EOT @ 1896'. PC perfs fr/1829' – 1875'. PBSD @ 1920'. RDMO.

OWU & RWTP after restim @ 1:30 P.M., 9/19/06.