

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE\*  
(See other instructions on reverse side)

FOR APPROVED  
OMB NO. 1004-0137  
RCVD DEC 5 '06  
OIL CONS. DIV.

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO. **SF-078543** **DIST. 3**

WELL COMPLETION OR RECOMPLETION REPORT AND LOG\*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other \_\_\_\_\_

b. TYPE OF COMPLETION: NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other \_\_\_\_\_

2. NAME OF OPERATOR  
**ConocoPhillips**

3. ADDRESS AND TELEPHONE NO.  
**PO Box 4289, Farmington, NM 87499 (505) 326-9700**

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)\*  
At surface **Unit G (SWNE), 1685' FNL & 1960' FEL**  
At top prod. interval reported below **SAME**  
At total depth **SAME**

6. IF INDIAN, ALLOTTEE OR TRIBE NAME \_\_\_\_\_

7. UNIT AGREEMENT NAME  
**San Juan 32-7 Unit**

8. FARM OR LEASE NAME, WELL NO.  
**San Juan 32-7 Unit #38**

9. API WELL NO. **30-045-33690**

10. FIELD AND POOL, OR WILDCAT  
**Blanco MV/ Basin DK**

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA  
**Sec. 33, T32N, R7W, NMPM**

14. PERMIT NO. \_\_\_\_\_ DATE ISSUED \_\_\_\_\_

12. COUNTY OR PARISH  
**San Juan**

13. STATE  
**New Mexico**

15. DATE SPUDDED **8/18/06**

16. DATE T.D. REACHED **8/25/06**

17. DATE COMPL. (Ready to prod.) **10/25/06**

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)\*  
**KB-6652' GL-6639'**

19. ELEV. CASINGHEAD \_\_\_\_\_

20. TOTAL DEPTH, MD & TVD **8205'**

21. PLUG, BACK T.D., MD & TVD **8200'**

22. IF MULTIPLE COMPL., HOW MANY\* **2**

23. INTERVALS DRILLED BY \_\_\_\_\_ ROTARY TOOLS **X** CABLE TOOLS \_\_\_\_\_

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)\*  
**Basin Dakota 8078' - 8186'**

25. WAS DIRECTIONAL SURVEY MADE  
**NO**

26. LOGS  
**Gamma Ray/CCL Acoustic Cement Bond Log**

27. WAS WELL CORED  
**No**

| 28. CASING RECORD (Report all strings set in well) |                 |                |           |                                 |                  |
|----------------------------------------------------|-----------------|----------------|-----------|---------------------------------|------------------|
| CASING SIZE/GRADE                                  | WEIGHT, LB./FT. | DEPTH SET (MD) | HOLE SIZE | TOP OF CEMENT, CEMENTING RECORD | AMOUNT PULLED    |
| 9-5/8" K-55                                        | 40#             | 220'           | 12-1/4"   | TOC - Surf; 187 sx              | 25 bbls (565 cf) |
| 7" J-55                                            | 20#             | 3799'          | 8-3/4"    | TOC - Surf; 551 sx              | 65 bbls (1123)   |
| 4-1/2" N=80                                        | 11.9#           | 8203'          | 6-1/4"    | TOC - 2980'; 321 sx             | 0 bbls (646 cf)  |
|                                                    |                 |                |           |                                 |                  |
|                                                    |                 |                |           |                                 |                  |

| 29. LINER RECORD |          |             |               |             | 30. TUBING RECORD |                |                 |
|------------------|----------|-------------|---------------|-------------|-------------------|----------------|-----------------|
| SIZE             | TOP (MD) | BOTTOM (MD) | SACKS CEMENT* | SCREEN (MD) | SIZE              | DEPTH SET (MD) | PACKER SET (MD) |
|                  |          |             |               |             | 2-3/8" 4.7# J-55  | 8123'          |                 |
|                  |          |             |               |             |                   |                |                 |

31. PERFORATION RECORD (Interval, size and number)  
**.34, total holes = 62 holes**  
**8078' - 8112' 1 SPF = 18 holes**  
**8120' - 8186' 2 SPF = 44 holes**

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.  
DEPTH INTERVAL (MD) **8078'-8186'** AMOUNT AND KIND OF MATERIAL USED **420 gal 15% HCL, slickwater, 14696# 20/40 TLC**

33. PRODUCTION

|                                    |                                                                                        |                                                 |
|------------------------------------|----------------------------------------------------------------------------------------|-------------------------------------------------|
| DATE FIRST PRODUCTION<br><b>SI</b> | PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump)<br><b>Flowing</b> | WELL STATUS (Producing or shut-in)<br><b>SI</b> |
| DATE OF TEST<br><b>10/24/06</b>    | HOURS TESTED<br><b>1 hr</b>                                                            | CHOKE SIZE<br><b>1/2"</b>                       |
| PROD'N FOR TEST PERIOD<br><b>0</b> | OIL-BBL<br><b>0</b>                                                                    | GAS-MCF<br><b>41 mcf</b>                        |
| WATER-BBL<br><b>0</b>              | GAS-OIL RATIO<br><b>0</b>                                                              |                                                 |

FLOW. TUBING PRESS. **SI -400 #** CASING PRESSURE **SI- 900#** 24-HOUR RATE **0** OIL-BBL **0** GAS-MCF **984 mcf** WATER-BBL **0** OIL GRAVITY-API (CORR.)

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) **To be sold** TEST WITNESSED BY \_\_\_\_\_

35. LIST OF ATTACHMENTS  
**This is a DK/MV commingled well per order DHC 2307AZ**

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Rhonda Rogers by JE TITLE **Regulatory Technician** DATE **11/15/06**

\*(See Instructions and Spaces for Additional Data on Reverse Side) **ACCEPTED FOR RECORD**

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

DEC 04 2006

NMOCD

FARMINGTON FIELD OFFICE

Tops

| SUMMARY OF POROUS ZONES: (Show all important zones for porosity and contents thereof, cored intervals; and drill-stem, tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries-): |       |         |                                                                                            | GEOLOGIC MARKERS |       |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|---------|--------------------------------------------------------------------------------------------|------------------|-------|
| San Juan 32-7 Unit #38                                                                                                                                                                                                                        |       |         |                                                                                            |                  |       |
| FORMATION                                                                                                                                                                                                                                     | TOPS  | BOTTOMS | DESCRIPTION, CONTENTS, ECT.                                                                | NAME             | TOP   |
| Ojo Alamo                                                                                                                                                                                                                                     | 2381' | 2531'   | White, cr-gr ss.                                                                           | Ojo Alamo        | 2381' |
| Kirtland                                                                                                                                                                                                                                      | 2531' | 3171'   | Gry sh interbedded w/tight, gry, fine-gr ss.                                               | Kirtland         | 2531' |
| Fruitland                                                                                                                                                                                                                                     | 3171' | 3517'   | Dk gry-gry carb sh, coal, grn silts, light-med gry, fine gr ss.                            | Fruitland        | 3171' |
| Pictured Cliffs                                                                                                                                                                                                                               | 3517' | 3701'   | Bn-Gry, fine grn, tight ss.                                                                | Pictured Cliffs  | 3517' |
| Lewis                                                                                                                                                                                                                                         | 3701' | 4781'   | Shale w/siltstone stringers                                                                | Lewis            | 3701' |
| Chacra                                                                                                                                                                                                                                        | 4781' | 5215'   | Gry fn grn silty, glauconitic sd stone w/drk gry shale                                     | Chacra           | 4781' |
| Mas. Cliff House                                                                                                                                                                                                                              | 5215' | 5634'   | ss. Ggry, fine-grn, dense sil ss.                                                          | Mas. Cliff House | 5215' |
| Menefee                                                                                                                                                                                                                                       | 5634' | 5858'   | Med-dark gry, fine gr ss, carb sh & coal                                                   | Menefee          | 5634' |
| Point Lookout                                                                                                                                                                                                                                 | 5858' | 7181'   | Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation             | Point Lookout    | 5858' |
| Gallup                                                                                                                                                                                                                                        | 7181' | 7898'   | Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. interbed sh       | Gallup           | 7181' |
| Greenhorn                                                                                                                                                                                                                                     | 7898' | 7960'   | Highly calc gry sh w/thin lmsl.                                                            | Greenhorn        | 7898' |
| Graneros                                                                                                                                                                                                                                      | 7960' | 8083'   | Dk gry shale, fossil & carb w/pyrite incl.                                                 | Graneros         | 7960' |
| Dakota                                                                                                                                                                                                                                        | 8083' | 8083'   | Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks | Dakota           | 8083' |