

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-039-29871
1. Type of Well: Oil Well <input type="checkbox"/> Gas Well <input checked="" type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator DEVON ENERGY PRODUCTION CO., L.P.		6. State Oil & Gas Lease No.
7. Address of Operator P.O. Box 6459 Navajo Dam, NM 87419		7. Lease Name or Unit Agreement Name: Northeast Blanco Unit
10. Well Location Unit Letter L : 1800 feet from the SOUTH line and 580 feet from the WEST line Section 16 Township T 30 N Range R 7 W NMPM County Rio Arriba		8. Well No. 427A
		9. Pool name or Wildcat Basin Fruitland Coal
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 6311' GL		

RCVD DEC 11 '06
OIL CONS. DIV.
DIST. 3

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- ☐ PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON
☐ TEMPORARILY ABANDON ☐ CHANGE PLANS
☐ PULL OR ALTER CASING ☐ MULTIPLE COMPLETION

☒ Other:

SUBSEQUENT REPORT OF:

- ☐ REMEDIAL WORK ☐ ALTERING CASING
☐ COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT
☐ CASING TEST & CEMENT JOB

☒ OTHER: Casing and Cement Report

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

On 11/30/06, drilled 12-1/4" hole to 285'. Ran and set 6 jts 9-5/8" 32.3# ST&C H-40 casing at 274'. Cemented casing with 200 sx (42 bbls) Class "B" neat cement with 2% CaCl, and 1/4# Flocele mixed at 15.6 ppg. Circulated 15 bbls cement to surface. Tested casing to 300 psi- low and 750 psi- high for 30 minutes. Good Test

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Kenny Rhoades TITLE Company Representative DATE 12-5-06
Type or print name Kenny Rhoades Telephone No. 505-324-5600

(This space for State use)

APPROVED BY A. Villanueva TITLE DEPUTY OIL & GAS INSPECTOR, DIST. 3 DATE DEC 11 2006
Conditions of approval, if any:

[Signature]