

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Sundry Notices and Reports on Wells

1. Type of Well
GAS

2. Name of Operator

BURLINGTON

RESOURCES OIL & GAS COMPANY LP

3. Address & Phone No. of Operator

PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. Location of Well, Footage, Sec., T, R, M

660' FNL, 660' FEL, Sec. 14, T-28-N, R-11-W, NMPM

5. Lease Number

NMSF-03179

6. If Indian, All. or
Tribe Name

7. Unit Agreement Name

Well Name & Number

Aztec #5

9. API Well No.

30-045-07529

10. Field and Pool

Fulcher Kutz PC

11. County and State

San Juan Co, NM

12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA

Type of Submission

Type of Action

☐ Notice of Intent

☐ Abandonment

☐ Change of Plans

☒ Subsequent Report

☐ Recompletion

☐ New Construction

☐ Final Abandonment

☐ Plugging Back

☐ Non-Routine Fracturing

☐ Casing Repair

☐ Water Shut off

☐ Altering Casing

☐ Conversion to Injection

☒ Other - Restimulation

13. Describe Proposed or Completed Operations

6-6-03 MIRU. ND WH. NU BOP. TOO H w/85 jts 1" tbg. Left 3 jts tbg in hole. TIH w/3 1/2" RBP, set @ 1770'. Load hole w/wtr. Circ hole clean. PT RBP to 300 psi, OK. TOO H w/RBP. PT csg to 3500 psi, failed. Wtr coming up around WH. Dig up WH. SD for weekend.

6-9-03 TIH w/pkr to 400'. Made multiple tool settings. Found hole in csg @ 0-30'. Circ out bradenhead. TOO H w/pkr. TIH w/retrieving tool. Latch RBP. TOO H w/RBP. SDON.

6-10-03 TIH w/fishing tools. Fishing. TOO H w/fish & fishing tools. Blow well & CO. SDON.

6-11-03 ND BOP. TIH, cut 7" csg away from 3 1/2" csg. TOO H. TIH w/free point. TOO H.

Cut off orange peel from 3 1/2" csg. Swedge on top of 3 1/2" csg had bad weld.

Cut off swedge. Weld slip collar on top of 3 1/2" csg. PT 3 1/2" csg to 1000 psi,

OK. Cut collar off 3 1/2" csg, weld plate between 3 1/2" x 7" csg. Weld on 2"

nipple. PT 3 1/2" csg to 3000 psi, OK. NU BOP. SDON.

6-12-03 TIH, blow well & CO to PBTD. ND BOP. NU WH. RD. Rig released.

6-18-03 MIRU. Frac existing Pictured Cliffs perforations w/272 bbl 20# linear gel,

154,700 SCF N2, 100,000# 20/40 Arizona sd. CO after frac. RD.

6-23-03 MIRU. TIH w/coiled tbg to 1746'. Blow well & CO to PBTD @ 1946'. TOO H. SDON.

6-24-03 Blow well & CO. RD.

6-30-03 MIRU. ND WH. NU BOP. TIH, tag up @ 1926'. Blow well & CO.

7-1/2-03 Blow well & CO.

7-3-03 Blow well & CO. TOO H. TIH w/59 jts 1 1/2" 2.9# J-55 IJ tbg, landed @ 1847'.

(SN @ 1846'). ND BOP. NU WH. RD. Rig released.

14. I hereby certify that the foregoing is true and correct.

Signed [Signature] Title Regulatory Supervisor Date 7/28/03

(This space for Federal or State Office use)

APPROVED BY _____ Title _____ Date _____

CONDITION OF APPROVAL, if any:

ACCEPTED FOR RECORD

AUG 07 2003

FARMINGTON FIELD OFFICE

NMOCD