submitted in lieu of Form 3160-5

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

BUREAU OF LAND MANAGEMENT	2008 DEC - 7
Sundry Notices and Reports on Wells	2008 DEC 7 PM 2 57
1. Type of Well GAS	RECEIVES. Lease Number NMSF-078384 6. If Indian, All. or Tribe Name
2. Name of Operator BURLINGTON RESCURCES OIL & GAS COMPANY LI	7. Unit Agreement Name
3. Address & Phone No. of Operator	8. Well Name & Number
PO Box 4289, Farmington, NM 87499 (505) 326-9700	Newsom B #9 9. API Well No.
4. Location of Well, Footage, Sec., T, R, M Unit G (SWNE), 1595' FNL & 1815' FEL, Sec. 7, T26	30-045-05943 10. Field and Pool Basin DK / Blanco MV 11. County and State San Juan Co., NM
Final Abandonment X Casing Repair Altering Casing 13. Describe Proposed or Completed Operations 9/7/06 MIRU Aztec 376. 9/12/06 ND WH, NU BOP -PT-OK. RIH w/tbg.	New Construction Non-Routine Fracturing Water Shut off
@ 3710°. To perf @ 3520° & squeeze w/200 sx cement. OK'd by Troy S & squeezed 1.5 bbls Neat cement. WOC. 10/5/06 RIH w/mill & tagged ceme Load hole & PT – no test. TOH w/pkr. TIH open ended to 3587°. Spotted % bbl. Pressured up to 1800# wait 15 min. RD cementers. TOH. 10/12/0 casing to 600#/30 min. Good test. D/O CIB @ 4226. Tried to test MV, onl Troy S (BLM) to squeeze MV perfs q/150 sx cement w/100% excess & try to 10/23/06 RIH w/CIBP & set @ 6290°. PT to 1500#/OK. TIH & set pkr @ MV from 4276° – 4360 w/200 sx Type V w/2% Versaset. Locked up @ 150	& Jim L with BLM on 10/3/06. Shot perf @ 3520', attempt to pump into perf. Only could ent @ 3272'. D/O cement to 3578'. Circ. Hole. 10/10/06 RIH w/packer & set @ 3532'. I 8 bbls cement. Reversed up tbg. Squeezed cement. Pumped 2.5 bbls. Pumped away 06 TIH w/bit & tagged up @ 3367'. D/O cement from 3367' – 3587'. Circ. Hole. PT ly producing water. Ran log, showed only making water. 10/20/06 Rec'd approval from
4276' - 4243'. 10/30/06 Called BLM & rec'd verbal approval from Adrienne B. to squeeze Shut-in w/1500#. WOC. 10/31/06 D/O cement from 41145' to 4369'. Circ	e balance kplug. Spotted 5.5 bbls (20 sx) cement from 4360' – 4176'. Squeezed cement. cc. Hole. PT casing to 600#/30 min. OK. 11/2/06 RIH & tagged fill @ 62 60'. Circ. Hobbit – couldn't. TOH w/tbg. Found bad jts. 11/7/06 TIH w/2-3/8", 4.7# tb g and C/O fil released rig 11/8/06.
14. I hereby certify that the foregoing is true and correct Signed Lug Lugster Patsy Clugster	