<u>District I</u>
1625 N. French Dr., Hobbs, NM 88240
<u>District II</u>
1301 W. Grand Avenue, Artesia, NM 88210
<u>District III</u>
1000 Rio Brazos Road, Aztec, NM 87410
<u>District IV</u>
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Form C-144 June 1, 2004

For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Santa Fe, NM 87505 Pit or Below-Grade Tank Registration or Closure

Is pit or below-grade tank covered by a "general plan"? Yes 🔀 No 🗌 Type of action: Registration of a pit or below-grade tank
Closure of a pit or below-grade tank Telephone: (505)326-9200 e-mail address: Operator: BP America Production Company Address: 200 Energy Ct, Farmington, NM 87401 Facility or well name: CORNELL B # 1E API#: 30045 24135 U/L or Qtr/Qtr B Sec 14 T 29 NR 12 W Longitude ______ NAD: 1927 🗌 1983 🔀 County: San Juan Latitude Surface Owner: Federal State Private Indian Pit Below-grade tank Type: Drilling Production Disposal Volume: bbl Type of fluid: \(\) RCVD DEC18'06 Construction material: DIL CONS. DIV. Double-walled, with leak detection? Yes I If no, explain why not. Lined Unlined Liner type: Synthetic Thickness mil Clay Dist. d Pit Volume ____bbl Less than 50 feet (20 points) Depth to ground water (vertical distance from bottom of pit to seasonal 50 feet or more, but less than 100 feet (10 points) high water elevation of ground water.) 100 feet or more (0 points) Yes (20 points) Wellhead protection area: (Less than 200 feet from a private domestic No (0 points) water source, or less than 1000 feet from all other water sources.) Less than 200 feet (20 points) Distance to surface water: (horizontal distance to all wetlands, playas, 200 feet or more, but less than 1000 feet (10 points) irrigation canals, ditches, and perennial and ephemeral watercourses.) 1000 feet or more (0 points) Ranking Score (Total Points) If this is a pit closure: (1) Attach a diagram of the facility showing the pit's relationship to other equipment and tanks. (2) Indicate disposal location: (check the onsite box if your are burying in place) onsite **a** offsite **b** If offsite, name of facility . (3) Attach a general description of remedial action taken including remediation start date and end date. (4) Groundwater encountered: No 🔂 Yes 🔲 If yes, show depth below ground surface ft. and attach sample results. (5) Attach soil sample results and a diagram of sample locations and excavations. Additional Comments: See Attached Documentation I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that the above-described pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines X, a general permit , or an (attached) alternative OCD-approved plan . Date: 11/01/2005 Printed Name/Title Jeffrey C. Blagg, Agent Signature Your certification and NMOCD approval of this application/closure does not relieve the operator of liability should the contents of the pit or tank contaminate ground water or otherwise endanger public health or the environment. Nor does it relieve the operator of its responsibility for compliance with any other federal, state, or local laws and/or regulations. Approval: DEPUTY OIL & GAS INSPECTOR, DIST. AT DEC 18 2006 Printed Name/Title

3004524135 **BLAGG ENGINEERING, INC.** LOCATION NO: 81146 P.O. BOX 87, BLOOMFIELD, NM 87413 (505) 632-1199 10616 COCR NO: FIELD REPORT: PIT CLOSURE VERIFICATION PAGE No: 13 WELL#: 1E TYPE: BLOW LOCATION: NAME: CORNELL DATE FINISHED: QUAD/UNIT: B SEC: 14 TWP: Z9N RNG: 12W PM: NM CNTY: SJ ST: NM **ENVIRONMENTAL** NWINE CONTRACTOR: FUNT (BEN) QTR/FOOTAGE: 1120 2 1570E ICB SPECIALIST: EXCAVATION APPROX. 12 FT. x /Z FT. x 3 FT. DEEP. CUBIC YARDAGE: CLOSE AS REMEDIATION METHOD: **DISPOSAL FACILITY:** MANM 073695 RANGE FORMATION: FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY OF FT. 5486 FROM WELLHEAD. NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: >1000 DEPTH TO GROUNDWATER: >100 NMOCD TPH CLOSURE STD: _ 5000 PPM NMOCD RANKING SCORE: OVM CALIB. READ. = 131.2 ppm SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. GAS = 250 ppm RF = 0.52TIME: 1305 am/pm DATE: 2-7-03 SOIL TYPE: (SAND) SILTY SAND / SILT / SILTY CLAY / CLAY / GRAVEL / OTHER Y RIVER COSSE REDDISH TAN SOIL COLOR: COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE CONSISTENCY (NON COHESIVE SOILS): LOOSE / FIRM / DENSE / VERY DENSE PLASTICITY (CLAYS): NON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC DENSITY (COHESIVE CLAYS & SILTS): SOFT / FIRM / STIFF / VERY STIFF / HARD MOISTURE: DRY (SLIGHTLY MOIST) MOIST / WET / SATURATED / SUPER SATURATED CLOSED DISCOLORATION/STAINING OBSERVED: YES (NO EXPLANATION -HC ODOR DETECTED: YES (NO EXPLANATION -SAMPLE TYPE: GRAB! COMPOSITE - # OF PTS. USE BACKHUE TO DIG TEST TRENUL DDITIONAL COMMENTS: VISUAL EUDENCE OF CONTAMINATION FIELD 418.1 CALCULATIONS SCALE SAMP. TIME mL FREON DILUTION READING CALC. (ppm) SAMP. ID LAB NO. WEIGHT (g) 0 FT PIT PROFILE PIT PERIMETER OVM **READING** FIELD HEADSPACE SAMPLE (ppm) 1@ 2@ 0.0 3@ 0.0 4@ 5@ 12 1 (Z) LAB SAMPLES ANALYSIS Δ 137 PRSSE P.D. = PIT DEPRESSION; B.G. = BELOW GRADE; B = BELOW T.H. = TEST HOLE; ~ = APPROX.; T.B. = TANK BOTTOM TRAVEL NOTES: CALLOUT: 2-7-03 0945 1150 7-03



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

| Client: | Blagg / BP | Project #: | 94034-010 |
|----------------------|-----------------|---------------------|-----------|
| Sample ID: | BLOW 2 @ 6' | Date Reported: | 02-10-03 |
| Laboratory Number: | 24787 | Date Sampled: | 02-07-03 |
| Chain of Custody No: | 10616 | Date Received: | 02-07-03 |
| Sample Matrix: | Soil | Date Extracted: | 02-10-03 |
| Preservative: | Cool | Date Analyzed: | 02-10-03 |
| Condition: | Cool and Intact | Analysis Requested: | 8015 TPH |

| Parameter | Concentration (mg/Kg) | Det. Limit (mg/Kg) |
|------------------------------|-----------------------|--------------------------|
| Gasoline Range (C5 - C10) | ND | 0.2 |
| Diesel Range (C10 - C28) | ND | 0.1 |
| Total Petroleum Hydrocarbons | ND | 0.2 |

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Cornell B 1E.

Analyst C. Cylum

Review Review