

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*

(See other In-
structions on
reverse side)FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

DIST. 3

5. LEASE DESIGNATION AND SERIAL NO.

NM-03402

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL: OIL ☐ GAS ☒ DRY ☐ Other ☐

7. UNIT AGREEMENT NAME

San Juan 32-8 Unit

8. FARM OR LEASE NAME, WELL NO.

San Juan 32-8 Unit 34

9. API WELL NO.

30-045-33150

10. FIELD AND POOL, OR WILDCAT

Blanco MV/Basin DK

11. SEC., T., R., M., OR BLOCK AND SURVEY
OR AREA

Sec. 22, T31N, R08W, NMPM

b. TYPE OF COMPLETION:

NEW ☒ WORK ☐ DEE ☐ PLUG ☐ DIFF. ☐ Other ☐
WELL OVER P-EN BACK RESVR

2. NAME OF OPERATOR

ConocoPhillips

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)*

At surface Unit B (NWNE) 1165' FNL & 1860' FEL

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO.

DATE ISSUED

12. COUNTY OR

PARISH

San Juan

13. STATE

New Mexico

15. DATE SPUDDED

9/29/06

16. DATE T.D. REACHED

9/25/06

17. DATE COMPL. (Ready to prod.)

11/27/06

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)*

6526' - GL

19. ELEV. CASINGHEAD

20. TOTAL DEPTH, MD & TVD

8070'

21. PLUG, BACK T.D., MD & TVD

8067'

22. IF MULTIPLE COMPL.

HOW MANY*

2

23. INTERVALS

DRILLED BY

ROTARY TOOLS

Yes

CABLE TOOLS

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)*

Blanco Mesaverde 5177' - 6069'

25. WAS DIRECTIONAL

SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

CBL/TDT/GR/CCL Log

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
9 5/8"	32.3# H-40	235'	12 1/4"	Surface: 150 sx (177 cf)	19 bbls
7"	20# J-55	3724'	8 3/4"	Surface: 690 sx (266 cf)	76 bbls
				DV Tool @ 2858'	
4 1/2"	11.6# N-80	8068'	8 1/4"	TOC 2650'; 480 sx (696 cf)	

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	7925'	
					4.7# J-55		

30. TUBING RECORD

PERFORMANCE RECORD (Interval, size and number)	ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.
Mesaverde @ .34" holes	
PLO 5518' - 6069' = 1 spf = 30 Holes	DEPTH INTERVAL (MD)
CH 5177' - 5374' = 1 spf = 23 Holes	AMOUNT AND KIND OF MATERIAL USED
MN 5403' - 5473' = 1 spf = 7 Holes	5518' - 6069' Frac w/ 107254# 20/40 brady sand & 5000# 20/40 TLC.
Total = 60 Holes	w/ 1277400 SCF N2
	5177'-5473' Frac w/ 98737# 20/40 brady san & 5000# 20/40 TLC.
	w/ 123300 SCF N2

33. PRODUCTION

DATE FIRST PRODUCTION	PRODUCTION METHOD (Flowing, gas lift, pumping-size and type of pump)	WELL STATUS (Producing or shut-in)
SI	Flow	SI
DATE OF TEST	HOURS TESTED	CHOKE SIZE
11/21/06	3	.5"
FLOW. TUBING PRESS.	CASING PRESSURE	PROD'N FOR TEST PERIOD
FTP - 170#	SICP - 460#	OIL-BBL
		GAS-MCF
		WATER-BBL
		GAS-OIL RATIO
		140 mcf
		5 BWPD

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This is a commingled Blanco MV/Basin DK per DHC # 2279AZ

W./I. hereby certify that the foregoing and attached information is complete and correct as determined from all available records

ACCEPTED FOR RECORD

SIGNED Kandis Leland TITLE Regulatory Technician DATE 02/20/06

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department of agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

FARMINGTON FIELD OFFICE
BY [Signature]

NMOC

Ojo Alamo	2322'	3076'	White, cr-gr ss.	Ojo Alamo	2322'
Kirtland			Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	
Fruitland	3076'	3422'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3076'
Pictured Cliffs	3422'	3609'	Bn-Gry, fine grn, tight ss.	Pic. Cliffs	3422'
Lewis	3609'	4175'	Shale w/siltstone stringers	Lewis	3609'
Huerfanito Bentonite	4175'	4559'	White, waxy chalky bentonite	Huerfanito Bent.	4175'
Chacra	4559'	5179'	Gry fn grn silty, glauconitic sd stone w/drck gry shale	Chacra	4559'
Mesa Verde	5179'	5380'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	5179'
Menefee	5380'	5695'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5380'
Point Lookout	5695'	6088'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5695'
Mancos	6088'	7003'	Dark gry carb sh.	Mancos	6088'
Gallup	7003'	7735'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg. interbed sh	Gallup	7003'
La Ventana	XXXX	XXXX	Wt to lt buff to med grn sl carb bent	Greenhorn	7735'
Greenhorn	7735'	7793'	Highly calc gry sh w/thin lmst.	Graneros	7793'
Graneros	7793'	7888'	Dk gry shale, fossil & carb w/pyrite incl.	Dakota	7888'
Dakota	7888'		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks		