District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Road, Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe office

Form C-144 June 1, 2004

Pit or Below-Grade Tank Registration or Closure

Operator: <u>Dugan Production Corp</u> Tele	phone: (505)325-1821 e-mail address:		_
Address: P.O. Box 420, Farmington, New Mexico 87401			-
Facility or well name: Dome Navajo 17-22-7 No. 2 API County: Sandoval Latitude 36.13728 Longitude	#: <u>30-043-20480</u> U/L or Qtr/Qtr <u>K</u> Sec 107.60153 NAD: 1927	17T22NR ner Federal □ State □ 1	_7W Private ∏ Indian ⊠
			-
Pit	Below-grade tank		OIL CONS. DI
Type: Drilling ☐ Production ☑ Disposal ☐ Workover ☐ Emergency ☐	Volume:bbl Type of fluid: Construction material:		
Lined Unlined 🗵	Double-walled, with leak detection? Yes If no		VIOI. O
Liner type: Synthetic Thickness mil Clay	Bouble-walled, with leak detection? Yes [] If no	i, explain why not.	
Pit Volume173 ±bbl	Less than 50 feet	(20 maints)	
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(20 points) (10 points)	0
high water elevation of ground water.)	100 feet or more	(0 points)	•
	100 feet of more	(o points)	
Wellhead protection area: (Less than 200 feet from a private domestic	Yes	(20 points)	
water source, or less than 1000 feet from all other water sources.)	No	(0 points)	0
	Less than 200 feet	(20 points)	
Distance to surface water: (horizontal distance to all wetlands, playas,	200 feet or more, but less than 1000 feet	(10 points)	0
irrigation canals, ditches, and perennial and ephemeral watercourses.)	1000 feet or more	(0 points)	
	Ranking Score (Total Points)	-	0
	Name of the Control of the Control		•
		1	
his is a pit closure: (1) attach a diagram of the facility showing the pit's			
r are burying in place) onsite 🛛 offsite 🔲 If offsite, name of facility_			
nediation start date and end date. (4) Groundwater encountered: No 🖬 Y	es If yes, show depth below ground surface	ft. and attach	sample results. (5)
ach soil sample results and a diagram of sample locations and excavation	S.	·	
Additional Comments:			
18' x 18' x 3'± deep unlined production pit, center located at approxim	nately 81 Feet South 48° East of wellhead		
Jse backhoe to dig into pit and sample. Submit 5-point composite sample	e from pit walls and base		
for laboratory testing.			
hereby certify that the information above is true and complete to the best has been/will be constructed or closed according to NMOCD guideling Date: December 11, 2006			
Printed Name/Title Jeffrey C Blagg, Agent	Signature Jaff	C. Black	_
Your certification and NMOCD approval of this application/closure does otherwise endanger public health or the environment. Nor does it relieve regulations.	not relieve the operator of liability should the content	ts of the pit or tank conta	minate ground water or or local laws and/or
Approval: Printed Name/Title DEPUTY CIL & GAS INSPECTOR, DIST. 27	Signature Ball Sall	Date:	EC 1 4 2006

JO 0-10 20 100 JO. 15 100 X 10 (. 60155										
	7	1/ 6	- 1			NEERING	•		LOCATION NO:	
CLIEN	r: <u> </u>	UGA	<u>N</u>	P.O. BOX	87, BLO (505) 632		', NW 0/4		COCR NO:	14725
FIE	FIELD REPORT: PIT CLOSURE VERIFICATION PAGE NO: 1 of _						of			
LOCA.	TION:	NAME	DAME N	AV 17-22-7	WELL#: 4	7 TYPE	SEP	r	DATE STARTED:	1-13-06
				TWP: 22 N RNO					DATE FINISHED:	1-13-06
				1570 FWL				1 F	ENVIRONMENTAL SPECIALIST:	TUS
EXCA	VATIO	ON A	PPROX.	NA FT. X	NA FT.	X_NA_FT	. DEEP. CI	UBIC Y	ARDAGE:	0
DISPO				AA		REMEDIA			CLOSE	15 15
LAND						0-C-14-20				
			REMARK	(S: PIT LOC		KIMATELY 81				
DEPTH 1	O GROU	NDWA	TER: >100	NEAREST W	ATER SOURCE:	>1000	NEARESTS	SURFACE	WATER: >10	00
NMOCD			^			5000 PF				
							OVM CALIB.			
SUIL	ANU	EXC	AVATIO	N DESCRIPT	ION:	•	OVM CALIB.			$\frac{RF = 0.52}{11/13}$
eou TV	'DE: 6/	ND /	CII TV SANI	0-6 SSILT/SILTY	~! AV / C! AV /	CRAVEL OTH			DPM DATE: _	D L'
SOIL COL	.OR:									
				HESIVE SLIGHTLY			COHESIVE			
				LS): (OOSE) FIRM / SLIGHTLY PLAST			/ HIGHLY PLAST	ic or		
DENSITY	(COHES	IVE CL	AYS & SILTS)	: SOFT / FIRM / ST	IFF / VERY STIFF	/ HARD				
				MOIST / WET / SAT		R SATURATED				
			ING OBSERVI	ED: YES (NO) EXP PLANATION -	LANATION -					
SAMPLE	TYPE: (GRAB (COMPOSITE	# OF PTS. 5		18 × 18 × 3	2 + X00 A	114	lings Pu	()5.75
ADDITION	IAL COM	MENTS): <u> </u>		B	ACKINE to	Die Int	b P	HY SAN	de.
							U			
SC	ALE				T	ELD 418.1 CALC				T
	ALL	1	SAMP. TIMI	E SAMP. ID	LAB NO.	WEIGHT (g)	mL FREON	DILUT	IONREADING	CALC. (ppm)
0	•	FT		<u> </u>	 	ļ				
7		L	DIMET	 =D	<u> </u>			DI.	T PROFIL	<u> </u>
N PIT PERIMETER PIT PROFILE										
SAMPOUND READING										
		i	13'	¥ -	SAMPLE	FIELD HEADSPACE (ppm)				
			×	$\overline{}$	1 @		-			•••
	[)	3@		7		-18 -	A
1					4 @ 5 @		77	7		<u> </u>
Λ	×		×	* 18 A	5-Pt- 66°	0,0] 5 4			16'
										1
	(]			1 /		1 1 1	mester. The second second
LAD CAMPIED STORE										
LAB SAMPLES SAMPLE ANALYSIS TIME BEDROCK SANDSTONE										
S-PA T/B/CL 1235										
					<u> </u>		-			
P.D. = Pff (EPRESS	ION; B.	.G. = BELOW (SRADE; B = BELOW			7			
T.H. = TEST HOLE; ~ = APPROX.; T.B. = TANK BOTTOM										
TRAVEL NOTES: CALLOUT: ONSITE: U/13/06										



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / Dugan	Project #:	94034-010
Sample ID:	Dome Navajo 17-22-7 #2	Date Reported:	11-24-06
Laboratory Number:	39219	Date Sampled:	11-13-06
Chain of Custody No:	14725	Date Received:	11-17-06
Sample Matrix:	Soil	Date Extracted:	11-20-06
Preservative:	Cool	Date Analyzed:	11-24-06
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	ND	0.2
Diesel Range (C10 - C28)	ND	0.1
Total Petroleum Hydrocarbons	ND	0.2

ND - Parameter not detected at the stated detection limit.

References:

Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments:

Pit Closures

5-Point Composite

Alex P. Peler.

Mustre of Walter Review



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / Dugan	Project #:	94034-010
Sample ID:	Dome Navajo 17-22-7 #2	Date Reported:	11-24-06
Laboratory Number:	39219	Date Sampled:	11-13-06
Chain of Custody:	14725	Date Received:	11-17-06
Sample Matrix:	Soil	Date Analyzed:	11-24-06
Preservative:	Cool	Date Extracted:	11-20-06
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)
Benzene	ND	1.8
Toluene	28.8	1.7
Ethylbenzene	27.0	1.5
p,m-Xylene	73.9	2.2
o-Xylene	14.7	1.0
Total BTEX	144	

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery	
	Fluorobenzene	97.0 %	
	1,4-difluorobenzene	97.0 %	
	Bromochlorobenzene	97.0 %	

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

Pit Closures 5-Point Composite

PRACTICAL SOLUTIONS FOR A BETTER TOMORROW

Chloride

Client:

Blagg / Dugan

Project #:

94034-010

Sample ID:

Dome Navajo 17-22-7 #2

Date Reported:

11-21-06

Lab ID#:

39219

Date Sampled:

11-13-06

Sample Matrix:

Soil

Date Received:

Preservative:

Cool

11-17-06

Condition:

Date Analyzed:

11-21-06

Cool and Intact

Chain of Custody:

14725

Parameter

Concentration (mg/Kg)

Total Chloride

234

Reference:

Standard Methods For The Examination of Water And Waste Water", 18th ed., 1992.

Comments:

Pit Closures

5-Point Composite