

Form 3160-4
(October 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN DUPLICATE*
(See other instructions on reverse side)

FOR APPROVED
OMB NO. 1004-0137

Expires: December 31, 1991

DIST. 3

WELL COMPLETION OR RECOMPLETION REPORT AND LOG*

1a. TYPE OF WELL:				OIL ☐ GAS ☒ DRY ☐ Other ☐			
b. TYPE OF COMPLETION:				NEW ☒ WORK ☐ DEE ☐ PLUG ☐ DIFF. ☐ Other ☐			
2. NAME OF OPERATOR ConocoPhillips				9. API WELL NO. 30-045-33114			
3. ADDRESS AND TELEPHONE NO. PO BOX 4289, Farmington, NM 87499 (505) 326-9700				10. FIELD AND POOL, OR WILDCAT Blanco MV/Basin DK			
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)* At surface Unit K (NESW) 2200' FSL & 1955' FWL At top prod. interval reported below Same as above At total depth Same as above				11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA Sec. 21, T31N, R08W, NMPM			
14. PERMIT NO.		DATE ISSUED		12. COUNTY OR PARISH San Juan		13. STATE New Mexico	
15. DATE SPUDDED 9/27/06	16. DATE T.D. REACHED 10/9/06	17. DATE COMPL. (Ready to prod.) 11/29/06		18. ELEVATIONS (OF, RKB, RT, BR, ETC.)* 6552' GL		19. ELEV. CASINGHEAD	
20. TOTAL DEPTH, MD & TVD 8040'		21. PLUG, BACK T.D., MD & TVD 8032'		22. IF MULTIPLE COMPL., HOW MANY* 2		23. INTERVALS DRILLED BY ROTARY TOOLS Yes CABLE TOOLS	
24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)* Blanco Mesaverde 5029' - 6074'						25. WAS DIRECTIONAL SURVEY MADE No	
26. TYPE ELECTRIC AND OTHER LOGS RUN CBL/TDT/GR/CCL Log						27. WAS WELL CORED No	
28. CASING RECORD (Report all strings set in well)							
CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD		AMOUNT PULLED	
9 5/8"	32.3# H-40	238'	12 1/4"	Surface: 150 sx (174 cf)		10 bbls	
7"	20# J-55	3716'	8 3/4"	Surface: 655 sx (1375 cf)		217 bbls	
4 1/2"	11.6# N-80	8035'	6 1/4"	DV tool set @ 2906' TOC 2780'; 490 sx (696 cf)			
29. LINER RECORD				30. TUBING RECORD			
SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2 3/8"	7750'	
					4.7# J-55		
31. PERFORATION RECORD (Interval, size and number) Mesaverde @ .34" holes PL&LM 5029' - 5511' = 1 spf = 28 Holes UM&CH 5596' - 6074' = 1 spf = 26 Holes Total = 54 Holes				32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC. DEPTH INTERVAL (MD) AMOUNT AND KIND OF MATERIAL USED 5029' - 5511' Frac w/ 60 Q Slickfoam w/ 92450 # of 20/40 AZ sand & 10000# 20/40 TLC sand. 5596' - 6074' Frac w/ 60 Q Slickfoam w/ 92639 # of 20/40 AZ sand & 10000# 20/40 TLC sand.			
33. PRODUCTION							
DATE FIRST PRODUCTION SI		PRODUCTION METHOD (Flowing, gas lift, pumping—size and type of pump) Flow				WELL STATUS (Producing or shut-in) SI	
DATE OF TEST 11/22/06	HOURS TESTED 4	CHOKE SIZE .5"	PROD'N FOR TEST PERIOD OIL-BBL	GAS-MCF 139 mcf	WATER-BBL		GAS-OIL RATIO
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE SITP - 350# FCP - 126#	OIL-BBL	GAS-MCF 831 mcf	WATER-BBL		OIL GRAVITY-API (CORR.)
34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.) To be sold						TEST WITNESSED BY	
35. LIST OF ATTACHMENTS							

This is a commingled Blanco MV & Basin Dakota per DHC # 2266AZ

W/. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED Kandis Leland TITLE Regulatory Technician DATE 12/21/06

*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and wilfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

8

Ojo Alamo	2220'	2778'	White, cr-gr ss.	Ojo Alamo	2220'
Kirtland	2778'	3035'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	2778'
Fruitland			Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	3035'
Pictured Cliffs	3035'	3460'	Bn-Gry, fine grn, tight ss.	Pic.Cliffs	3460'
Lewis	3460'	3618'	Shale w/siltstone stringers	Lewis	3618'
Huerfanito Bentonite	3618'	3737'	White, waxy chalky bentonite	Huerfanito Bent.	3737'
Chacra	3737'	4410'	Gry fn grn silty, glauconitic sd stone w/dr k gry shale	Chacra	4410'
Mesa Verde	4410'	5022'	Light gry, med-fine gr ss, carb sh & coal	Mesa Verde	5022'
Menefee	5022'	5388'	Med-dark gry, fine gr ss, carb sh & coal	Menefee	5388'
Point Lookout	5388'	5715'	Med-light gry, very fine gr ss w/frequent sh breaks in lower part of formation	Point Lookout	5715'
Mancos	5715'	6085'	Dark gry carb sh.	Mancos	6085'
Gallup	6085'	7015'	Lt gry to brn calc carb micac glauc silts & very fine gr gry ss w/irreg.interbed sh	Gallup	7015'
La Ventana	7015'	7740'	Wt to lt buff to med grn sl carb bent	Greenhorn	7740'
Greenhorn	7740'	7793'	Highly calc gry sh w/thin lmst.	Graneros	7793'
Graneros	7793'	7880'	Dk gry shale, fossil & carb w/pyrite incl.	Dakota	7880'
Dakota	7880'		Lt to dk gry foss carb sl calc sl silty ss w/pyrite incl thin sh bands clay & shale breaks		