

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I

P.O. Box 1980, Hobbs, NM 88240

**OIL CONSERVATION DIVISION**

2040 Pacheco St.

Santa Fe, NM 87505

DISTRICT II

P.O. Drawer DD, Artesia, NM 88210

DISTRICT III

1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.

30-045-24861

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

LG-3926

**SUNDRY NOTICES AND REPORTS ON WELLS**

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

7. Lease Name or Unit Agreement Name

State of NM 16

2. Name of Operator

Elm Ridge Resources, Inc.

8. Well No.

21

3. Address of Operator

PO Box 156 Bloomfield, NM 87413

9. Pool name or Wildcat

Nageezi-Gallup

4. Well Location

Unit Letter C : 890 Feet From The North Line and 1920 Feet From The West Line

Section 16 Township 23N Range 8W NMPM San Juan County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

7013 GL

**Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data**

11. **NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent date, including estimated date of starting any proposed work) SEE RULE 1103.

Elm Ridge Resources, Inc. Plug and Abandoned the above referenced well as follows on  
11-10-04: (Please see attached for procedures)

SIGNATURE

*Amy Mackey*

TITLE

Production Assistant

DATE

11/11/04

TYPE OR PRINT NAME

Amy Mackey

TELEPHONE NO. 505-632-3476 ext. 201

(This space for State Use)

APPROVED BY

*H. Villanueva*

COUNTY OIL & GAS INSPECTOR, DIST. 6

DATE

Nov. 16, 2004

CONDITIONS OF APPROVAL, IF ANY:

*k*

**Plugging procedure for the State of New Mexico 16-21.**

**11/2/04**

**Plug 1)** Set retainer @ 1575' Pumped 34 sks of standard cement to squeeze off PC (1589'-1614'). Drilled out retainer, cement, and CIBP @ 1730' to set lower plugs.

**11/10/04**

**Plug 1)** Set balanced plug from 2451'-2301'. Pumped 18 sks. of standard cement.

**Plug 2)** Set balanced plug from 2055'-1905'. Pumped 18 sks of standard cement.

**Plug 3)** Set balanced plug from 1439'-1589'. Pumped 18 sks of standard cement.

**Plug 4)** Set balanced plug from 1170'-870'. Pumped 35 sks. of standard cement.

**Plug 5)** Set balanced plug from 309'-159'. Pumped 18 sks. of standard cement.

**Plug 6)** Set balanced plug from 50' – surface. Pumped 8 sks of standard cement. 12 sks of standard cement w/ 2% CaCl.