

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

9156 CG
91650
Operator Burlington Resources Location: Unit C Sec. 30 Twp 28 Rng 6

Name of Well/Wells or Pipeline Serviced SS 28-6 #160M 30-039-25742
36721A; 36043A

Elevation _____ Completion Date 4-15-98 Total Depth 300' Land Type SF

Casing Strings, Sizes, Types & Depths 8" PVL X 20'

If Casing Strings are cemented, show amounts & types used 4 Bags Cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used
None

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 190. Soap

Depths gas encountered: None

Ground bed depth with type & amount of coke breeze used: 300', 1600 lbs
Lorisco SW

Depths anodes placed: 290, 280, 270, 260, 250, 240, 230, 215

Depths vent pipes placed: 300'

Vent pipe perforations: Bottom 150'

Remarks: _____

RECEIVED
MAR 9 1999

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

COMPANY NAME: Burlington Resources

WELL NAME: SJ 28-6 # 0M

LEGAL LOCATION: 30-28-6

COUNTY: R.O. Arriba

DATE: 4-15-98

DEPTH: 300'

BIT SIZE: 7 1/4

DRILLER NAME: Jack Ledbetter

SIZE AND TYPE OF CASING: 8" PVC X 20'

TYPE OF COKE: 20KSLD SW

AMT. OF COKE BACKFILL: 1600 lbs

VENT PIPE: 300'

PERF. PIPE: Bottom 150'

ANODE AMT. & TYPE: Anotek - Duriron

BOULDER DRILLING:

DEPTH			DEPTH			DEPTH			COMPLETION INFORMATION:			
FT.	LOG	ANODE	FT.	LOG	ANODE	FT.	LOG	ANODE	WATER DEPTHS: 190 Sec p			
									ISOLATION PLUGS:			
100			285	1.4		430						
105			270	1.4	3	435						
110			275	2.5		440						
115			280	2.0	2	445			ANODE#	DEPTH	NO COK	COKED
120			285	1.5		450			1	290	1.7	2.9
125			290	1.7	1	455			2	280	1.9	4.3
130			295	1.4		460			3	270	2.5	3.0
135			300	T.D.		465			4	260	1.8	4.9
140			305			470			5	250	2.1	5.8
145			310			475			6	240	1.7	5.8
150	1.2		315			480			7	230	2.0	5.3
155	1.7		320			485			8	215	3.1	5.4
160	1.6		325			490			9			
165	1.4		330			495			10			
170	1.4		335			500			11			
175	1.3		340			505			12			
180	1.3		345			510			13			
185	1.2		350			515			14			
190	1.1		355			520			15			
195	1.1		360			525			16			
200	1.4		365			530			17			
205	1.1		370			535			18			
210	1.4		375			540			19			
215	2.0	8	380			545			20			
220	1.3		385			550			21			
225	1.0		390			555			22			
230	1.6	7	395			560			23			
235	2.7		400			565			24			
240	2.7	6	405			570			25			
245	1.9		410			575			26			
250	1.7	5	415			580			27			
255	2.0		420			585			28			
260	1.8	4	425			590			29			
						595			30			

LOGGING VOLTS: 11.83

VOLTAGE SOURCE: Auto

TOTAL AMPS: 11.8

TOTAL G/B RESISTANCE: 1.0

REMARKS: