

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Burlington Resources Location: Unit Sec. 12 Twp 27 Rng 6

Name of Well/Wells or Pipeline Served SJ 28-6 #161 M

30-039-25768

Elevation Completion Date 5-11-98 Total Depth 300' Land Type SF

Casing Strings, Sizes, Types & Depths 8" PVC X 20'

If Casing Strings are cemented, show amounts & types used 4 Bag cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. 100 S&P

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 300' = 1600 lbs

LORESCO SW

Depths anodes placed: 290, 280, 260, 250, 240, 215, 205, 195

Depths vent pipes placed: 300'

Vent pipe perforations: Bottom 150'

Remarks:

RECEIVED
MAR - 9 1999

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be include

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

COMPANY NAME: Burlington Resources

WELL NAME: SJ 28-6 # 161 M

SF-079363

LEGAL LOCATION: NE SE 12-27-6

COUNTY: R. O. Arriba

DATE: 5-11-98

TYPE OF COKE: Loresco SW

DEPTH: 300

AMT. OF COKE BACKFILL: 1620 lbs

BIT SIZE: 6 3/4

VENT PIPE: 300'

DRILLER NAME: Jack Ledbetter

PERF. PIPE: Bottom 150'

SIZE AND TYPE OF CASING: 8" PVC x 20'

ANODE AMT. & TYPE: Anotec - Duriron

BOULDER DRILLING:

DEPTH			DEPTH			DEPTH			COMPLETION INFORMATION:
FT.	LOG	ANODE	FT.	LOG	ANODE	FT.	LOG	ANODE	WATER DEPTHS: 100' 5.00
									ISOLATION PLUGS:
100			265	1.9		430			
105			270	1.8		435			
110			275	2.0		440			
115			280	2.6	2	445			
120			285	2.4		450			
125			290	2.6	1	455			
130			295	2.0		460			
135			300	T.O.		465			
140			305			470			
145			310			475			
150	1.1		315			480			
155	1.4		320			485			
160	2.6		325			490			
165	3.1		330			495			
170	3.0		335			500			
175	3.9		340			505			
180	3.1		345			510			
185	2.5		350			515			
190	2.8		355			520			
195	2.9	8	360			525			
200	2.4		365			530			
205	2.8	7	370			535			
210	2.7		375			540			
215	2.8	6	380			545			
220	1.7		385			550			
225	1.2		390			555			
230	1.8		395			560			
235	2.1		400			565			
240	2.2	5	405			570			
245	2.3		410			575			
250	2.4	4	415			580			
255	2.4		420			585			
260	1.9	3	425			590			
						595			

LOGGING VOLTS: 12.87

VOLTAGE SOURCE: Auto

TOTAL AMPS: 15.8

TOTAL G/B RESISTANCE: .81

REMARKS:

DPT# 23746A/33865 A

AFE# ?

RAC

2680.00

150.75

2830.75

Larry Byars