

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Burlington Location: Unit C Sec 24 Twp 30 Rng 11

Name of Well/Wells or Pipeline Served LLOYD #2A
30-045-29531

Elevation _____ Completion Date 6-25-98 Total Depth _____ Land Type _____

Casing Strings, Sizes, Types & Depths 20' 8" surface
CASING

If Casing Strings are cemented, show amounts & types used _____
NO

If Cement or Bentonite Plugs have been placed, show depths & amounts used _____
NO

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. DAMP 100'

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 315' w 1000/lbs
COKE breeze

Depths anodes placed: 300 295 290 285 280 275 270 260

Depths vent pipes placed: 315

Vent pipe perforations: bottom 200

Remarks: _____

RECEIVED
MAR - 9 1999
OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

TIERRA DYNAMICS COMPANY

DEEP WELL GROUNDED LOG DATA SHEET

COMPANY NAME: BURLINGTON RESOURCES

SEP 24-T30-R11W

WELL NAME: LOVELL 2A

LEGAL LOCATION: 24T30-R11W

COUNTY: SAN JUAN NM

DATE: 6-25-78

TYPE OF COKE: SYV

DEPTH: 320

AMT. OF COKE BACKFILL: 1000 #

BIT SIZE: 6 1/4

VENT PIPE: 300

DRILLER NAME: MERCER

PERF. PIPE: 200-300

SIZE AND TYPE OF CASING: 20" 8" PVP

ANODE AMT. & TYPE: 8

BOULDER DRILLING:

DEPTH			DEPTH			DEPTH			COMPLETION INFORMATION:
FT.	LOG	ANODE	FT.	LOG	ANODE	FT.	LOG	ANODE	WATER DEPTHS: 100-110
									ISOLATION PLUGS:
100	1.2		265	2.1		430			
105	1.8		270	2.0		435			
110	1.9		275	2.4		440			
115	1.7		280	3.0		445			
120	1.6		285	1.9		450			
125	2.0		290	2.0		455			
130	2.3		295	2.2		460			
135	2.8		300	1.8		465			
140	1.7		305	1.4		470			
145	1.8		310	2.1		475			
150	1.6		315	2.1		480			
155	1.6		320			485			
160	1.9		325			490			
165	1.1		330			495			
170	1.7		335			500			
175	2.1		340			505			
180	2.2		345			510			
185	2.2		350			515			
190	2.5		355			520			
195	2.1		360			525			
200	2.0		365			530			
205	2.1		370			535			
210	2.0		375			540			
215	2.0		380			545			
220	2.0		385			550			
225	1.5		390			555			
230	1.3		395			560			
235	1.9		400			565			
240	1.7		405			570			
245	2.2		410			575			
250	2.2		415			580			
255	2.0		420			585			
260	2.2		425			590			
						595			

LOGGING VOLTS: 12.6

VOLTAGE SOURCE: BAT.

TOTAL AMPS: 19.1

TOTAL G/B RESISTANCE: 0.1059

REMARKS: