

submitted in lieu of Form 3160-5  
**UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT**

2007 JAN 22 PM 3:42

Sundry Notices and Reports on Wells

RECEIVED  
BLM  
210 FARMINGTON NM

1. **Type of Well**  
GAS

2. **Name of Operator**  
ConocoPhillips

3. **Address & Phone No. of Operator**  
PO Box 4289, Farmington, NM 87499 (505) 326-9700

4. **Location of Well, Footage, Sec., T, R, M**  
Unit M (SWSW), 460' FSL & 295' FWL, Sec. 25, T29N, R6W, NMPM

5. **Lease Number**  
NM-012671

6. **If Indian, All. or Tribe Name**

7. **Unit Agreement Name**

8. **San Juan 29-6 Unit Well Name & Number**

9. **SJ 29-6 Unit #81F API Well No.**  
30-039-29863

10. **Field and Pool**  
Basin Dakota/Blanco Mesa Verde

11. **County and State**  
Rio Arriba Co., NM

**12. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OTHER DATA**

Type of Submission	Type of Action
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Abandonment <input type="checkbox"/> Change of Plans
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Recompletion <input type="checkbox"/> New Construction
<input type="checkbox"/> Final Abandonment	<input type="checkbox"/> Plugging <input type="checkbox"/> Non-Routine Fracturing
	<input type="checkbox"/> Casing Repair <input type="checkbox"/> Water Shut off
	<input type="checkbox"/> Altering Casing <input type="checkbox"/> Conversion to Injection

☒ Other - Casing Report

**13. Describe Proposed or Completed Operations**

1/06/07 MIRU Bearcat #4. PT 9 58/8" casing to 600 #/30 min- good test. RIH w/8 3/4" bit. D/O cement & ahead to 3625' intermediate depth. Circ hole. RIH w/84 jts 7" 20# J-55 ST & C casing set @ 3625'. RU to cement. 1/13/07 Pumped pre-flush of 10 bbls H2O/10 bbls Mudflush/10 bbls H2O. Pumped Scavenger 19 sx(57 cf - 10 bbls) Premium Lite Cement w/3% CaCl, .25 #/sx Cello-flake, 5 #/sx LCM-1, .4% FL-52, & .4% SMS. Lead- pumped 470sx(1001cf-178 bbls) Premium Lite Cement w/3% CaCl, .25 #/sx Cello-Flakes, 5 #/sx LCM-1, .4% FL-52, & .4% SMS. Tail-pumped 90 sx(124cf- 22 bbls) Type III Cement w/1% CaCl, .25 #/sx Cello-Flakes & .2% FL-52. Plug down @ 23:21 hrs on 1/13/07. Circ 45 bbls cement to reserve pit. RD cementers & ND BOP. Install B section.

1/14/07 NU. PT 7" casing to 1500 #/30 min- good test. RIH w/6 1/4" bit. D/O cement, tagged @ 3578' & ahead to 7787' (TD). TD reached o 1/18/07. Circ hole. RIH w/162 jts 4 1/2" 10.5# J-55 ST & C, & 21 jts 4 1/2" 11.6# J-55 LT & C casing set @ 7785'. RU to cement. 1/19/07 Pumped pre-flush of 10 bbls mudflush, & 2 bbls H2O. Pumped Scavenger 9 sx(27cf- 5 bbls) Premium Lite HS FM Cement w/.25 #/sx Cello-Flake, .3% CD-32, 6.25 #/sx LCM-1 & 1% FL-52, followed w/276 sx(546cf- 97 bbls) Premium Lite HS FM Cement w/.25 #/sx Cello-Flake, .3% CD-32, 6.25 #/sx LCM-1 & 1% FL-52. Plug down @ 0218hrs on 1/20/07. ND BOP. RR @0900 hrs 1/20/07.

The casing TOC & PT will be conducted by the completion rig and results shown on next report.

**14. I hereby certify that the foregoing is true and correct.**

Signed Tracey N. Monroe Tracey N. Monroe Title Regulatory Technician Date 1/22/07

(This space for Federal or State Office use)

APPROVED BY \_\_\_\_\_ Title \_\_\_\_\_ Date JAN 25 2007

CONDITION OF APPROVAL, if any:

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD

FARMINGTON FIELD OFFICE