submitted in lieu of Form 3160-5

UNITED STATES	•	
DEPARTMENT OF T	HE	INTERIOR
BUREAU OF LAND N	ИA	NAGEMENT

Sundry Notices and Repo	orts on Wells			
1. Type of Well GAS		07 FEB - 5 PM 3: 48 RECEIVED BLM	5. 6.	Lease Number NMNM-05791 If Indian, All. or Tribe Name
2. Name of Operator ConocoPhillips	2	10 FARMINGTON NM	7.	Unit Agreement Name RCVD FEB9'07 OIL CONS. DIV.
3. Address & Phone No. of Oper	ator		- 8.	DIST. 3 Well Name & Number
PO Box 4289, Farmington, NM 87499 (505) 326-9700			9.	Graham B WN Fed #4 API Well No.
4. Location of Well, Footage, Sec., T, R, M Sec., T—N, R—W, NMPM			10.	30-045-11580 Field and Pool
Unit G (SWNE), 1610' FNL & 1555' FEL, Sec. 10, T27N, R8W NMPM		11.	Blanco PC South County and State San Juan, NM	
Type of Submission: ☐ Notice of Intent ☐ Subsequent Report ☐ Final Abandonment	Type of Action: ☐ Abandonment ☐ Recompletion ☐ Plugging ☐ Casing Repair ☐ Altering Casing	Change of Plans New Construction Non-Routine Fracturing Water Shut-off Conversion to Injection		
13. Describe Proposed or Complet 10/11/06 MIRU A-Plus #4. Check END WH, NU BOP. TOOH w/ tbg., TPT csg to 500 PSI, leaking. Spot Plut TOC w/ excess @ 1785'. TOOH, W 23 sx type 3 cmnt. (1.32 yield, 14.8 holes in csg. Tagged TOC plug #2 & location gave go ahead to fill csg. w verbal approval to go ahead on 10/1 mix water) TOC unknown inside & o spoke w/ BLM rep on 10/18/06-fill (surf. plug) w/107 sx type 3 cmnt (BH valve & circ. good cmnt out BH. 10/19/06 check TOC in csg down RD rig, cut off anchors & released	BH & CSG PSI- both flow ITH w/ CR to 2119'. PT the second	og. to 1000 PSI, holding. Sting of 25 sx type 3 cmnt. (1.32 yield, 1751'. PT csg., leaking. Load csg. water) est. TOC w/ excess @ 1. sg. from 1194' to 196'. TOOH w/00' to cover holes & squeeze out (1194' to 200') w/ 82 sx type 3 of g. WOC. CK PSI- csg. 9# & BH & pumped cmnt thru csg. holes & gal/sx, mix water) Filled csg. ning tbg. Squeeze 77 sx outside, annulus full of cmnt. Top off co	out & load 14.8 #/g . and pum 123'. TOO ' pkr. BLI side of c cmnt. (1.3 3#. TIH s to surf & BH w/ csg. WC	d & circ. csg. clean w/ 45 bbls. pal, 6.3 gal/sx, mix water) est. ped Plug #2 (1455' - 1235') w/ OH, WOC. TIH w/ pkr to look for M inspector Ernest Saentz on csg. Steve Mason w/ BLM gave 32 yield, 14.8 #/gal, 6.3 gal/sx, & tagged TOC plug #3 @ 537', out BH. Pumped Plug #4 cmnt. SI, closed csg valve, opene OC. Dig out WH & anchors.
14. I hereby certify that the forego	oing is true and correct. Philana Tho		y Tech	Date <u>2/5/07</u>
(This space for Federal or State Office	ce use)			ACCEPTED FOR BEFORD
APPROVED BY CONDITION OF APPROVAL, if an	Title			Date FER 0.8.2007

NMOCD 5