District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Road, Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico Energy Minerals and Natural Resources

Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505

Form C-144 June 1, 2004 For drilling and production facilities, submit to appropriate NMOCD District Office.
For downstream facilities, submit to Santa Fe

Pit or Below-Grade Tank Registration or Closure Is pit or below-grade tank covered by a "general plan"? Yes 🗷 No

Operator: BP America Production Company Telephone	ne: (505)326-9200 e-mail address:	
Address: 200 Energy Ct, Farmington, NM 87401		
Facility or well name: GCU # Z44 API #:3	0045 11690 U/Lor Otr/Otr J	Sec 36 T 28 NR 12 W
	Longitude	
Surface Owner: Federal State Private Indian		
Pit	Below-grade tank	
Type: Drilling Production Disposal	Volume:bbl Type of fluid: /	
Workover Emergency	Construction material: Double-walled, with leak detection? Yes I If no	
Lined Unlined	Double-walled, with leak detection? Yes If no	, explain why not.
Liner type: Synthetic Thicknessmil Clay [/ V /	<u> </u>
Pit Volumebbl		
	Less than 50 feet	(20 points)
Depth to ground water (vertical distance from bottom of pit to seasonal	50 feet or more, but less than 100 feet	(10 points)
high water elevation of ground water.)	100 feet or more	(0 points)
	Yes	(20 points)
Wellhead protection area: (Less than 200 feet from a private domestic	No	(0 points)
water source, or less than 1000 feet from all other water sources.)	140	(o points)
Distance to surface water: (horizontal distance to all wetlands, playas,	Less than 200 feet	(20 points)
irrigation canals, ditches, and perennial and ephemeral watercourses.)	200 feet or more, but less than 1000 feet	(10 points)
inigation carais, attores, and percinnal and epitemetal watercourses.	1000 feet or more	(0 points)
	Ranking Score (Total Points)	0
If this is a pit closure: (1) Attach a diagram of the facility showing the pit	's relationship to other equipment and tanks (2) India	cate disposal location: (check the onsite box if
your are burying in place) onsite 🔀 offsite 🗌 If offsite, name of facility_		
remediation start date and end date. (4) Groundwater encountered: No		
(5) Attach soil sample results and a diagram of sample locations and excava		
Additional Comments:	41013.	
See Attached Documentation		\$2573 \$74 \$455.00
See Attached Documentation		The same figures and strike the
		\$7.50 \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\
	· · · · · · · · · · · · · · · · · · ·	
I hereby certify that the information above is true and complete to the bes	t of my knowledge and heliaf. I further continue that	the above described pit or below goods to be
has been/will be constructed or closed according to NMOCD guidelin	es 🔀, a general permit 🗌 , or an (attached) alterni	ative OCD-approved plan
!		
Date:11/01/2005	111.0	
	ture Juffy C. Sligy	
Your certification and NMOCD approval of this application/closure does otherwise endanger public health or the environment. Nor does it relieve regulations.		
Approval: Printed Name/Title	Signature B. S. Bell	Date: JAN 3 0 2007

FIELD REPORT: PIT CLOSURE VERIFICATION PAGE NO:		
QUAD/UNIT: \$\int Sec: 36 \text{ twp: 28\infty rng: 12\infty pm: pm cnty: 5\int st: pm \text{ environmental specialist: } \text{NV} \\ \text{QTR/FOOTAGE: 1850'S/Z510'E } \text{N\omegasternst} \text{CONTRACTOR: FL\omegasternst} \text{(BF\omegasternst)} \text{Specialist: } \text{NV} \\ EXCAVATION APPROX. 30 FT. x 35 FT. x 3 FT. DEEP. CUBIC YARDAGE:		
QUADJUNIT: J SEC: 36 TWP: 250 RNG: 120 PM: NAT CNTY: 5 J ST: NAT QTR/FOOTAGE: 1850 5 Z 510 E NW(SE CONTRACTOR: FLAT (BED) SPECIALIST: NV EXCAVATION APPROX. 30 FT. x 35 FT. x 3 FT. DEEP. CUBIC YARDAGE: 100 DISPOSAL FACILITY: 0N-SITE REMEDIATION METHOD: LANDERRY LAND USE: RANGE - NAMED LEASE: NATION STORE FORMATION: 0K FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 219 FT. NGW FROM WELLHEAD. DEPTH TO GROUNDWATER: 2100 NEAREST WATER SOURCE: 21000 NEAREST SURFACE WATER: 21000 NMOCD RANKING SCORE: 0 NMOCD TPH CLOSURE STD: 5000 PPM SOIL AND EXCAVATION DESCRIPTION: 0VM CALIB. READ. = 51.1 PPM CHECK OVM CALIB. GAS = 100 PPM RF = 0.52 TIME: 1100 ampt DATE: 5/21 D3 SOIL TYPE: SAND/ SILTY SAND / SILT (SULTX CLAY) CLAY / GRAVEL / OTHER BEDROCK (CAYSTONE - SALDSTONE)		
QTR/FOOTAGE: /850 5 / Z510 E NO/SE CONTRACTOR; FLINT (BEN) SPECIALIST: NV EXCAVATION APPROX. 30 FT. x 35 FT. x 3 FT. DEEP. CUBIC YARDAGE: 100 DISPOSAL FACILITY: DN-51TE REMEDIATION METHOD: LANDERRY LAND USE: RANGE - NANATO LEASE: // NO 78391 FORMATION: OR FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 219 FT. NG N WELLHEAD. DEPTH TO GROUNDWATER: >100' NEAREST WATER SOURCE: >1000' NEAREST SURFACE WATER: >1000' NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: 5000 PPM SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. READ. = 51.1 ppm CHECK OVM CALIB. GAS = 100 ppm RF = 0.52 TIME: 110 ampt DATE: 5/21 D3 SOIL TYPE: SAND/ SILTY SAND / SILT / SILTX CLAY / GRAVEL / OTHER BEDROCK (CMYSTONE - SANDSTONE)		
DISPOSAL FACILITY: DISPOSAL FACILITY: SWAF, USE NAME - SWAF, USE NAME - NAME - NAME - NAME - NAME - LEASE: FORMATION: FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 219 FT. NGRW FROM WELLHEAD. DEPTH TO GROUNDWATER: NEAREST WATER SOURCE: NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. READ. = 51.1 ppm CHECK OVM CALIB. GAS = 100 ppm RF = 0.52 TIME: 1:10 am/pm DATE: 5/2103 SOIL TYPE: GAND/ SILTY SAND/ SILT (SULTX CLAY / GRAVEL / OTHER BEDIOCIK (CMYSTONE - SANDSTONE)		
LAND USE: RANGE - NANASO LEASE: NMO78391 FORMATION: OR FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 219 FT. NGW FROM WELLHEAD. DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: >1000 NEAREST WATER SOURCE: >1000 PPM SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. READ. = 51.1 ppm CHECK OVM CALIB. GAS = 100 ppm RF = 0.52 TIME: 1:10 am/pm DATE: 5/2103 SOIL TYPE: GAND/ SILTY SAND / SILT / SULTX CLAY / GRAVEL / OTHER BEDIOOK (CMYSTONE - SANDSTONE)		
FIELD NOTES & REMARKS: PIT LOCATED APPROXIMATELY 219 FT. NGRW FROM WELLHEAD. DEPTH TO GROUNDWATER: >100 NEAREST WATER SOURCE: >1000 NEAREST SURFACE WATER: >1000 NEAREST SURFACE NEAREST SURFACE WATER: >1000 NEAREST SURFACE NEAREST SURFACE NEAREST SURFACE NEAREST SURFACE NEAREST SURFACE NEAREST SURFACE NEA		
DEPTH TO GROUNDWATER: >100' NEAREST WATER SOURCE: >1000' NEAREST SURFACE WATER: >1000' NMOCD RANKING SCORE: O NMOCD TPH CLOSURE STD: 5000 PPM SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. READ. = 51.1 ppm CHECK OVM CALIB. GAS = 100 ppm RF = 0.52 TIME: 1:10 am/pm DATE: 5/2103 SOIL TYPE: SAND/ SILTY SAND / SILT (SILTX CLAY) CLAY / GRAVEL / OTHER BEDIOOK (CAYSTONE - SANDSTONE)		
NMOCD RANKING SCORE: NMOCD TPH CLOSURE STD: SOO PPM SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. READ. = ST. / ppm CHECK OVM CALIB. GAS = /O ppm RF = 0.52 TIME: /O am/pm DATE: S/21 O 3 SOIL TYPE: SAND/ SILTY SAND / SILT (SILTX CLAY) CLAY / GRAVEL / OTHER BEDROOLK (CAYSTONE SANDSTONE)		
SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. READ. = 51.1 ppm CHECK OVM CALIB. GAS = 100 ppm RF = 0.52 TIME: 1:10 am/pm DATE: 5/21 03 SOIL TYPE: SAND/ SILTY SAND / SILT (SILTX CLAY) CLAY / GRAVEL / OTHER BEDIOCK (CAYSTONE - SANDSTONE)		
SOIL AND EXCAVATION DESCRIPTION: OVM CALIB. GAS = 100 ppm RF = 0.52 TIME: 1:10 am/pm DATE: 5/21/03 SOIL TYPE: GAND/ SILTY SAND / SILT / SILTX CLAY / GRAVEL / OTHER BEDROCK (CMYSTONE - SANDSTONE)		
SOIL TYPE: SANDI SILTY SAND I SILT ISILTY CLAY I GRAVEL I OTHER BEDROCK (CMYSTONG - SANDSTONE)		
SOIL TYPE: SANDI SILTY SAND I SILT I (SILTX CLAY) CLAY I GRAVEL I OTHER BEDROCK (CAYSTONE - SANDSTONE)		
COHESION (ALL OTHERS): NON COHESIVE / SLIGHTLY COHESIVE / COHESIVE / HIGHLY COHESIVE		
CONSISTENCY (NON COHESIVE SOILS): LOOSE / LIBM / DENSE / VERY DENSE PLASTICITY (CLAYS): LOON PLASTIC / SLIGHTLY PLASTIC / COHESIVE / MEDIUM PLASTIC / HIGHLY PLASTIC		
DENSITY (COHESIVE CLAYS & SILTS): SOFT / EIRW STIFE VERY STIFF / HARD		
MOISTURE: DRY / STIGHTLY MOISD MOISD WET / SATURATED / SUPER SATURATED DISCOLORATION/STAINING OBSERVED: CED/ NO EXPLANATION - LT. GRAY TO BLACK		
HC ODOR DETECTED: (ES) NO EXPLANATION - EXCAUATED SOIL		
SAMPLE TYPE: GRADI COMPOSITE . # OF PTS		
BOROCK		
FIELD 418,1 CALCULATIONS		
SCALE SAMP. TIME SAMP. ID LAB NO. WEIGHT (g) mL FREON DILUTION READING CALC. (ppm)		
0 FT		
PIT PERIMETER 100 PIT PROFILE		
READING		
SAMPLE FIELD HEADSPACE A 30 A		
10 5 647 20 BERON		
Been 30		
A 5 0 5 1		
SAMPLE 500 5 BEDROCK of		
0/5colored		
B.6.		
LAB SAMPLES		
P.D. SAMPLE ANALYSIS TIME		
W 2 17 17 17 17 17 17 17 17 17 17 17 17 17		
R.G. ARTA "BTEX (80218) "		
(BOTH PASSED)		
B.S		



EPA METHOD 8015 Modified Nonhalogenated Volatile Organics Total Petroleum Hydrocarbons

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 5'	Date Reported:	05-27-03
Laboratory Number:	25712	Date Sampled:	05-22-03
Chain of Custody No:	10877	Date Received:	05-22-03
Sample Matrix:	Soil	Date Extracted:	05-23-03
Preservative:	Cool	Date Analyzed:	05-27-03
Condition:	Cool and Intact	Analysis Requested:	8015 TPH

Parameter	Concentration (mg/Kg)	Det. Limit (mg/Kg)
Gasoline Range (C5 - C10)	127	0.2
Diesel Range (C10 - C28)	305	0.1
Total Petroleum Hydrocarbons	432	0.2

ND - Parameter not detected at the stated detection limit.

References: Method 8015B, Nonhalogenated Volatile Organics, Test Methods for Evaluating Solid Waste,

SW-846, USEPA, December 1996.

Comments: GCU #244 Blow Pit Grab Sample.

Analyst C. Opposition

Mistering Walter



EPA METHOD 8021 AROMATIC VOLATILE ORGANICS

Client:	Blagg / BP	Project #:	94034-010
Sample ID:	1 @ 5'	Date Reported:	05-27-03
Laboratory Number:	25712	Date Sampled:	05-22-03
Chain of Custody:	10877	Date Received:	05-22-03
Sample Matrix:	Soil	Date Analyzed:	05-27-03
Preservative:	Cool	Date Extracted:	05-23-03
Condition:	Cool & Intact	Analysis Requested:	BTEX

Parameter	Concentration (ug/Kg)	Det. Limit (ug/Kg)	
Benzene	338	1.8	
Toluene	1,850	1.7	
Ethylbenzene	781	1.5	
p,m-Xylene	2,210	2.2	
o-Xylene	1,140	1.0	
Total BTEX	6,320		

ND - Parameter not detected at the stated detection limit.

Surrogate Recoveries:	Parameter	Percent Recovery
	Fluorobenzene	97 %
	1,4-difluorobenzene	97 %
•.	Bromochlorobenzene	97 %

References:

Method 5030B, Purge-and-Trap, Test Methods for Evaluating Solid Waste, SW-846, USEPA,

December 1996.

Method 8021B, Aromatic Volatile Organics, Test Methods for Evaluating Solid Waste, SW-846,

USEPA, December 1996.

Comments:

GCU #244 Blow Pit Grab Sample.