

3638

30-039-2117L

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit K Sec. 13 Twp 25 Rng 06

Name of Well/Wells or Pipeline Serviced _____

CANYON LA190 UNIT #288

Elevation 6633' Completion Date 7/24/93 Total Depth 430' Land Type F

Casing Strings, Sizes, Types & Depths 6 1/2" SET 59' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 12 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT A WATER SEEP AT 70', AND A MAJOR

WATER VEIN AT 221'. WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 430' DEPTH.

USED 124 SACKS OF ASBURY 2185 (6200#)

Depths anodes placed: 291', 285', 278', 271', 266', 260', 254', 248', 176', 170', 136', 130', 124', 116', + 110'.

Depths vent pipes placed: SURFACE TO 430'.

Vent pipe perforations: BOTTOM 330'.

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.

If Federal or Indian, add Lease Number.