

3875

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

30-045-28969

Operator Meridian Oil Inc. Location: Unit L Sec. 17 Twp. 27 Rng. 11

Name of Well/Wells or Pipeline Serviced _____

WHITLEY A #100

Elevation _____ Completion Date 9/13/93 Total Depth 446' Land Type I

Casing Strings, Sizes, Types & Depths 9 1/2" SET 78' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 16 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,
Salty, Sulphur, Etc. HIT WATER AT 85', AND MORE FRESH WATER

AT 250'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 446' Depth,

Used 126 SACKS OF ASBURY 218R (6300#)

Depths anodes placed: 418', 411', 404', 397', 387', 375', 369', 342', 335', 329', 321', 314', 307', 278', + 271'

Depths vent pipes placed: SURFACE TO 446'

Vent pipe perforations: BOTTOM 340'

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.