

30-045-21695

5225

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator KOCH EXPLORATION COMPANY Location: Unit P Sec. 21 Twp 31 Rng 10

Name of Well/Wells or Pipeline Serviced LAMBE-3-A

Elevation 6219 Completion Date 8-31-82 Total Depth 300' Land Type* F-NM-03187

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used NONE

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. @-140' AND 280' SULPHUR & ALKALI

Depths gas encountered: NONE

Type & amount of coke breeze used: METALLURGICAL--1800#

Depths anodes placed: 270'-260'-240'-210'-200'-190'-180'-170'-160'-150'-

Depths vent pipes placed: 290'

Vent pipe perforations: FROM 150' DOWN

Remarks:

RECEIVED

MAR 16 1990

OIL CON. DIV

EXT. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CORROSION CONTROL CO.

P. O. BOX 179 - PHONE 334-6361
AZTEC, NEW MEXICO 87410

Drilling Log (Attach Hereto). ☐

Completion Date August 31, 1982

Well Name <u>Lanbe #3-A</u>		Location <u>Kock</u>			
Type & Size Bit Used <u>6 3/4"</u>				Work Order No.	
Anode Hole Depth <u>300'</u>	Total Drilling Rig Time <u>7 hrs</u>	Total Lbs. Coke Used <u>1800 #</u>	Lost Circulation Mat'l Used	No. Sacks Mud Used	
Anode Depth					
#1 <u>270</u>	#2 <u>260</u>	#3 <u>240</u>	#4 <u>210</u>	#5 <u>200</u>	#6 <u>190</u>
#7 <u>180</u>	#8 <u>170</u>	#9 <u>160</u>	#10 <u>150</u>		
Anode Output (Amps)					
#1 <u>3.0</u>	#2 <u>3.5</u>	#3 <u>3.7</u>	#4 <u>4.1</u>	#5 <u>4.9</u>	#6 <u>4.7</u>
#7 <u>4.2</u>	#8 <u>5.1</u>	#9 <u>4.9</u>	#10 <u>3.9</u>		
Anode Depth					
#11	#12	#13	#14	#15	#16
#17	#18	#19	#20		
Anode Output (Amps)					
#11	#12	#13	#14	#15	#16
#17	#18	#19	#20		
Total Circuit Resistance			No. 8 C.P. Cable Used		
Volts <u>11.6</u>	Amps <u>22.7</u>	Ohms <u>.51</u>	No. 2 C.P. Cable Used		

Remarks: Water at 140' & 280'. Used 300' of 3/4" West pipe.

We are on El Paso Power

El Paso is on our Ground bed
for their sun ray PC well

All Construction Completed

Cody Munk
(Signature)

GROUND BED LAYOUT SKETCH

