

1812-30-045-28942.
18-30-045-10726 Plugged 3836
265-30-045-27993 Plugged.

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit K Sec. 17 Twp 31 Rng 09

Name of Well/Wells or Pipeline Serviced _____

S.J. 32-9 UNITS #18R, #18, + #265

Elevation 6491 Completion Date 10/22/93 Total Depth 494' Land Type F

Casing Strings, Sizes, Types & Depths 10/20 Set 59' of 8" PVC Casing.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 21 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. HIT SOME FRESH WATER AT 85', AND MORE

WATER AT 380'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 494' Depth.

USED 144 SACKS OF ASBURY 218R (7200#)

Depths anodes placed: 463', 455', 448', 441', 434', 427', 420', 413', 406', 266', 259', 195', 188', 171', + 164'.

Depths vent pipes placed: SURFACE TO 494'.

Vent pipe perforations: BOTTOM 380'.

Remarks: _____

OIL CON. DIV.

DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.