

3258

**OCD CATHODIC PROTECTION DEEPWELL GROUND BED REPORT
DATA SHEET: NORTHWESTERN NEW MEXICO**

SUBMIT 2 COPIES TO O.C.D. AZTEC OFFI

OPERATOR: PHILLIPS PETROLEUM CO.
FARMINGTON, NM 87401
PHONE: 599-3400

30-045-29460

RECEIVED
FEB 10 1998
OIL CON. DIV.
DIST. 3

LOCATION INFORMATION

WELLNAME OR PIPELINE SERVED: SJ 32-8 #253

ADDITIONAL WELLS: NA

LEGAL LOCATION G-27-32-8

DATE OF INSTALLATION: 7/11/97

LEASE NUMBER: SF-080412-A

TYPE OF LEASE: FEDERAL

PPCO RECTIFIER NUMBER: FM-605

TOTAL G/B DEPT 420

GROUND BED INFORMATION

CASING SIZE: 8

CASING TYPE: PVC

CASING DEPTH: 20

CASING CEMENT: YES

TOP ANODE: 334

BOTTOM ANODE 400

INDIVIDUAL ANODE DEPTHS 334,340,346,352,358,364,370,376,382,388,394,400

AMOUNT OF COKE: 2000

WATER INFORMATION

WATER DEPTH (1): 260

WATER DEPTH (2): NA

CEMENT PLUGS: NA

OTHER INFORMATION

GAS DEPTH: NA

VENT PIPE DEPTH 420

TOP OF VENT PERFORATIONS: 240

REMARKS: G/B DRILLED 7/97

IF ANY OF THE ABOVE DATA IS UNAVAILABLE, PLEASE INDICATE SO. COPIES OF ALL LOGS, INCLUDING DRILLERS LOGS, WATER ANALYSIS, AND WELL BORE SCHEMATICS SHOULD BE SUBMITTED WHEN AVAILABLE. UNPLUGGED UNABANDONED WELLS ARE TO BE INCLUDED.

*- LAND TYPE MAY BE SHOWN: F-FEDERAL; I-INDIAN; S-STATE; P-FEE
IF FEDERAL OR INDIAN, ADD LEASE NUMBER.

PPCO.GROUNDBED LOG

PHILLIPS PETROLEUM CO.			DEEP WELL CATHODIC PROTECTION GROUNDBED LOG--DATA SHEET									
DRILLED BY: (DRILLER'S NAME AND COMPANY) JACK LEDBETTER - TIERRA DYNAMIC												
LOCATION NAME: 55-32-8# 253				DATE DRILLED: 7-11-97								
LEGAL LOCATION: Sec 27-32N-90W				SIZE AND TYPE OF CASING: 8" P/C								
PPCO ID NO.(FM NO.) 605				DEPTH OF CASING: 30'								
TOTAL DEPTH: 420'				COKE:(CIRCLE) PETR. OR MET. AMOUNT: 2000 LBS.								
DIAMETER OF HOLE: 6 3/4"				TYPE OF ANODES: Anode Division								
COUNTY: San Juan												
COMPLETION INFORMATION:												
DEPTH FT.	LOG	ANODE	DEPTH FT.	LOG	ANODE	DEPTH FT.	LOG	ANODE	WATER DEPTH	VENT PPE PERFS	ISOLA- TION PLUGS	
100			265	1.5		430			1) 260	TOP: 240	1)	
105			270	1.2		435			2)	BTM: 420	2)	
110			275	1.2		440			ANODE#	DEPTH	OUTPUT NO COKE	OUTPUT COKED
115			280	1.1		445						
120			285	1.3		450			1	400	1.3	3.4
125			290	1.5		455			2	394	1.4	3.4
130			295	1.4		460			3	388	1.2	3.9
135			300	1.4		465			4	382	1.2	4.2
140			305	1.1		470			5	376	1.0	4.1
145			310	.8		475			6	370	1.3	4.5
150			315	.7		480			7	364	1.4	5.4
155			320	1.0		485			8	358	1.4	5.5
160			325	1.4		490			9	352	1.2	5.2
165			330	1.3		495			10	346	1.3	5.0
170			335	1.3	12	500			11	340	1.4	5.0
175			340	1.3	11	505			12	334	1.3	4.6
180			345	1.0	10	510			13			
185			350	1.1	9	515			14			
190			355	1.3		520			15			
195			360	1.3	8	525			16			
200	.9		365	1.4	7	530			17			
205	.9		370	1.4	6	535			18			
210	.5		375	1.2	5	540			19			
215	1.1		380	1.0	4	545			20			
220	1.0		385	1.2	3	550			21			
225	1.0		390	1.1		555			22			
230	.9		395	1.2	2	560			23			
235	.6		400	1.3	1	565			24			
240	.3		405	.7		570			25			
245	.2		410	.2		575			26			
250	.2		415	.2		580			27			
255	.2		420	T.D.		585			28			
260	.4		425			590			29			

LOGGING VOLTS: 11.56

VOLTAGE SOURCE: A10

TOTAL AMPS: 12.8

TOTAL G/B RESISTANCE: 190

REMARKS: