

295- 30-039-24716
92- 30-039-06596
189- 30-039-20283 - Plugged.

5004

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator UNOCAL OIL & GAS DIVISION Location: Unit NE Sec. 11 Twp 26N Rng 7W

Name of Well/Wells or Pipeline Serviced Rincon Unit 295, 92 & 189

Elevation 6487' Completion Date 9/30/91 Total Depth 300' Land Type* P

Casing, Sizes, Types & Depths NONE

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A

Depths & thickness of water zones with description of water when possible Fresh, Clear,
Salty, Sulphur, Etc. Just damp-moist at 140' depth

RECEIVED
OCT 25 1991
OIL CON. DIV.
DIST. 3

Depths gas encountered: N/A - NONE

Type & amount of coke breeze used: Carbon metallurgical coke = 2000 lbs

Depths anodes placed: 206', 210', 232', 238', 244', 250', 256', 262', 268' & 275' deep

Depths vent pipes placed: From 0' to 300'

Vent pipe perforations: 1/8" diameter holes from 140' to 300' = 160' perforated

Remarks: First ground bed drilled on this location.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CITY:

WELL NAME:

Bacon Unit #29

LOCATION:

T26N

DATE:

9/30/91

TOTAL VOLTS:

12.49

TOTAL AMP:

8.0

OHMS RESISTANCE:

1.57

												ANODE HEADINGS			
DEEP	100 ANODE	ANODE NO.	DEEP	100 ANODE	ANODE NO.	DEEP	100 ANODE	ANODE NO.	DEEP	100 ANODE	ANODE NO.	NO.	DEPTH	NO COKE	WITH COKE
5			185	.3		365			545			1	275	1.0	2.0
10			190	.3		370			550			2	268	1.4	2.8
15			195	.3		375			555			3	262	2.1	3.7
20			200	.4		380			560			4	256	2.0	3.7
25			205	.5	10	385			565			5	250	1.9	3.2
30			210	.8	9	390			570			6	244	1.2	2.9
35			215	.3		395			575			7	238	1.4	2.8
40			220	.6		400			580			8	232	.9	2.0
45			225	.4		405			585			9	210	.8	1.4
50			230	.6		410			590			10	206	.8	1.4
55			235	1.1	8	415			595						
60			240	1.4	7	420			600						
65			245	.9	8	425			605						
70			250	1.6	6	430			610						
75			255	1.5	5	435			615						
80			260	1.5	4	440			620						
85			265	1.0	3	445			625						
90			270	1.2	2	450			630						
95			275	.9	1	455			635						
100			280	.4		460			640						
105			285	.4		465			645						
110			290	.4		470			650						
115			295	.3		475			655						
120			300	.7	10	480			660						
125			305			485			665						
130			310			490			670						
135			315			495			675						
140	.7		320			500			680						
145	.8		325			505			685						
150	.6		330			510			690						
155	.1		335			515			695						
160	.1		340			520			700						
165	.2		345			525			705						
170	.4		350			530			710						
175	.4		355			535			715						
180	.2		360			540			720						

STATIC
WATER
LEVEL

REMARKS:

110' (1") perforated PVC Vent pipe
140' (1") PVC Vent pipe