

3270

**DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)**

API 30-039-25487

Operator: UNOCAL – Bloomfield, NM Location: Unit G Sec. 11 Twp. 26N Rng. 7W

Name of Well/Wells or Pipeline Serviced: RINCON UNIT 304 DK/MV

Elevation: 6519 GR Completion Date: 12/27/95 Total Depth: 300' Land Type* F

Casing, Sizes, Types & Depths: NONE

If Casing is cemented, show amounts & types used: NONE

If Cement or Bentonite Plugs have been placed, show depths & amounts used: NONE

Depths & thickness of water zones with description of water when possible: WATER AT 220'

Fresh, Clear, Salty, Sulfur, Etc.: CLEAR

Depths gas encountered: NONE

Type & amount of coke breeze used: 3300 LBS., SWB PETROLEUM COKE

Depths anodes placed: 180' 190' 200' 207' 215' 222' 235' 243' 250' 260'

Depths vent pipes placed: 0' – 285', 1" PVC

Vent pipe perforations: 1/8" PERFORATIONS FROM 100' TO 285'

Remarks: FIRST GROUND BED INSTALLED ON THIS LOCATION.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analysis & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F–Federal; I–Indian; S–State; P–Fee
If Federal or Indian, add Lease Number.

RECEIVED
FEB - 5 1996
OIL CON. DIV.
DIST. 3

CPS GROUND BED CONSTRUCTION WORKSHEET

REMARKS (notes for construction log)
2,800 lb of Coke Breeze + 500 lb. of Coke Breeze = 3,300 lb. of Coke Breeze

DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	DEPTH	LOG ANODE	ANODE #	FULL COKE
100			295			490			685			
105			300			495			690			
110			305			500			695			
115			310			505			700			
120			315			510			ANODE	DEPTH	NO	FULL
125			320			515			#		COKE	COKE
130			325			520			1	260	.7	1.4
135			330			525			2	250	1.1	2.5
140			335			530			3	243	1.6	2.5
145			340			535			4	235	1.7	4.8
150			345			540			5	222	1.6	4.0
155	.4		350			545			6	215	1.3	4.8
160	.3		355			550			7	207	1.0	4.1
165	.3		360			555			8	200	1.0	1.6
170	.4		365			560			9	190	.7	1.5
175	.5		370			565			10	180	.7	1.4
180	.7		375			570			11			
185	.7		380			575			12			
190	.7		385			580			13			
195	.7		390			585			14			
200	.6		395			590			15			
205	.7		400			595			16			
210	.6		405			600			17			
215	1.0		410			605			18			
220	1.4		415			610			19			
225	1.5		420			615			20			
230	1.8		425			620			21			
235	1.7		430			625			22			
240	1.5		435			630			23			
245	1.8		440			635			24			
250	.2		445			640			25			
255	1.0		450			645			26			
260	.7		455			650			27			
265	.2		460			655			28			
270	.2		465			660			29			
275	.2		470			665			30			
280	.4		475			670						
285	FAD		480			675						
290			485			680						

COMPANY

DAILY DRILLING REPORT

12/-27

1995

WELL NAME:

304

WELL NUMBER:

304

SECTION:

TOWNSHIP:

HÄNGE:

WATER AT:

FEET:

HOLE MADE:

220'

300'

DESCRIPTION OF FORMATION

[illegible]

REMARKS:

Went to reception at 2.20!

Drilling

Tool Dresser

