

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS

NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

3322

API 30-045-10165

Operator EL PASO FIELD SERVICES Location: Unit B Sec. 34 Twp 31 Rng 9

Name of Well/Wells or Pipeline Served PRITCHARD B #2 #70127

Elevation _____ Completion Date 4-3-97 Total Depth 320 Land Type F NM013686

Casing, Sizes, Types & Depths 8 5/8 - PVC - 80'

If Casing is cemented, show amounts & types used 4 Bags Z. A Type V # 2

If Cement or Bentonite Plugs have been placed, show depths & amounts used _____

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. _____

RECEIVED
MAR - 2 1998

OIL CON. DIV.
DIST. 3

Depths gas encountered: _____

Type & amount of coke breeze used: 40 resco SW 2200 lbs

Depths anodes placed: 185 - 285

Depths vent pipes placed: 300

Vent pipe perforations: 140

Remarks: _____

Darrells

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

* Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

DEEP WELL GROUND BED DATA

DATE April 3, 1997COMPANY EPFS/AmocoCOUNTY San JuanSTATE NMCONTRACT NO. FC-96-1000UNIT NO. 70127LOCATION Pritchard B-2GROUNDBED: DEPTH 320 Ft., DIA. 7 7/8 In., ANODES (10) 2 x 60 SHA-2CASING: SIZE 8 In., DEPTH 20 Ft.

DEPTH FT.	DRILLER'S LOG	RESISTIVITY		ANODE NUMBER	DEPTH TO ANODE TOP	BEFORE COKE	AFTER COKE
		OHMS	AMPS				
5	Casing						
10	"						
15	"						
20	Sand & Clay						
25	"						
30	"						
35	"						
40	Shale		1.4				
45	"		1.4				
50	"		1.4				
55	"		1.4				
60	"		1.5				
65	"		1.3				
70	Blue Sandstone		1.1				
75	"		0.9				
80	"		0.9				
85	"		0.9				
90	"		0.9				
95	"		0.5				
100	"		0.4				
105	"		0.3				
110	"		0.7				
115	"		0.5				
120	"		0.4				
125	"		0.6				
130	"		0.8				
135	"		0.7				
140	"		0.7				
145	"		0.7				
150	Shale		0.8				
155	"		0.7				
160	Sandstone		0.7				
165	"		0.7				
170	"		0.6				
175	"		0.7				
180	Shale		0.8				
185	"		2.3				
190	"		2.4				
195	"		2.7				
200	"		2.6				
205	"		2.5				
210	"		2.4				
215	"		2.3				
220	"		2.3				
225	"		2.2				
230	"		1.9				
235	"		2.0				
240	Shale		2.0				

COMPANY EPFS/Amoco

DATE April 3, 1997

LOCATION Pritchard B-2

UNIT NO. 70127

DEPTH FT	DRILLER'S LOG	RESISTIVITY		ANODE NUMBER	DEPTH TO ANODE TOP	BEFORE COKE	AFTER COKE
		OHMS	AMPS				
245	Shale		2.4	5	245	2.4	7.7
250	"		2.2				
255	"		2.2	4	255	2.1	6.6
260	"		2.2				
265	"		2.0	3	265	2.3	6.2
270	"		2.0				
275	"		2.3	2	275	2.3	6.2
280	"		2.2				
285	"		2.1	1	285	2.2	5.4
290	"		1.8				
295	"		2.0				
300	"						
305	"						
310	"						
315	"						
320	Shale						
325							
330							
335							
340							
345							
350							
355							
360							
365							
370							
375							
380							
385							
390							
395							
400							
405							
410							
415							
420							
425							
430							
435							
440							
445							
450							
455							
460							
465							
470							
475							
480							
485							
490							
495							
500							
505							
510							