

3472

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

(Submit 3 copies to OCD Aztec Office)

30-045-27008

Operator MERIDIAN OIL INC. Location: Unit L Sec. 13 Twp 22 Rng 8Name of Well/Wells or Pipeline Serviced REESE MESA #100

cps 2044w

Elevation 7097' Completion Date 10/13/88 Total Depth 440' Land Type* N/ACasing, Sizes, Types & Depths N/AIf Casing is cemented, show amounts & types used N/AIf Cement or Bentonite Plugs have been placed, show depths & amounts used
N/ADepths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. 210' NO SAMPLEDepths gas encountered: N/AType & amount of coke breeze used: N/ADepths anodes placed: 385', 375', 365', 355', 345', 330', 310', 295', 285', 275'Depths vent pipes placed: 400'Vent pipe perforations: 190'Remarks: gb #1

RECEIVED

MAY 31 1991

OIL CON. DIV
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

MERIDIAN OIL INC.
WELL CASING
CATHODIC PROTECTION CONSTRUCTION REPORT
DAILY LOG

Drilling Log (Attach Hereto) ☐

comp 10-14-88
Completion Date 10-13-88

CPS #	Well Name, Line or Plot:	Work Order #	State:	Ins. Union Check
2044W	Rebo Mesa #100	3248A	600'W = .649V	☒ Good ☐ Bad
Lot #	Anode Size:	Anode Type:	Size Box:	
13-32-8	2" x 60"	Duriron	1 3/4	
Depth Drilled:	Depth Logged:	Drilling Rig Time	Total Lbs. Coke Used	Less Circulation Mat'l Used
440'	400'			
Anode Depth				
# 1 3.85	# 2 3.75	# 3 3.65	# 4 3.55	# 5 3.45
# 6 3.30	# 7 3.10	# 8 2.95	# 9 2.85	# 10 2.75
Anode Output (Amps)				
# 1 3.5	# 2 4.0	# 3 3.4	# 4 3.0	# 5 3.1
# 6 3.9	# 7 3.6	# 8 3.5	# 9 3.9	# 10 4.3
Anode Depth				
# 11	# 12	# 13	# 14	# 15
# 16	# 17	# 18	# 19	# 20
Anode Output (Amps)				
# 11	# 12	# 13	# 14	# 15
# 16	# 17	# 18	# 19	# 20
Total Circuit Resistance			No. 8 C.P. Cable Used	No. 2 C.P. Cable Used
Volt's 12.06	Amps 18.2	Ohms .66		

Remarks: 2 meters at 270', sample would not settle out.
Installed 400' of 1" PVC vent pipe, bottom 190' perforated.

GR 4074.00
Rectifier Size: 40 v 16 A 669.00
Addn'l Depth: 0
Depth Credit: 100' @ 3.50 = 350.00 ✓
Extra Cable: 180' @ .24 = 43.20 ✓
Ditch & 1 Cable: 160' @ .70 = 112.00 ✓
Ditch & 2 Cable: 0
25' Meter Pole: 0
20' Meter Pole: 1 @ 297.00 = 297.00 ✓
10' Stub Pole: 0
Junction Box: 1 @ 225.00 = 225.00 ✓

5070.20
- 253.51
5323.71

All Construction Completed

Calvin Rodman
(Signature)

