

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENTSUBMIT IN DUPLICATE\*  
(See other instructions on reverse side)FOR APPROVED  
OMB NO. 1004-0137

Expires: December 31, 1991

5. LEASE DESIGNATION AND SERIAL NO.

NMSF- 078566-A

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

207 APR 13 PM 3:21

7. UNIT AGREEMENT NAME

RECEIVED

8. FARM OR LEASE NAME, WELL NO.

210 Howell 100

9. API WELL NO.

30-045-33876 -0062

10. FIELD AND POOL, OR WILDCAT

Basin FC/Blanco PC

11. SEC., T., R., M., OR BLOCK AND SURVEY OR AREA

Sec. 34 T28N 68W NMPM

RCOD APR 18 '07

OIL CONS. DIV.

DIST. 3

## WELL COMPLETION OR RECOMPLETION REPORT AND LOG\*

1a. TYPE OF WELL: OIL WELL ☐ GAS WELL ☒ DRY ☐ Other ☐

b. TYPE OF COMPLETION:

NEW WELL ☒ WORK OVER ☐ DEEP-EN ☐ PLUG BACK ☐ DIFF. RESVR ☐ Other ☐

2. NAME OF OPERATOR

BURLINGTON RESOURCES OIL &amp; GAS COMPANY

3. ADDRESS AND TELEPHONE NO.

PO BOX 4289, Farmington, NM 87499 (505) 326-9700

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements)\*

At surface Unit N (SESW) 1040' FSL, 1630' FWL

At top prod. interval reported below Same as above

At total depth Same as above

14. PERMIT NO. DATE ISSUED

12. COUNTY OR PARISH

San Juan

13. STATE

New Mexico

15. DATE SPURRED

11/21/06

16. DATE T.D. REACHED

11/28/06

17. DATE COMPL. (Ready to prod.)

4/3/07

18. ELEVATIONS (DF, RKB, RT, BR, ETC.)\*

GL 5698' KB 5710'

19. ELEV. CASING HEAD

20. TOTAL DEPTH, MD &amp; TVD

2335'

21. PLUG. BACK T.D., MD &amp; TVD

2284'

22. IF MULTIPLE COMPL., HOW MANY\*

2

23. INTERVALS DRILLED BY

yes

ROTARY TOOLS

CABLE TOOLS

24. PRODUCTION INTERVAL (S) OF THIS COMPLETION-TOP, BOTTOM, NAME (MD AND TVD)\*

Basin Fruitland Coal 2038' - 2114'

25. WAS DIRECTIONAL SURVEY MADE

No

26. TYPE ELECTRIC AND OTHER LOGS RUN

Gamma Ray Casing Collars

27. WAS WELL CORED

No

28. CASING RECORD (Report all strings set in well)

CASING SIZE/GRADE	WEIGHT, LB./FT.	DEPTH SET (MD)	HOLE SIZE	TOP OF CEMENT, CEMENTING RECORD	AMOUNT PULLED
7"	20# J-55	228'	8 3/4"	surface; 250sx (320 cf)	surface
4 1/2"	10.5# J-55	2327'	6 1/4"	TOC surface; 290sx (573cf)	DV Tool @1585'

29. LINER RECORD

SIZE	TOP (MD)	BOTTOM (MD)	SACKS CEMENT*	SCREEN (MD)	SIZE	DEPTH SET (MD)	PACKER SET (MD)
					2-3/8"	2182'	

31. PERFORATION RECORD (Interval, size and number)

@2SPF  
2038' - 2058', 2068' - 2074', 2077' - 2083'  
2088' - 2114'.  
Total hole = 116

32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.

2038' - 2114'  
10 bbls 155 HCL Acid, Pumped 3500 gal 25# Xlink  
Pre-pad. Followed by 40824 gal 25# Linear 75% N2  
Foam w/150000# 20/40 Brady Sand & 1395400 SCF N2.

33.

DATE FIRST PRODUCTION		PRODUCTION METHOD (Flowing, gas lift, pumping--size and type of pump)					WELL STATUS (Producing or shut-in)	
SI		Flowing					SI	
DATE OF TEST	HOURS TESTED	CHOKE SIZE	PROD'N FOR TEST PERIOD	OIL-BBL	GAS-MCF	WATER-BBL	GAS-OIL RATIO	
4/3/07	1	1/2"	→		19.62 mcf			
FLOW. TUBING PRESS.	CASING PRESSURE	CALCULATED 24-HOUR RATE	OIL-BBL	GAS-MCF	WATER-BBL	OIL GRAVITY-API (CORR.)		
110#		→		471 mcf/d				

34. DISPOSITION OF GAS (Sold, used for fuel, vented, etc.)

To be sold

TEST WITNESSED BY

35. LIST OF ATTACHMENTS

This is a Basin FC/Blanco PC well being DHC per order # 2412AZ

36. I hereby certify that the foregoing and attached information is complete and correct as determined from all available records

SIGNED D. McCoy, W. McArthur TITLE Regulatory TechnicianDATE 4/4/07

\*(See Instructions and Spaces for Additional Data on Reverse Side)

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

NMOCD

ACCEPTED FOR RECORD

APR 17 2007

FARMINGTON FIELD OFFICE

T. Salinas

Ojo Alamo	1181'	1323'	White, cr-gr ss.	Ojo Alamo	1181'
Kirtland	1323'	1857'	Gry sh interbedded w/tight, gry, fine-gr ss.	Kirtland	1323'
Fruitland	1857'	2129'	Dk gry-gry carb sh, coal, grn silts, light-med gry, tight, fine gr ss.	Fruitland	1857'
Pictured Cliffs	2129'		Bn-Gry, fine grn, tight ss.	Pic.Cliffs	2129'