

30-045-28970

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator Meridian Oil Inc. Location: Unit G Sec. 30 Twp 28 Rng 11

Name of Well/Wells. or Pipeline Serviced _____

RHodes C#100

Elevation _____ Completion Date 9/9/93 Total Depth 485' Land Type I

Casing Strings, Sizes, Types & Depths 7/8 SET 59' OF 8" PVC CASING.

NO GAS, WATER, OR BOULDERS WERE ENCOUNTERED DURING CASING.

If Casing Strings are cemented, show amounts & types used Cemented

WITH 12 SACKS.

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NONE

Depths & thickness of water zones with description of water: Fresh, Clear, Salty, Sulphur, Etc. HIT A DAMP LAYER AT 85' AND FRESH WATER AT 215'. A WATER SAMPLE WAS TAKEN.

Depths gas encountered: NONE

Ground bed depth with type & amount of coke breeze used: 485' DEPTH.

USED 140 SACKS OF ASBURY 218R (7000#)

Depths anodes placed: 475', 468', 461', 454', 445', 438', 432', 382', 376', 343', 333', 307', 164', 153', + 130'.

Depths vent pipes placed: SURFACE TO 485'.

Vent pipe perforations: BOTTOM 370'.

Remarks: _____

RECEIVED

JAN 31 1994

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.