

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO

Operator MORIDIAN OIL Location: Unit Sec 33 Twp 30 Rng 7

Name of Well/Wells or Pipeline Serviced SJ 30-6 #92A

30-039-25409

Elevation Completion Date Total Depth Land Type

Casing Strings, Sizes, Types & Depths 100' of 8" PVC surface

CASING

If Casing Strings are cemented, show amounts & types used yes with

18 BAGS cement

If Cement or Bentonite Plugs have been placed, show depths & amounts used

NO

Depths & thickness of water zones with description of water: Fresh, Clear,

Salty, Sulphur, Etc. Damp 110' WATER 280'

Depths gas encountered: NO

Ground bed depth with type & amount of coke breeze used: 448' deep

with 5700 lbs LoreSCO Type SCW

Depths anodes placed: 435, 425, 370, 360, 351, 310, 275, 265, 255, 245, 238, 230, 210

200, 165

Depths vent pipes placed: 448

Vent pipe perforations: bottom 320'

Remarks:

RECEIVED
FEB 19 1997

OIL CON. DIV.
DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

CPS GROUND BED CONSTRUCTION WORKSHEET

CPS#	P/L NAME(s), NUMBER(s) S.J. 30-6 #92-A					
WD #	TOTAL	VOLTS	AMPS	- OHMS	DATE	NAME
		10.86	16.6	.65	3-10-95	MRW

REMARKS (notes for construction log)

STATIC 600' SE = 806

DAMP 110' (WATER AT 280' Drilled 460' Logged 448'
 perforated bottom 320' 57 bags Loresco

DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	DEPTH	LOG	ANODE	
	ANODE	*		ANODE	*		ANODE	*		ANODE	*	
100			295	.6		490			685			
105			300	.7		495			690			
110			305	.6		500			695			
115			310	.9		505			700			
120			315	.9		510			ANODE	DEPTH	NO	FULLY
125	1.0		320	.6		515			*		COKE	COKE
130	.9		325	.4		520			1	435	1.0	3.2
135	.6		330	.4		525			2	425	1.0	3.4
140	.5		335	.3		530			3	370	1.2	4.5
145	.5		340	.7		535			4	360	1.1	4.6
150	.4		345	.7		540			5	351	1.2	4.3
155	.4		350	.9		545			6	310	1.1	3.4
160	.3		355	1.1		550			7	275	1.0	3.8
165	1.2		360	1.0		555			8	265	1.0	4.0
170	.4		365	1.2		560			9	255	1.0	4.1
175	.3		370	1.2		565			10	245	1.3	4.4
180	.3		375	.7		570			11	238	1.3	6.1
185	.2		380	.5		575			12	230	1.0	4.8
190	.1		385	.5		580			13	210	1.0	3.3
195	.		390	.4		585			14	200	1.2	3.4
200	1.1		395	.4		590			15	165	1.2	3.0
205	1.3		400	.5		595			16			
210	.9		405	.3		600			17			
215	.7		410	.4		605			18			
220	.6		415	.9		610			19			
225	.5		420	.9		615			20			
230	.9		425	.9		620			21			
235	1.3		430	1.2		625			22			
240	1.5		435	1.0		630			23			
245	1.2		440	.6		635			24			
250	.9		445	.4		640			25			
255	1.0		450	.4	448	645			26			
260	.9		455			650			27			
265	.9		460			655			28			
270	.9		465			660			29			
275	1.0		470			665			30			
280	.7		475			670						
285	.6		480			675						
290	.6		485			680						

DISTRIBUTION - original - permanent CPS FILE

copy - Division Corrosion Supervisor

copy - Region Corrosion Specialist