

4393

36-045-12139

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 copies to OCD Aztec Office)

Operator MERIDIAN OIL Location: Unit NE Sec. 7 Twp 30 Rng 8

Name of Well/Wells or Pipeline Serviced HOWELL C #3

cps 14w

Elevation 6039' Completion Date 11/4/61 Total Depth 200' Land Type * N/A

Casing, Sizes, Types & Depths N/A

If Casing is cemented, show amounts & types used N/A

If Cement or Bentonite Plugs have been placed, show depths & amounts used
N/A

Depths & thickness of water zones with description of water when possible:
Fresh, Clear, Salty, Sulphur, Etc. N/A

Depths gas encountered: N/A

Type & amount of coke breeze used: 1560 lbs.

Depths anodes placed: 187', 180', 174', 130', 74', 68'

Depths vent pipes placed: N/A

Vent pipe perforations: N/A

Remarks: gb #1

RECEIVED
MAY 31 1991
OIL CON. DIST. 3

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

SAN JUAN DIVISION
WELL CASING CATHODIC PROTECTION
DAILY CONSTRUCTION
PROGRESS REPORT

DATE 11/4/61

WELL NAME - Howell 3-C

WORK ORDER NO. 184-52028

NUMBER AND DEPTH OF HOLES: #1 200', #2 , #3 , #4 , #5 .

DEPTH OF EACH ANODE: #1 187', #2 180', #3 174', #4 130', #5 74', #6 68', #7
#8 , #9 , #10 .

ANODE RESISTANCES: #1 4.0, #2 4.4, #3 5.4, #4 6.4, #5 3.5, #6 3.9, #7
#8 , #9 , #10 .

TOTAL CIRCUIT RESISTANCE: 1.5 OHMS.

DRILLING LOG: (ATTACH HERETO)

AMOUNT OF COKE BREEZE PLACED IN EACH HOLE: #1 23 Bags ^{1560#} #2 , #3
#4 , #5 .

ANY DIFFICULTIES ENCOUNTERED IN DRILLING:

ROCKS-

LOST CIRCULATION-

CASING INSTALLED-

*Drilled Blind from 140' ON LOST CIRCULATION TIE
3AYS*

DATE ALL CONSTRUCTION COMPLETED .

REMARKS:

*Water truck standby 7 hrs while loading hole.
Unable to get anode #1 any lower
logged & install anode #4 at lowest Resistance 130'*

*Bad Blind spot at 120' upper section of
the hole will probably be dry hole*

Coke 8.3 lbs/lb

ED Paulk
SIGNATURE OF INSPECTOR

MORNING

DAYLIGHT

EVENING

Driller		Total Men In Crew		
FROM	TO	FORMATION	WT-BIT	R.P.M.
0	28	Barren Sub.		
28	41	Heavy Sand	65002	
41	76	Gravelly		
76	82	Gravelly Heavy Clay		

		NO. DC	SIZE	Q	LENG.
BIT NO.		NO. DC	SIZE		LENG.
SERIAL NO.		STANDS			
SIZE	6 1/2"	SINGLES			
TYPE	2	DOWN ON KELLY			
MAKE	WAME	TOTAL DEPTH			
MUD RECORD		MUD, ADDITIVES USED AND RECEIVED			

Time	Wt.	Vis.	
FROM	TO		TIME BREAKDOWN

FROM	TO	TIME	STANDARD
82	130	Brown	130
130	186	Gray	186
186	200	Blue	200

REMARKS -

REMARKS -

REMARKS -
X needed Blind from

140 ft on East Circulation
Tide

3/12/20

2 sacks mud

SIGNED: Toolpusher

Company Supervisor