

DATA SHEET FOR DEEP GROUND BED CATHODIC PROTECTION WELLS
NORTHWESTERN NEW MEXICO
(Submit 3 Copies to OCD Aztec Office)

MB-2

Operator: BLACKWOOD & NICHOLS CO. Location: Unit K, Sec. 14, Twp 31N, Rng 7W.

Name of Well/Wells or Pipeline Serviced NEBU 480

30-045-27722

Elevation 6480' Completion Date 9-2-93 Total Depth 390' Land Type* Surface: F Mineral: NM-03356

Casing, Sizes, Types & Depths 8-5/8" SCH 40 P.V.C. - 100', 7-7/8" Open Hole

If Casing is cemented, show amounts & types used 20 sks Portland Zia I-II

If Cement or Bentonite Plugs have been placed, show depths & amounts used N/A

Depths & thickness of water zones with description of water when possible:

Fresh, Clear, Salty, Sulphur, Etc. No Water

Depths gas encountered: N/A

Type & amount of coke breeze used: Asbury Flo-Coke, 4,650#

Depths anodes placed: 200' - 297' (10)

Depths vent pipes placed: TD to 4' Above Ground Level

Vent pipe perforations: Bottom - 280'

Remarks: Groundbed located 217' N 90° E from NEBU 480 wellhead.

If any of the above data is unavailable, please indicate so. Copies of all logs, including Drillers Log, Water Analyses & Well Bore Schematics should be submitted when available. Unplugged abandoned wells are to be included.

*Land Type may be shown: F-Federal; I-Indian; S-State; P-Fee.
If Federal or Indian, add Lease Number.

Signed by: James K. Ahlberg

Title: Operations Engineer

Date: 11/19/93

BLACKWOOD & NICHOLS CATHODIC GROUND BED DRILLERS REPORT

S. 14 T31N 14

EPTH	STRATA	NOTES	DEPTH	STRATA	NOTES
5'					
10'					
15'	N ↑				
20'	N				
25'	S ↓				
30'	S				
35'	S				
40'	S				
45'	S				
50'	X				
55'	X				
60'					
65'					
70'	L				
75'	V				
80'	A				
85'	H				
90'	S				
95'					
100	v				

ILLER geese mauling

INSPECTOR Joe Matyszek

BLACKWOOD & NICHOLS CATHODIC GROUND BED DRILLERS REPORT

MB-2 WELL # N.E.B.U. #480

L S 14 T 31 R

[illegible]

ILLER

INSPECTOR